

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The ASI TVU001 is Designed for

FEATURES:

-
-
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	1.2 A
V_{CB0}	45 V
V_{CEO}	25 V
V_{EBO}	3.5 V
P_{DISS}	19.4 W @ T _C = 25 °C
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	12 °C/W

PACKAGE STYLE .280 4L STUD

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	1.010 / 25.65	1.055 / 26.80
B	.220 / 5.59	.230 / 5.84
C	.270 / 6.86	.285 / 7.24
D	.003 / 0.08	.007 / 0.18
E	.117 / 2.97	.137 / 3.48
F	.572 / 14.53	
G	.130 / 3.30	
H	.245 / 6.22	.255 / 6.48
I	.640 / 16.26	
J	.175 / 4.45	.217 / 5.51
K	.275 / 6.99	.285 / 7.24

ORDER CODE: ASI10643

CHARACTERISTICS T_C = 25 °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CB0}	I _C = 2.0 mA	45			V
BV_{CER}	I _C = 40 mA R _{BE} = 10 Ω	50			V
BV_{CEO}	I _C = 40 mA	24			V
BV_{EBO}	I _E = 0.5 mA	3.5			V
I_{CB0}	V _{CB} = 28 V			0.45	mA
h_{FE}	V _{CE} = 5.0 V I _C = 200 mA	200		120	---
C_{OB}	V _{CB} = 20 V f = 1.0 MHz			7	pF
P_G IMD₁	V _{CE} = 20 V I _C = 440 mA f = 860 MHz P _{OUT} = 1.0 W	10 -60			dB dBc