

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The ASI TVU150A is Designed for

FEATURES:

- Input Matching Network
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	25 A
V_{CB0}	60 V
V_{CEO}	30 V
V_{EBO}	3.0 V
P_{DISS}	310 W @ T _C = 25 °C
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	0.55 °C/W

PACKAGE STYLE .450 BAL FLG(B)

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.373 / 9.47	.385 / 9.78
B	.205 / 5.21	
C	.120 / 3.25	.130 / 3.30
D	.411 / 10.44	.421 / 10.69
E	.825 / 20.96	.865 / 21.97
F	.525 / 13.34	.535 / 13.59
G	1.255 / 31.88	1.265 / 32.18
H	1.675 / 42.55	1.685 / 42.80
I	.002 / 0.05	.006 / 0.15
J	.095 / 2.41	.105 / 2.67
K	.115 / 2.92	.135 / 3.43
L		.250 / 6.35
M	.445 / 11.30	.457 / 11.61

ORDER CODE: ASI10653

CHARACTERISTICS T_C = 25 °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CB0}	I _C = 100 mA	60			V
BV_{CEO}	I _C = 100 mA	30			V
BV_{EBO}	I _E = 10 mA	3.0			V
I_{CES}	V _{CE} = 28 V			10	mA
h_{FE}	V _{CE} = 5.0 V I _C = 3.0 A	15		70	---
C_{OB}	V _{CB} = 28 V f = 1.0 MHz			100	pF
P_G	V _{CE} = 28 V I _C = 2 X 500 mA f = 860 MHz P _{OUT} = 150 W	6.5			dB