

# NPN SILICON RF POWER TRANSISTOR

**DESCRIPTION:**

The ASI VMB80-28S is Designed for

**FEATURES:**

- 
- 
- **Omnigold™** Metalization System

**MAXIMUM RATINGS**

<b>I<sub>C</sub></b>	9.0 A
<b>V<sub>CB0</sub></b>	65 V
<b>V<sub>CEO</sub></b>	36 V
<b>V<sub>EBO</sub></b>	4.0 V
<b>P<sub>DISS</sub></b>	103 W @ T <sub>C</sub> = 25 °C
<b>T<sub>J</sub></b>	-65 °C to +200 °C
<b>T<sub>STG</sub></b>	-65 °C to +150 °C
<b>θ<sub>JC</sub></b>	1.05 °C/W

**PACKAGE STYLE .380 4L STUD**

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.220 / 5.59	.230 / 5.84
B	.980 / 24.89	
C	.370 / 9.40	.385 / 9.78
D	.004 / 0.10	.007 / 0.18
E	.320 / 8.13	.330 / 8.38
F	.100 / 2.54	.130 / 3.30
G	.450 / 11.43	.490 / 12.45
H	.090 / 2.29	.100 / 2.54
I	.155 / 3.94	.175 / 4.45
J		.750 / 19.05

**ORDER CODE: ASI10749**

**CHARACTERISTICS** T<sub>C</sub> = 25 °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
<b>BV<sub>CEO</sub></b>	I <sub>C</sub> = 200 mA	36			<b>V</b>
<b>BV<sub>CES</sub></b>	I <sub>C</sub> = 20mA	65			<b>V</b>
<b>BV<sub>EBO</sub></b>	I <sub>E</sub> = 10 mA	4.0			<b>V</b>
<b>I<sub>CES</sub></b>	V <sub>CE</sub> = 28 V			10	<b>mA</b>
<b>h<sub>FE</sub></b>	V <sub>CE</sub> = 5.0 V      I <sub>C</sub> = 500 mA	5.0		--	<b>---</b>
<b>C<sub>OB</sub></b>	V <sub>CB</sub> = 28 V      f = 1.0 MHz			200	<b>pF</b>
<b>P<sub>G</sub></b>	V <sub>CC</sub> = 28 V      P <sub>OUT</sub> = 80 W      f = 88 MHz	10			<b>dB</b>
<b>η<sub>C</sub></b>			60		<b>%</b>