



# AZ100LVEL16VT ARIZONA MICROTEK, INC.

## ECL/PECL Oscillator Gain Stage & Buffer with Selectable Enable

### FEATURES

- High Bandwidth for  $\geq 1\text{GHz}$
- **Similar Operation as AZ100LVEL16VR Except in Disabled Condition:  $Q_{HG}$  is High**
- Operating Range of 3.0V to 5.5V
- Minimizes External Components
- Selectable Enable Polarity and Threshold (CMOS/TTL or PECL)
- Available in a 3x3 mm or 2x2 mm MLP Package

### PACKAGE AVAILABILITY

PACKAGE	PART NO.	MARKING
MLP 8 (2x2x.9)	AZ100LVEL16VTMA	TMA
MLP 8 (2x2x.9)	AZ100LVEL16VTMAR1	TMA
MLP 8 (2x2x.75)	AZ100LVEL16VTNA	TNA
MLP 8 (2x2x.75)	AZ100LVEL16VTNAR1	TNA
MLP 8 (2x2x.9)	AZ100LVEL16VTMB	TMB
MLP 8 (2x2x.9)	AZ100LVEL16VTMBR1	TMB
MLP 8 (2x2x.75)	AZ100LVEL16VTNB	TNB
MLP 8 (2x2x.75)	AZ100LVEL16VTNBR1	TNB
MLP 16	AZ100LVEL16VTL	AZM16T
MLP 16 T&R	AZ100LVEL16VTLR1	AZM16T
MLP 16 T&R	AZ100LVEL16VTLR2	AZM16T
DIE	AZ100LVEL16VTX	N/A

### DESCRIPTION

The AZ100LVEL16VT is a specialized oscillator gain stage with high gain output buffer including an enable. The  $Q_{HG}/\bar{Q}_{HG}$  outputs have a voltage gain several times greater than the  $Q/\bar{Q}$  outputs.

#### MLP 16, 3x3 mm Package (L) or DIE (X)

The AZ100LVEL16VTL provides a selectable enable that allows continuous oscillator operation. See truth table below for enable function. If Enable pull-up is desired in the CMOS mode, an external  $\leq 20\text{ k}\Omega$  resistor connecting EN to  $V_{CC}$  will override the on-chip pull-down resistor. When disabled the  $Q_{HG}$  output is forced high and the  $\bar{Q}_{HG}$  output is forced low. The AZ100LVEL16VT also provides a  $V_{BB}$  and 470  $\Omega$  internal bias resistors from D to  $V_{BB}$  and  $\bar{D}$  to  $V_{BB}$ . The  $V_{BB}$  pin can support 1.5 mA sink/source current. Bypassing  $V_{BB}$  to ground with a 0.01  $\mu\text{F}$  capacitor is recommended.

The outputs Q and  $\bar{Q}$  each have a selectable on-chip pull-down current source. See truth table below for current source functions. External resistors may also be used to increase pull-down current to a maximum total of 25 mA.

Outputs  $Q_{HG}$  and  $\bar{Q}_{HG}$  each have an optional on-chip pull-down current source of 10 mA. When pad/pin  $V_{EEP}$  is left open (NC), the output current sources are disabled and the  $Q_{HG}/\bar{Q}_{HG}$  operate as standard PECL/ECL. When  $V_{EEP}$  is connected to  $V_{EE}$ , the current sources are activated. The  $Q_{HG}/\bar{Q}_{HG}$  pull-down current can be decreased, by using a resistor to connect  $V_{EEP}$  to  $V_{EE}$ . (See graph on page 5)

#### MLP 8, 2x2 mm Package (M,N) with A & B Bonding Options

The MLP 8, 2x2mm versions of the AZ100LVEL16VT operate in the PECL/ECL mode with an enable input (EN) controlling the  $Q_{HG}/\bar{Q}_{HG}$  outputs. When the EN input is LOW, the  $\bar{Q}$  and  $Q_{HG}/\bar{Q}_{HG}$  outputs follow the input. When EN is HIGH, the  $Q_{HG}$  output is forced high and the  $\bar{Q}_{HG}$  output is forced low.

The Q,  $Q_{HG}$ , and  $\bar{Q}_{HG}$  current sources are disabled, while the  $\bar{Q}$  output operates with a 4 mA current source to VEE. This is accomplished by internal bonding of CS-SEL, EN-SEL and  $V_{EEP}$ .

For the MLP 8, 2x2mm version B, the  $\bar{D}$  input is internally tied directly to the VBB pin and the D input is tied to the VBB pin through a 470  $\Omega$  internal bias resistor. In the MLP 8, 2x2mm version A, both D and  $\bar{D}$  inputs are brought out and tied to the VBB pin through 470  $\Omega$  internal bias resistors.

NOTE: Specifications in the ECL/PECL tables are valid when thermal equilibrium is established.

# AZ100LEVEL16VT


## ENABLE TRUTH TABLE

EN-SEL (MLP 16 or DIE)	EN	Q/Q̄	Q <sub>HG</sub>	Q̄ <sub>HG</sub>
NC	PECL Low, V <sub>EE</sub> or NC	Data	Data	Data
NC	PECL High or V <sub>CC</sub>	Data	High	Low
V <sub>EE</sub> *	CMOS Low or V <sub>EE</sub>	Data	High	Low
V <sub>EE</sub> *	CMOS High or V <sub>CC</sub>	Data	Data	Data
V <sub>EE</sub> *	NC, no external pull-up	Data	High	Low
V <sub>EE</sub> *	NC, with ≤20kΩ to V <sub>CC</sub>	Data	Data	Data

\*Connections to V<sub>CC</sub> or V<sub>EE</sub> must be less than 1Ω.

## PIN DESCRIPTION

PIN	FUNCTION
D/D̄	Data Inputs
Q/Q̄	Data Outputs
Q <sub>HG</sub> /Q̄ <sub>HG</sub>	Data Outputs w/High Gain
V <sub>BB</sub>	Reference Voltage Output
EN-SEL	Selects Enable Logic
EN	Enable Input
CS-SEL	Selects Q and Q̄ Current Source Magnitude
V <sub>EHP</sub>	Optional Q <sub>HG</sub> and Q̄ <sub>HG</sub> Current Sources
V <sub>EE</sub>	Negative Supply
V <sub>CC</sub>	Positive Supply



MLP16

## CURRENT SOURCE TRUTH TABLE (MLP 16 or DIE)

CS-SEL	Q	Q̄
NC	4mA typ.	4mA typ.
V <sub>EE</sub> *	8mA typ.	8mA typ.
V <sub>CC</sub> *	0	4mA typ.

\*Connections to V<sub>CC</sub> or V<sub>EE</sub> must be less than 1Ω.

**Absolute Maximum Ratings are those values beyond which device life may be impaired.**

Symbol	Characteristic	Rating	Unit
V <sub>CC</sub>	PECL Power Supply (V <sub>EE</sub> = 0V)	0 to +8.0	Vdc
V <sub>I</sub>	PECL Input Voltage (V <sub>EE</sub> = 0V)	0 to +6.0	Vdc
V <sub>EE</sub>	ECL Power Supply (V <sub>CC</sub> = 0V)	-8.0 to 0	Vdc
V <sub>I</sub>	ECL Input Voltage (V <sub>CC</sub> = 0V)	-6.0 to 0	Vdc
I <sub>OUT</sub>	Output Current Q <sub>HG</sub> /Q̄ <sub>HG</sub> --- Continuous	50	mA
	--- Surge	100	
	Output Current Q/Q̄ --- Continuous	25	
	--- Surge	50	
T <sub>A</sub>	Operating Temperature Range	-40 to +85	°C
T <sub>STG</sub>	Storage Temperature Range	-65 to +150	°C

# AZ100LVEL16VT

## 100K ECL DC Characteristics ( $V_{EE} = -3.0V$ to $-5.5V$ , $V_{CC} = GND$ )

Symbol	Characteristic	-40°C		0°C		25°C		85°C		Unit
		Min	Max	Min	Max	Min	Max	Min	Max	
$V_{OH}$	Output HIGH Voltage <sup>2</sup>	-1045	-835	-995	-835	-995	-835	-995	-835	mV
$V_{OH}$	Output HIGH Voltage <sup>4</sup>	-1085	-880	-1025	-880	-1025	-880	-1025	-880	mV
$V_{OL}$	Output LOW Voltage <sup>2,4</sup>	-1925	-1555	-1900	-1620	-1900	-1620	-1900	-1620	mV
$V_{IH}$	Input HIGH Voltage D/ $\bar{D}$ , EN (PECL) EN (CMOS/TTL)	-1165 $V_{EE}+2000$	-880 $V_{CC}$	-1165 $V_{EE}+2000$	-880 $V_{CC}$	-1165 $V_{EE}+2000$	-880 $V_{CC}$	-1165 $V_{EE}+2000$	-880 $V_{CC}$	mV
$V_{IL}$	Input LOW Voltage D/ $\bar{D}$ , EN (PECL) EN (CMOS/TTL)	-1810 $V_{EE}$	-1475 $V_{EE} + 800$	-1810 $V_{EE}$	-1475 $V_{EE} + 800$	-1810 $V_{EE}$	-1475 $V_{EE} + 800$	-1810 $V_{EE}$	-1475 $V_{EE} + 800$	mV
$V_{BB}$	Reference Voltage	-1390	-1250	-1390	-1250	-1390	-1250	-1390	-1250	mV
$I_{IL}$	Input LOW Current EN <sup>3</sup>	0.5		0.5		0.5		0.5		$\mu A$
$I_{IH}$	Input HIGH Current EN <sup>3</sup>		150		150		150		150	$\mu A$
$I_{EE}$	Power Supply Current <sup>1</sup>		48		48		48		54	mA

1. Specified with  $V_{EEP}$  and CS-SEL open for MLP16 and DIE. Subtract 4mA for MLP8.
2. Specified with  $V_{EEP}$  and CS-SEL connected to  $V_{EE}$  for MLP16 and DIE only.
3. Specified with EN-SEL open for MLP16 and DIE only.
4. Specified with  $Q_{HG}/\bar{Q}_{HG}$  connected with  $50 \Omega$  to  $V_{CC} - 2V$  for MLP 8 only.

## 100K LVPECL DC Characteristics ( $V_{EE} = GND$ , $V_{CC} = +3.3V$ )

Symbol	Characteristic	-40°C		0°C		25°C		85°C		Unit
		Min	Max	Min	Max	Min	Max	Min	Max	
$V_{OH}$	Output HIGH Voltage <sup>1,3</sup>	2255	2465	2305	2465	2305	2465	2305	2465	mV
$V_{OH}$	Output HIGH Voltage <sup>1,5</sup>	2215	2420	2275	2420	2275	2420	2275	2420	mV
$V_{OL}$	Output LOW Voltage <sup>1,3,5</sup>	1375	1745	1400	1655	1480	1680	1400	1680	mV
$V_{IH}$	Input HIGH Voltage D/ $\bar{D}$ , EN (PECL) <sup>1</sup> EN (CMOS/TTL)	2135 2000	2420 $V_{CC}$	2135 2000	2420 $V_{CC}$	2135 2000	2420 $V_{CC}$	2135 2000	2420 $V_{CC}$	mV
$V_{IL}$	Input LOW Voltage D/ $\bar{D}$ , EN (PECL) <sup>1</sup> EN (CMOS/TTL)	1490 GND	1825 800	1490 GND	1825 800	1490 GND	1825 800	1490 GND	1825 800	mV
$V_{BB}$	Reference Voltage <sup>1</sup>	1910	2050	1910	2050	1910	2050	1910	2050	mV
$I_{IL}$	Input LOW Current EN <sup>4</sup>	0.5		0.5		0.5		0.5		$\mu A$
$I_{IH}$	Input HIGH Current EN <sup>4</sup>		150		150		150		150	$\mu A$
$I_{EE}$	Power Supply Current <sup>2</sup>		48		48		48		54	mA

1. For supply voltages other than 3.3V, use the ECL table values and ADD supply voltage value.
2. Specified with  $V_{EEP}$  and CS-SEL open for MLP16 and DIE. Subtract 4mA for MLP8.
3. Specified with  $V_{EEP}$  and CS-SEL connected to  $V_{EE}$  for MLP16 and DIE only.
4. Specified with EN-SEL open for MLP16 and DIE only.
5. Specified with  $Q_{HG}/\bar{Q}_{HG}$  connected with  $50 \Omega$  to  $V_{CC} - 2V$  for MLP 8 only.

## 100K PECL DC Characteristics ( $V_{EE} = GND$ , $V_{CC} = +5.0V$ )

Symbol	Characteristic	-40°C		0°C		25°C		85°C		Unit
		Min	Max	Min	Max	Min	Max	Min	Max	
$V_{OH}$	Output HIGH Voltage <sup>1,3</sup>	3955	4165	4005	4165	4005	4165	4005	4165	mV
$V_{OH}$	Output HIGH Voltage <sup>1,5</sup>	3915	4120	3975	4120	3975	4120	3975	4120	mV
$V_{OL}$	Output LOW Voltage <sup>1,3,5</sup>	3075	3445	3100	3338	3100	3338	3100	3338	mV
$V_{IH}$	Input HIGH Voltage D/ $\bar{D}$ , EN (PECL) <sup>1</sup> EN (CMOS/TTL)	3835 2000	4120 $V_{CC}$	3835 2000	4120 $V_{CC}$	3835 2000	4120 $V_{CC}$	3835 2000	4120 $V_{CC}$	mV
$V_{IL}$	Input LOW Voltage D/ $\bar{D}$ , EN (PECL) <sup>1</sup> EN (CMOS/TTL)	3190 GND	3525 800	3190 GND	3525 800	3190 GND	3525 800	3190 GND	3525 800	mV
$V_{BB}$	Reference Voltage <sup>1</sup>	3610	3750	3610	3750	3610	3750	3610	3750	mV
$I_{IL}$	Input LOW Current EN <sup>4</sup>	0.5		0.5		0.5		0.5		$\mu A$
$I_{IH}$	Input HIGH Current EN <sup>4</sup>		150		150		150		150	$\mu A$
$I_{EE}$	Power Supply Current <sup>2</sup>		48		48		48		54	mA


1. For supply voltages other than 5.0V, use the ECL table values and ADD supply voltage value.
2. Specified with  $V_{EEP}$  and CS-SEL open for MLP16 and DIE. Subtract 4mA for MLP8.
3. Specified with  $V_{EEP}$  and CS-SEL connected to  $V_{EE}$  for MLP16 and DIE only.
4. Specified with EN-SEL open for MLP16 and DIE only.
5. Specified with  $Q_{HG}/\bar{Q}_{HG}$  connected with  $50 \Omega$  to  $V_{CC} - 2V$  for MLP 8 only.

# AZ100LVEL16VT

## AC Characteristics ( $V_{EE} = -3.0V$ to $-5.5V$ ; $V_{CC} = GND$ or $V_{EE} = GND$ ; $V_{CC} = +3.0V$ to $+5.5V$ )


Symbol	Characteristic	-40°C			0°C			25°C			85°C			Unit
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
$t_{PLH} / t_{PHL}$	Propagation Delay D to Q/ $\bar{Q}$ Outputs <sup>1</sup> (SE)			400			400			400			430	ps
	D to $Q_{HG}/\bar{Q}_{HG}$ Outputs <sup>1</sup> (SE)			550			550			550			630	
$t_{SKEW}$	Duty Cycle Skew <sup>2</sup> (SE)		5	20		5	20		5	20		5	20	ps
$V_{PP}$	Minimum Input Swing <sup>3</sup> DIFF SE	80 160			80 160			80 160			80 160			mV
$t_r / t_f$	Output Rise/Fall Times <sup>1</sup> (20% - 80%)	100		260	100		260	100		260	100		260	ps

- For MLP16 output specified with  $V_{EEP}$  and CS-SEL connected to  $V_{EE}$  with an AC coupled  $50\Omega$  load. For MLP8, AC coupled  $50\Omega$  on  $\bar{Q}$  to  $V_{CC} - 2V$  and DC coupled  $50\Omega$  to  $V_{CC} - 2V$  on  $Q_{HG}/\bar{Q}_{HG}$ .
- Duty cycle skew is the difference between a  $t_{PLH}$  and  $t_{PHL}$  propagation delay through a device.
- $V_{PP}$  is the minimum peak-to-peak input swing for which AC parameters guaranteed. The device has a voltage gain of  $\approx 20$  to Q/ $\bar{Q}$  outputs and a voltage gain of  $\approx 100$  to  $Q_{HG}/\bar{Q}_{HG}$  outputs.



TIMING DIAGRAM


MLP 16  
3x3 mm



TOP VIEW



Bottom Center Pad may be left open or tied to  $V_{EE}$

ADJUSTABLE HIGH GAIN OUTPUT CURRENT




# AZ100LVEL16VT


## LOGIC DIAGRAMS AND PINOUTS FOR 2x2mm PACKAGE



**EN operation on the versions A and B follows the PECL functionality, see Timing Diagram above.**



**Bottom Center Pad is the  $V_{EE}$  return.**




**Bottom Center Pad may be left open or tied to  $V_{EE}$ . Pin 4 is the  $V_{EE}$  return.**

**AZ100LVEL16VT**

**DIE PAD COORDINATES**


**AZ100LVEL16VT DIE:**




**PAD CENTER COORDINATES**

NAME	PAD DESIGNATION	X(Microns)	Y(Microns)
A	D	-342.5	312.5
B	$\bar{D}$	-342.5	144.5
C	$V_{BB}$	-342.5	-87.0
D	EN	-342.5	-255.0
E	$V_{EE}$	-33.5	-312.5
F	$V_{EEP}$	126.5	-312.5
G	EN-SEL	312.5	-248.5
H	$\bar{Q}_{HG}$	312.5	-98.5
I	$Q_{HG}$	312.5	51.5
J	CS-SEL	312.5	201.5
K	$V_{CC}$	302.5	342.5
L	Q	142.5	342.5
M	$\bar{Q}$	-140.5	342.5


**PACKAGE DIAGRAM  
MLP 8 DUAL 2x2mm**



TOP VIEW



BOTTOM VIEW



SIDE VIEW

**Note: All dimensions are in mm**



**PACKAGE DIAGRAM  
MLP 16**



- NOTES:
1. DIMENSIONING AND TOLERANCING CONFORM TO ASME T14-1994. THE TERMINAL #1 AND PAD NUMBERING CONVENTION SHALL CONFORM TO JESD 95-1 SPP-012.
  3. DIMENSION  $b$  APPLIES TO METALLIZED PAD AND IS MEASURED BETWEEN 0.25 AND 0.30mm FROM THE PAD TIP.
  4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS

DIM	MILLIMETERS	
	MIN	MAX
A	0.80	1.00
A1	0.00	0.05
A3	0.25 REF	
b	0.18	0.30
D	2.90	3.10
D2	0.25	1.95
E	2.90	3.10
E2	0.25	1.95
e	0.50 BSC	
L	0.30	0.50
aaa	0.25	
bbb	0.10	
ccc	0.10	

## AZ100LVEL16VT

Arizona Microtek, Inc. reserves the right to change circuitry and specifications at any time without prior notice. Arizona Microtek, Inc. makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Arizona Microtek, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Arizona Microtek, Inc. does not convey any license rights nor the rights of others. Arizona Microtek, Inc. products are not designed, intended or authorized for use as components in systems intended to support or sustain life, or for any other application in which the failure of the Arizona Microtek, Inc. product could create a situation where personal injury or death may occur. Should Buyer purchase or use Arizona Microtek, Inc. products for any such unintended or unauthorized application, Buyer shall indemnify and hold Arizona Microtek, Inc. and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Arizona Microtek, Inc. was negligent regarding the design or manufacture of the part.