


### Features

- Low Forward Voltage Drop
- Guard Ring Die Construction for Transient Protection
- Ideally Suited for Automatic Assembly
- Low Power Loss, High Efficiency
- Plastic Material: UL Flammability Classification Rating 94V-0

### Mechanical Data

- Case: SMA, Molded Plastic
- Terminals: Solder Plated Terminal - Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band or Cathode Notch
- Weight: 0.064 grams (approx.)
- Marking: B130L



SMA		
Dim	Min	Max
A	2.29	2.92
B	4.00	4.60
C	1.27	1.63
D	0.15	0.31
E	4.80	5.59
G	0.10	0.20
H	0.76	1.52
J	2.01	2.62
All Dimensions in mm		

### Maximum Ratings and Electrical Characteristics @ T<sub>A</sub> = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

Characteristic	Symbol	B130L	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage Blocking Voltage @ I <sub>R</sub> = 1mA	V <sub>RRM</sub> V <sub>RWM</sub> V <sub>R</sub>	30	V
RMS Reverse Voltage	V <sub>R(RMS)</sub>	21	V
Average Rectified Output Current @ T <sub>T</sub> = 105°C	I <sub>O</sub>	1.0	A
Peak Repetitive Forward Current (Note 2)	I <sub>FRM</sub>	2.0	A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave Superimposed on Rated Load (JEDEC Method)	I <sub>FSM</sub>	25	A
Forward Voltage @ I <sub>F</sub> = 1.0A, T <sub>J</sub> = 25°C @ I <sub>F</sub> = 2.0A, T <sub>J</sub> = 25°C @ I <sub>F</sub> = 1.0A, T <sub>J</sub> = 100°C @ I <sub>F</sub> = 2.0A, T <sub>J</sub> = 100°C	V <sub>FM</sub>	0.41 0.47 0.35 0.43	V
Peak Reverse Current @ V <sub>R</sub> = 15V, T <sub>A</sub> = 25°C @ V <sub>R</sub> = 30V, T <sub>A</sub> = 25°C @ V <sub>R</sub> = 15V, T <sub>A</sub> = 100°C @ V <sub>R</sub> = 30V, T <sub>A</sub> = 100°C	I <sub>RM</sub>	0.4 1.0 12 25	mA
Typical Junction Capacitance (Note 1)	C <sub>j</sub>	110	pF
Typical Thermal Resistance Junction to Terminal	R <sub>θJT</sub>	27	K/W
Operating Temperature Range	T <sub>j</sub>	-55 to +125	°C
Storage Temperature Range	T <sub>STG</sub>	-55 to +150	°C

Notes: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.  
2. At Rated V<sub>R</sub>, Square Wave, 25KHz, T<sub>C</sub> = 40°C.




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Max Non-Repetitive Peak Fwd Surge Current




Fig. 4 Typical Junction Capacitance




Fig. 5 Typical Reverse Characteristics