

# PTB 20248


## 0.7 Watts, 1465–1513 MHz

### Cellular Radio RF Power Transistor

#### Description

The 20248 is a class A, NPN, common emitter RF power transistor intended for 26 Vdc operation from 1465 to 1513 MHz. Rated at 0.7 watts minimum output power, it may be used for both CW and PEP applications. Ion implantation, nitride surface passivation and gold metallization are used to ensure excellent device reliability. 100% lot traceability is standard.

- 0.7 Watts, 26 Vdc
- Class A Characteristics
- Surface Mountable
- Available in Tape and Reel
- Gold Metallization
- Silicon Nitride Passivated



#### Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-Emitter Voltage	$V_{CER}$	55	Vdc
Collector-Base Voltage	$V_{CBO}$	55	Vdc
Emitter-Base Voltage (collector open)	$V_{EBO}$	4	Vdc
Collector Current (continuous)	$I_C$	0.5	Adc
Total Device Dissipation at $T_{flange} = 25^{\circ}C$ Above 25°C derate by	$P_D$	5.4 0.031	Watts W/°C
Storage Temperature Range	$T_{STG}$	-40 to +150	°C
Thermal Resistance ( $T_{flange} = 70^{\circ}C$ )	$R_{\theta JC}$	32.3	°C/W

## Electrical Characteristics (100% Tested)


Characteristic	Conditions	Symbol	Min	Typ	Max	Units
Breakdown Voltage C to E	$I_B = 0\text{ A}, I_C = 5\text{ mA}, R_{BE} = 22\ \Omega$	$V_{(BR)CER}$	55	—	—	Volts
Breakdown Voltage C to E	$V_{BE} = 0\text{ V}, I_C = 5\text{ mA}$	$V_{(BR)CES}$	55	—	—	Volts
Breakdown Voltage E to B	$I_C = 0\text{ A}, I_E = 5\text{ mA}$	$V_{(BR)EBO}$	4	5	—	Volts
DC Current Gain	$V_{CE} = 5\text{ V}, I_C = 200\text{ mA}$	$h_{FE}$	20	—	—	—

## RF Specifications (100% Tested)

Characteristic	Symbol	Min	Typ	Max	Units
<b>Gain</b> ( $V_{CC} = 26\text{ Vdc}, P_{out} = 0.2\text{ W}, I_{CQ} = 120\text{ mA}, f = 1513\text{ MHz}$ )	$G_{pe}$	10	12	—	dB
<b>Power Output at 1 dB Compression</b> ( $V_{CC} = 26\text{ Vdc}, I_{CQ} = 120\text{ mA}, f = 1513\text{ MHz}$ )	P-1dB	0.7	0.9	—	Watts
<b>Load Mismatch Tolerance</b> ( $V_{CC} = 26\text{ Vdc}, P_{out} = 0.7\text{ W}, I_{CQ} = 120\text{ mA}, f = 1513\text{ MHz}$ —all phase angles at frequency of test)	$\Psi$	—	—	5:1	—

## Impedance Data (data shown for fixed-tuned broadband circuit)

( $V_{CC} = 26\text{ Vdc}, P_{out} = 0.7\text{ W}, I_{CQ} = 120\text{ mA}$ )



Frequency MHz	Z Source		Z Load	
	R	jX	R	jX
1465	6.50	6.10	10.60	37.30
1489	5.70	7.60	10.70	38.90
1513	5.00	8.90	10.90	40.50

