


LOGIC LEVEL TRIAC

TO220-AB 	On-State Current 4 Amp	Gate Trigger Current 5 mA to 10 mA
	Off-State Voltage 200 V ÷ 600 V	
<p>This series of TRIACs uses a high performance PNPN technology.</p> <p>These parts are intended for general purpose AC switching applications with highly inductive loads.</p>		

Absolute Maximum Ratings, according to IEC publication No. 134

SYMBOL	PARAMETER	CONDITIONS	Min.	Max.	Unit
$I_{T(RMS)}$	RMS On-state Current	All Conduction Angle, $T_C = 110^\circ C$		4	A
I_{TSM}	Non-repetitive On-State Current	Full Cycle, 60 Hz		33	A
I_{TSM}	Non-repetitive On-State Current	Full Cycle, 50 Hz		30	A
I^2t	Fusing Current	$t_p = 10 \text{ ms}$, Half Cycle		4.5	A^2s
I_{GM}	Peak Gate Current	$20 \mu\text{s}$ max. $T_j = 125^\circ C$		4	A
$P_{G(AV)}$	Average Gate Power Dissipation	$T_j = 125^\circ C$		1	W
di/dt	Critical rate of rise of on-state current	$I_G = 2x I_{GT}$, $t_r = 100\text{ns}$ $f = 120 \text{ Hz}$, $T_j = 125^\circ C$	50		$\text{A}/\mu\text{s}$
T_j	Operating Temperature		-40	+125	$^\circ C$
T_{stg}	Storage Temperature		-40	+150	$^\circ C$

SYMBOL	PARAMETER	VOLTAGE			Unit
		B	D	M	
V_{DRM}	Repetitive Peak Off State Voltage	200	400	600	V
V_{RRM}					

LOGIC LEVEL TRIAC

Electrical Characteristics

SYMBOL	PARAMETER	CONDITIONS	Quadrant		SENSITIVITY					Unit
					04	05	07	08	09	
$I_{GT}^{(1)}$	Gate Trigger Current	$V_D = 12 \text{ V}_{DC}$, $R_L = 33 \Omega$, $T_j = 25^\circ\text{C}$ $V_D = V_{DRM}$,	Q1-Q3 Q4	MAX MAX	5	5	5	10	10	mA
						5	7		10	mA
I_{DRM}/I_{RRM}	Off-State Leakage Current	$V_R = V_{RRM}$, $T_j = 125^\circ\text{C}$ $T_j = 25^\circ\text{C}$		MAX MAX			1			mA
							5			μA
$V_{to}^{(2)}$	Threshold Voltage	$T_j = 125^\circ\text{C}$		MAX			0.9			V
$R_d^{(2)}$	Dynamic Resistance	$T_j = 125^\circ\text{C}$		MAX			120			m
$V_{TM}^{(2)}$	On-state Voltage	$I_T = 5.5 \text{ Amp}$, $t_p = 380 \mu\text{s}$, $T_j = 25^\circ\text{C}$		MAX			1.6			V
V_{GT}	Gate Trigger Voltage	$V_D = 12 \text{ V}_{DC}$, $R_L = 33 \Omega$, $T_j = 25^\circ\text{C}$	Q1-Q4 ⁽³⁾	MAX			1.3			V
V_{GD}	Gate Non Trigger Voltage	$V_D = V_{DRM}$, $R_L = 3.3\text{K}$, $T_j = 125^\circ\text{C}$			MIN		0.2			V
$I_H^{(2)}$	Holding Current	$I_T = 100 \text{ mA}$, Gate open, $T_j = 25^\circ\text{C}$		MAX	15	15	10	15	20	mA
I_L	Latching Current	$I_G = 1.2 I_{GT}$, $T_j = 25^\circ\text{C}$	Q1,Q3,Q4 ⁽⁴⁾ Q2	MAX MAX	10	10	10	25	20	mA
					20	20	15	30	40	
$dv/dt^{(2)}$	Critical Rate of Voltage Rise	$V_D = 0.67 \times V_{DRM}$, Gate open $T_j = 125^\circ\text{C}$		MIN	10	10	20	40	20	V/ μs
$(di/dt)c^{(2)}$	Critical Rate of Current Rise	$(dv/dt)c = 0.1 \text{ V}/\mu\text{s}$ $(dv/dt)c = 10 \text{ V}/\mu\text{s}$ without snubber	$T_j = 125^\circ\text{C}$	MIN MIN MIN	1.5	1.5	1.8	2.7	2.5	A/ms
					-	-	0.9	2.0	-	
					-	-	-	-	-	
$R_{th(j-c)}$	Thermal Resistance Junction-Case						2.6			$^\circ\text{C}/\text{W}$
$R_{th(j-a)}$	Thermal Resistance Junction-Ambient						60			$^\circ\text{C}/\text{W}$

(1) Minimum I_{GT} is guaranteed at 5% of I_{GT} max.


(2) For either polarity of electrode MT2 voltage with reference to electrode MT1.

(3) Q4 for 4 Quadrant Triacs

Q3 for 3 Quadrant Triacs

(4) Only for 4 Quadrant Triacs

PART NUMBER INFORMATION



LOGIC LEVEL TRIAC

Fig. 1: Maximum power dissipation versus RMS on-state current (full cycle).




Fig. 3: Relative variation of thermal impedance versus pulse duration.




Fig. 5: Surge peak on-state current versus number of cycles




Fig. 2: RMS on-state current versus case temperature (full cycle).




Fig. 4: On-state characteristics (maximum values)





Fig. 6: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10\text{ms}$, and corresponding value of I^2t .



LOGIC LEVEL TRIAC

Fig. 7: Relative variation of gate trigger current, holding current and latching versus junction temperature (typical values)






Fig. 8: Relative variation of critical rate of decrease of main current versus junction temperature



PACKAGE MECHANICAL DATA TO-220AB (Plastic)



REF.	DIMENSIONS		
	Milimeters		
	Min.	Nominal	Max.
A	15.20		15.90
a1		3.75	
a2	13.00		14.00
B	10.00		10.40
b1	0.61		0.88
b2	1.23		1.32
C	4.40		4.60
c1	0.49		0.70
c2	2.40		2.72
e	2.40		2.70
F	6.20		6.60
I	3.75		3.85
I4	15.80	16.40	16.80
L	2.65		2.95
I2	1.14		1.70
I3	1.14		1.70
M		2.60	