



MBRB1035 THRU MBRB1060

SCHOTTKY RECTIFIER

Reverse Voltage - 35 to 60 Volts

Forward Current - 10.0 Amperes

TO-263AB



Dimensions in inches and (millimeters)

FEATURES

- ◆ Plastic package has Underwriters Laboratory Flammability Classifications 94V-0
- ◆ Metal silicon junction, majority carrier conduction
- ◆ Low power loss, high efficiency
- ◆ High current capability, low forward voltage drop
- ◆ High surge capability
- ◆ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- ◆ Guardring for overvoltage protection
- ◆ High temperature soldering in accordance with CECC 802 / Reflow guaranteed



MECHANICAL DATA

Case: JEDEC TO-263AB molded plastic body

Terminals: Leads solderable per MIL-STD-750, Method 2026

Polarity: As marked

Mounting Position: Any

Weight: 0.08 ounces, 2.24 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

	SYMBOLS	MBRB1035	MBRB1045	MBRB1050	MBRB1060	UNITS
Maximum repetitive peak reverse voltage	V _{RRM}	35	45	50	60	Volts
Maximum working peak reverse voltage	V _{RWM}	35	45	50	60	Volts
Maximum DC blocking voltage	V _{DC}	35	45	50	60	Volts
Maximum average forward rectified current (SEE FIG. 1)	I _(AV)			10.0		Amps
Peak repetitive forward current at T _C =135°C (square wave 20 KHz)	I _{FRM}			20.0		Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}			150.0		Amps
Peak repetitive reverse surge current (NOTE 1)	I _{RRM}	1.0		0.5		Amps
Voltage rate of change (rated V _R)	dv/dt		10,000			V/μs
Maximum instantaneous forward voltage at (NOTE 2) I _F =10A, T _C =25°C I _F =10A, T _C =125°C I _F =20A, T _C =25°C I _F =20A, T _C =125°C	V _F	- 0.57 0.84 0.72		0.80 0.70 0.95 0.85		Volts
Maximum instantaneous reverse current at rated DC blocking voltage T _C = 25°C (NOTE 2) T _C =125°C	I _R		0.10 15.0			mA
Maximum thermal resistance, junction to case	R _{θJC}		2.0			°C/W
Operating junction temperature range	T _J		-65 to +150			°C
Storage temperature range	T _{STG}		-65 to +175			°C

NOTES:

(1) 2.0μs pulse width, f=1.0 KHz

(2) Pulse test: 300μs pulse width, 1% duty cycle

RATINGS AND CHARACTERISTIC CURVES MBRB1035 THRU MBRB1060

