


# BYM12-50 THRU BYM12-400 EGL41A THRU EGL41G

**SURFACE MOUNT GLASS PASSIVATED JUNCTION FAST EFFICIENT RECTIFIER**  
Reverse Voltage - 50 to 400 Volts      Forward Current - 1.0 Ampere



1st band denotes type and positive end (cathode)

Dimensions in inches and (millimeters)

\* Glass-plastic encapsulation is covered by

Patent No. 3,996,602 and brazed-lead assembly to Patent No. 3,930,306



## FEATURES

- ◆ Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- ◆ Capable of meeting environmental standards of MIL-S-19500
- ◆ For surface mount applications
- ◆ High temperature metallurgically bonded construction
- ◆ Glass passivated cavity-free junction
- ◆ Fast switching for high efficiency
- ◆ High temperature soldering guaranteed: 450°C/5 seconds at terminals. Complete device submersible temperature of 260°C for 10 seconds in solder bath



## MECHANICAL DATA

**Case:** JEDEC DO-213AB molded plastic over glass body

**Terminals:** Plated terminals, solderable per MIL-STD-750, Method 2026

**Polarity:** Two bands indicate cathode end -1st band denotes device type and 2nd band denotes repetitive peak reverse voltage rating

**Mounting Position:** Any

**Weight:** 0.116 ounce, 0.0046 gram

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

	SYMBOLS	BYM12 -50	BYM12 -100	BYM12 -150	BYM12 -200	BYM12 -300	BYM12 -400	UNITS
Fast efficient device: 1st band is green		EGL41A	EGL41B	EGL41C	EGL41D	EGL41F	EGL41G	
Polarity color bands (2cnd band)		GRAY	RED	PINK	ORANGE	BROWN	YELLOW	
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	50	100	150	200	300	400	Volts
Maximum RMS voltage	V <sub>RMS</sub>	35	70	105	140	210	280	Volts
Maximum DC blocking voltage	V <sub>DC</sub>	50	100	150	200	300	400	Volts
Maximum average forward rectified current at T <sub>T</sub> =75°C	I(AV)	1.0						Amp
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	30.0						Amps
Maximum instantaneous forward voltage at 1.0A	V <sub>F</sub>	1.0				1.25		Volts
Maximum DC reverse current at rated DC blocking voltage	I <sub>R</sub>	5.0				50.0		μA
		T <sub>A</sub> =25°C						
		T <sub>A</sub> =125°C						
Maximum reverse recovery time (NOTE 1)	t <sub>rr</sub>	50.0						ns
Typical junction capacitance (NOTE 2)	C <sub>J</sub>	20.0				14.0		pF
Maximum thermal resistance (NOTE 3)	R <sub>θJA</sub>	60.0						°C/W
(NOTE 4)	R <sub>θJT</sub>	30.0						
Operating junction and storage temperature range	T <sub>J</sub> , T <sub>STG</sub>	-65 to +175						°C

### NOTES:

(1) Reverse recovery test conditions: I<sub>F</sub>=0.5A, I<sub>R</sub>=1.0A, I<sub>rr</sub>=0.25A


(2) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts

(3) Thermal resistance from junction to ambient, 0.24 x 0.24" (6.0 x 6.0mm) copper pads to each terminal


(4) Thermal resistance from junction to terminal, 0.24 x 0.24" (6.0 x 6.0mm) copper pads to each terminal

# RATINGS AND CHARACTERISTIC CURVES BYM12-50 THRU BYM12-400, EGL41A THRU EGL41G


**FIG. 1 - MAXIMUM FORWARD CURRENT DERATING CURVE**




**FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT**




**FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS**



**FIG. 4 - TYPICAL REVERSE CHARACTERISTICS**



**FIG. 5 - TYPICAL JUNCTION CAPACITANCE**



**FIG. 6 - TYPICAL TRANSIENT THERMAL IMPEDANCE**

