

1x5MM(RECTANGULAR TYPE)(GAP) LED LAMP


1x5MM (Rectangular Type) (Gap)
LED Lamp

Test Condition

V_r = 5V

I_f = 20mA

I_f = 10mA (MCD)




Dimensions in mm

Maximum Ratings (T_a = 25 °C)

	Symbol	Value	Unit
Reverse Voltage	V _R	5	Volts
Reverse Current		10	µA (V _r = 5V)
Operating Temperature	T _{amb}	-40 to 85	°C
Storage Temperature	T _S	-40 to 85	°C

Electrical and Electronic Characteristic

Part No.	Colour	Wave Length λ P(nm)	Δλ (nm)	Pd (mv)	I _f (mA)	Peak I _f (mA)	V _f (V)			Rec I _f (mA)	I _v (mad)	
							Min.	Typ.	Max.		Min.	Typ.
ST1002DR	Red Diffused	700	90	45	10	35	1.7	2.1	2.8	5-10	0.4	1.0
ST1002DG	Green Diffused	565	30	45	10	35	1.7	2.1	2.8	10-20	0.8	1.0
ST1002DY	Yellow Diffused	585	35	45	10	35	1.7	2.0	2.8	10-20	0.7	1.0



SEMTECH ELECTRONICS LTD.
(wholly owned subsidiary of HONEY TECHNOLOGY LTD.)

