

**J110, J110A****N-Channel Silicon Junction Field-Effect Transistor**

- Choppers
- Commutators
- Analog Switches

**Absolute maximum ratings at  $T_A = 25^\circ\text{C}$** 

|  |                           |
|--|---------------------------|
| Reverse Gate Source & Reverse Gate Drain Voltage | - 25 V                    |
| Continuous Forward Gate Current                  | 50 mA                     |
| Continuous Device Power Dissipation              | 360 mW                    |
| Power Derating                                   | 3.27 mW/ $^\circ\text{C}$ |

At 25°C free air temperature:

## Static Electrical Characteristics

|                                   |                             | J110  |     | J110A |     | Unit | Process NJ450                                       |  |
|-----------------------------------|-----------------------------|-------|-----|-------|-----|------|---|--|
|                                   |                             | Min   | Max | Min   | Max |      | Test Conditions                                     |  |
| Gate Source Breakdown Voltage     | $V_{(\text{BR})\text{GSS}}$ | - 25  |     | - 25  |     | V    | $I_G = - 1 \mu\text{A}, V_{DS} = \emptyset\text{V}$ |  |
| Gate Reverse Current              | $I_{GSS}$                   |       | - 3 |       | - 3 | nA   | $V_{GS} = - 15\text{V}, V_{DS} = \emptyset\text{V}$ |  |
| Gate Source Cutoff Voltage        | $V_{GS(\text{OFF})}$        | - 0.5 | - 4 | - 0.5 | - 4 | V    | $V_{DS} = 5\text{V}, I_D = 1 \mu\text{A}$           |  |
| Drain Saturation Current (Pulsed) | $I_{DSS}$                   | 10    |     | 10    |     | mA   | $V_{DS} = 15\text{V}, V_{GS} = \emptyset\text{V}$   |  |
| Drain Cutoff Current              | $I_{D(\text{OFF})}$         |       | 3   |       | 3   | nA   | $V_{DS} = 5\text{V}, V_{GS} = - 10\text{V}$         |  |

## Dynamic Electrical Characteristics

|                                      |                     |  |    |  |    |          |   |                     |
|--------------------------------------|---------------------|--|----|--|----|----------|---|---------------------|
| Drain Source ON Resistance           | $r_{ds(\text{on})}$ |  | 18 |  | 25 | $\Omega$ | $V_{GS} = \emptyset, V_{DS} \leq 0.1\text{V}$       | $f = 1 \text{ kHz}$ |
| Drain Gate Capacitance               | $C_{gd}$            |  | 15 |  | 15 | pF       | $V_{DS} = \emptyset\text{V}, V_{GS} = - 10\text{V}$ | $f = 1 \text{ MHz}$ |
| Source Gate Capacitance              | $C_{gs}$            |  | 15 |  | 15 | pF       | $V_{DS} = \emptyset\text{V}, V_{GS} = - 10\text{V}$ | $f = 1 \text{ MHz}$ |
| Drain Gate + Source Gate Capacitance | $C_{gd} + C_{gs}$   |  | 85 |  | 85 | pF       | $V_{DS} = V_{GS} = \emptyset\text{V}$               | $f = 1 \text{ MHz}$ |

## Switching Characteristics

|                     |                     | Typ | Typ |    | J110                 | J110A |          |
|---------------------|---------------------|-----|-----|----|----------------------|-------|----------|
| Turn ON Delay Time  | $t_{d(\text{on})}$  | 4   | 4   | ns | $V_{DD}$             | 1.5   | V        |
| Rise Time           | $t_r$               | 1   | 1   | ns |                      |       |          |
| Turn OFF Delay Time | $t_{d(\text{off})}$ | 6   | 6   | ns |                      |       |          |
| Fall Time           | $t_f$               | 30  | 30  | ns |                      |       |          |
|                     |                     |     |     |    | $V_{GS(\text{OFF})}$ | - 5   | - 5      |
|                     |                     |     |     |    | $R_L$                | 150   | 150      |
|                     |                     |     |     |    |                      |       | $\Omega$ |



1000 N. Shiloh Road, Garland, TX 75042  
 (972) 487-1287 FAX (972) 276-3375

**TO-226AA Package**

Dimensions in Inches (mm)

**Pin Configuration**

1 Drain, 2 Source, 3 Gate

**Surface Mount**

SMPJ110, SMPJ110A

[www.interfet.com](http://www.interfet.com)