

J176, J177

P-Channel Silicon Junction Field-Effect Transistor

- Choppers
- Commutators
- Analog Switches

Absolute maximum ratings at $T_A = 25^\circ\text{C}$

Reverse Gate Source & Reverse Gate Drain Voltage	- 30 V
Continuous Forward Gate Current	50 mA
Continuous Device Power Dissipation	360 mW
Power Derating	3.27 mW/°C

At 25°C free air temperature:

Static Electrical Characteristics

		J176		J177		Unit	Process PJ99	
		Min	Max	Min	Max		Test Conditions	
Gate Source Breakdown Voltage	$V_{(BR)GSS}$	30		30		V	$I_G = 1 \mu\text{A}, V_{DS} = 0\text{V}$	
Gate Reverse Current	I_{GSS}		1		1	nA	$V_{GS} = 20\text{V}, V_{DS} = 0\text{V}$	
Gate Source Cutoff Voltage	$V_{GS(OFF)}$	1	4	0.8	2.25	V	$V_{DS} = -15\text{V}, I_D = -10\text{nA}$	
Drain Saturation Current (Pulsed)	I_{DSS}	- 2	- 35	- 1.5	- 20	mA	$V_{DS} = -15\text{V}, V_{GS} = 0\text{V}$	
Drain Cutoff Current	$I_{D(OFF)}$		- 1		- 1	nA	$V_{DS} = -15\text{V}, V_{GS} = 10\text{V}$	

Dynamic Electrical Characteristics

		Max		Max		Unit	Test Conditions
Drain Source ON Resistance	$r_{ds(on)}$	250		300			

Dynamic Electrical Characteristics

		Typ		Typ		Unit	Test Conditions
Drain Gate Capacitance	C_{gd}	5.5		5.5			
Source Gate Capacitance	C_{gs}	5.5		5.5		pF	$V_{DS} = 0\text{V}, V_{GS} = 10\text{V}$ f = 1 MHz
Drain Gate + Source Gate Capacitance	$C_{gd} + C_{gs}$	32		32		pF	$V_{DS} = V_{GS} = 0\text{V}$ f = 1 MHz

Switching Characteristics

						J176	J177	
Turn ON Delay Time	$t_{d(on)}$	15		20				ns
Rise Time	t_r	20		25		V_{DD}	- 6	- 6
Turn OFF Delay Time	$t_{d(off)}$	15		20		$V_{GS(OFF)}$	6	3
Fall Time	t_f	20		25		R_L	5.6k	10k
						$V_{GS(ON)}$	\emptyset	\emptyset

TO-226AA Package

Dimensions in Inches (mm)

Pin Configuration

1 Drain, 2 Gate, 3 Source

Surface Mount

SMPJ176, SMPJ177