



# SD1053C..L SERIES

## FAST RECOVERY DIODES

## Hockey Puk Version

### Features

- High power FAST recovery diode series
- 2.0 to 3.0  $\mu$ s recovery time
- High voltage ratings up to 3000V
- High current capability
- Optimized turn on and turn off characteristics
- Low forward recovery
- Fast and soft reverse recovery
- Press-puk encapsulation
- Case style conform to JEDEC DO-200AB (B-PUK)
- Maximum junction temperature 150°C

920A  
1050A



case style DO-200AB (B-PUK)

### Typical Applications

- Snubber diode for GTO
- High voltage free-wheeling diode
- Fast recovery rectifier applications

### Major Ratings and Characteristics

Parameters	SD1053C..L		Units
	S20	S30	
I <sub>F(AV)</sub>	1050	920	A
@ T <sub>hs</sub>	55	55	°C
I <sub>F(RMS)</sub>	1940	1700	A
I <sub>FSM</sub>	15000	13000	A
@ 50Hz	15700	13610	A
@ 60Hz			
V <sub>RRM</sub> range	1800 to 2500	1800 to 3000	V
t <sub>rr</sub>	2.0	3.0	$\mu$ s
@ T <sub>J</sub>	25	25	°C
T <sub>J</sub>	- 40 to 150		°C

## SD1053C..L Series

---

### ELECTRICAL SPECIFICATIONS

#### Voltage Ratings

Type number	Voltage Code	$V_{RRM}$ , maximum repetitive peak reverse voltage V	$V_{RSM}$ , maximum non-repetitive peak rev. voltage V	$I_{RRM}$ max. @ $T_J = T_J$ max. mA
SD1053C..S20L	18	1800	1900	50
	22	2200	2300	
	25	2500	2600	
SD1053C..S30L	18	1800	1900	50
	22	2200	2300	
	25	2500	2600	
	28	2800	2900	
	30	3000	3100	

#### Forward Conduction

Parameter	SD1053C..L		Units	Conditions
	S20	S30		
$I_{F(AV)}$ Max. average forward current @ heatsink temperature	1050(450)	920(390)	A	180° conduction, half sine wave
	55 (85)	55 (85)	°C	Double side (single side) cooled
$I_{F(RMS)}$ Max. RMS forward current	1940	1700	A	@ 25°C heatsink temperature double side cooled
$I_{FSM}$ Max. peak, one-cycle forward, non-repetitive surge current	15000	13000	A	t = 10ms No voltage reapplied
	15700	13610		
	12620	10930		
	13210	11450		
$I^2t$ Maximum $I^2t$ for fusing	1125	845	KA <sup>2</sup> s	t = 10ms 100% $V_{RRM}$ reapplied
	1027	772		
	796	598		
	727	546		
$I^{2\sqrt{t}}$ Maximum $I^{2\sqrt{t}}$ for fusing	11250	8450	KA <sup>2</sup> /s	t = 0.1 to 10ms, no voltage reapplied
$V_{F(TO)1}$ Low level value of threshold voltage	1.34	1.51	V	(16.7% x π x $I_{F(AV)}$ < I < π x $I_{F(AV)}$ ), $T_J = T_J$ max.
$V_{F(TO)2}$ High level value of threshold voltage	1.48	1.67		(I > π x $I_{F(AV)}$ ), $T_J = T_J$ max.
$r_{f1}$ Low level value of forward slope resistance	0.37	0.50	mΩ	(16.7% x π x $I_{F(AV)}$ < I < π x $I_{F(AV)}$ ), $T_J = T_J$ max.
$r_{f2}$ High level value of forward slope resistance	0.33	0.45		(I > π x $I_{F(AV)}$ ), $T_J = T_J$ max.
$V_{FM}$ Max. forward voltage drop	1.90	2.26	V	$I_{pk} = 1500A$ , $T_J = T_J$ max, $t_p = 10ms$ sinusoidal wave

SD1053C..L Series




Fig. 3 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 5 - Current Ratings Characteristics




Fig. 6 - Current Ratings Characteristics




Fig. 7 - Current Ratings Characteristics




Fig. 8 - Current Ratings Characteristics

## SD1053C..L Series

---




Fig. 9 - Forward Power Loss Characteristics




Fig. 10 - Forward Power Loss Characteristics




Fig. 11 - Forward Power Loss Characteristics




Fig. 12 - Forward Power Loss Characteristics




Fig. 13 - Maximum Non-repetitive Surge Current  
Single and Double Side Cooled




Fig. 14 - Maximum Non-repetitive Surge Current  
Single and Double Side Cooled

SD1053C..L Series




Fig. 15 - Maximum Non-repetitive Surge Current  
Single and Double Side Cooled




Fig. 16 - Maximum Non-repetitive Surge Current  
Single and Double Side Cooled




Fig. 17 - Forward Voltage Drop Characteristics




Fig. 18 - Forward Voltage Drop Characteristics




Fig. 19 - Thermal Impedance  $Z_{thJ-hs}$  Characteristic

## SD1053C..L Series

---




Fig. 20 - Typical Forward Recovery Characteristics




Fig. 21 - Typical Forward Recovery Characteristics




Fig. 22 - Recovery Time Characteristics



Fig. 23 - Recovery Charge Characteristics




Fig. 24 - Recovery Current Characteristics




Fig. 25 - Recovery Time Characteristics




Fig. 26 - Recovery Charge Characteristics




Fig. 27 - Recovery Current Characteristics

SD1053C..L Series




Fig. 28 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 29 - Frequency Characteristics




Fig. 30 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 31 - Frequency Characteristics




Fig. 32 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 33 - Frequency Characteristics

## SD1053C..L Series

---




Fig. 34 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 35 - Frequency Characteristics




Fig. 36 - Maximum Total Energy Loss Per Pulse Characteristics




Fig. 37 - Frequency Characteristics




Fig. 38 - Maximum Total Energy Loss Per Pulse Characteristics





Fig. 39 - Frequency Characteristics

## SD1053C..L Series

### Recovery Characteristics

Code	$T_J = 25^\circ\text{C}$	Test conditions			Max. values @ $T_J = 150^\circ\text{C}$			
		$I_{pk}$ Square Pulse (A)	$di/dt$ (A/ $\mu\text{s}$ )	$V_r$ (V)	$t_{rr}$ @ 25% $I_{RRM}$ ( $\mu\text{s}$ )	$Q_{rr}$ ( $\mu\text{C}$ )	$I_{rr}$ (A)	
S20	2.0	1000	100	-50	4.0	400	180	
S30	3.0	1000	100	-50	4.5	550	230	

### Thermal and Mechanical Specifications

Parameter	SD1053C..L		Units	Conditions
	S20	S30		
$T_J$ Max. junction operating temperature range	-40 to 150		°C	
$T_{stg}$ Max. storage temperature range	-40 to 150			
$R_{thJ-hs}$ Max. thermal resistance, case junction to heatsink	0.073 0.031		K/W	DC operation single side cooled DC operation double side cooled
F Mounting force, $\pm 10\%$	14700 (1500)		N (Kg)	
wt Approximate weight	255		g	
Case style	DO-200AB(B-PUK)		See Outline Table	

### $\Delta R_{thJ-hs}$ Conduction

(The following table shows the increment of thermal resistance  $R_{thJ-hs}$  when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction		Rectangular conduction		Units	Conditions
	Single Side	Double Side	Single Side	Double Side		
180°	0.009	0.008	0.006	0.006	K/W	$T_J = T_{J \text{ max.}}$
120°	0.011	0.011	0.011	0.011		
90°	0.014	0.014	0.015	0.015		
60°	0.020	0.021	0.021	0.022		
30°	0.036	0.036	0.036	0.036		

### Ordering Information Table

Device Code						
1	2	3	4	5	6	7
SD	105	3	C	30	S30	L
(1)	(2)	(3)	(4)	(5)	(6)	(7)
1 - Diode	2 - Essential part number	3 - Fast recovery	4 - C = Ceramic Puk	5 - Voltage code: Code x 100 = $V_{RRM}$ (See Voltage Ratings table)	6 - $t_{rr}$ code	7 - L = Puk Case DO-200AB(B-PUK)

## SD1053C..L Series

### Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics