



**HiPerFAST™ IGBT
Lightspeed™ Series**
IXGH 12N90C

V_{CES} = 900 V
 I_{C25} = 24 A
 $V_{CES(sat)}$ = 3.0 V
 $t_{fi(ty)}$ = 70 ns



Symbol	Test Conditions	Maximum Ratings		TO-247
V_{CES}	T_J = 25°C to 150°C	900	V	
V_{CGR}	T_J = 25°C to 150°C; $R_{GE} = 1 \text{ M}\Omega$	900	V	
V_{GES}	Continuous	±20	V	
V_{GEM}	Transient	±30	V	
I_{C25}	T_c = 25°C	24	A	
I_{C90}	T_c = 90°C	12	A	
I_{CM}	T_c = 25°C, 1 ms	48	A	
SSOA (RBSOA)	$V_{GE} = 15 \text{ V}$, $T_{VJ} = 125^\circ\text{C}$, $R_g = 33 \Omega$ Clamped inductive load, $L = 300 \mu\text{H}$	$I_{CM} = 24$ @ 0.8 V_{CES}	A	
P_c	T_c = 25°C	100	W	
T_J		-55 ... +150	°C	
T_{JM}		150	°C	
T_{stg}		-55 ... +150	°C	
M_d	Mounting torque with screw M3 Mounting torque with screw M3.5	0.45/4 0.55/5	Nm/lb.in. Nm/lb.in.	
Maximum lead temperature for soldering 1.6 mm (0.062 in.) from case for 10 s		300	°C	
Weight		6	g	



G = Gate, C = Collector,
E = Emitter, TAB = Collector

Features

- Very high frequency IGBT
- New generation HDMOS™ process
- International standard package JEDEC TO-247
- High peak current handling capability

Symbol	Test Conditions	Characteristic Values		
		($T_J = 25^\circ\text{C}$, unless otherwise specified)	min.	typ.
BV_{CES}	$I_c = 250 \mu\text{A}$, $V_{GE} = 0 \text{ V}$	600		V
$V_{GE(th)}$	$I_c = 250 \mu\text{A}$, $V_{GE} = V_{GE}$	2.5		5.0 V
I_{CES}	$V_{CE} = V_{CES}$ $V_{GE} = 0 \text{ V}$	$T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$	100 1.5	μA mA
I_{GES}	$V_{CE} = 0 \text{ V}$, $V_{GE} = \pm 20 \text{ V}$		±100	nA
$V_{CE(sat)}$	$I_c = I_{CE90}$, $V_{GE} = 15 \text{ V}$		3.0	V

Applications


- PFC circuit
- AC motor speed control
- DC servo and robot drives
- Switch-mode and resonant-mode power supplies
- High power audio amplifiers

Advantages

- Fast switching speed
- High power density

Symbol	Test Conditions	Characteristic Values		
		($T_J = 25^\circ\text{C}$, unless otherwise specified)	min.	typ.
g_{fs}	$I_C = I_{C90}$; $V_{CE} = 10 \text{ V}$, Pulse test, $t \leq 300 \mu\text{s}$, duty cycle $\leq 2 \%$	5	10	S
C_{ies} C_{oes} C_{res}	$V_{CE} = 25 \text{ V}$, $V_{GE} = 0 \text{ V}$, $f = 1 \text{ MHz}$	780	pF	
		60	pF	
		15	pF	
Q_g Q_{ge} Q_{gc}	$I_C = I_{C90}$, $V_{GE} = 15 \text{ V}$, $V_{CE} = 0.5 V_{CES}$	33	nC	
		10	nC	
		12	nC	
$t_{d(on)}$ t_{ri} $t_{d(off)}$ t_{fi} E_{off}	Inductive load, $T_J = 25^\circ\text{C}$ $I_C = I_{C90}$, $V_{GE} = 15 \text{ V}$, $L = 300 \mu\text{H}$ $V_{CE} = 0.8 \cdot V_{CES}$, $R_G = R_{off} = 22 \Omega$ Remarks: Switching times may increase for V_{CE} (Clamp) $> 0.8 \cdot V_{CES}$, higher T_J or increased R_G	20	ns	
		20	ns	
		135	200	ns
		70	180	ns
		0.32	0.70	mJ
$t_{d(on)}$ t_{ri} E_{on} $t_{d(off)}$ t_{fi} E_{off}	Inductive load, $T_J = 125^\circ\text{C}$ $I_C = I_{C90}$, $V_{GE} = 15 \text{ V}$, $L = 300 \mu\text{H}$ $V_{CE} = 0.8 \cdot V_{CES}$, $R_G = R_{off} = 22 \Omega$ Remarks: Switching times may increase for V_{CE} (Clamp) $> 0.8 \cdot V_{CES}$, higher T_J or increased R_G	20	ns	
		20	ns	
		0.15	mJ	
		200	ns	
		150	ns	
R_{thJC} R_{thCK}		0.70	mJ	
			1.25 K/W	
			0.25 K/W	

TO-247 AD (IXGH) Outline



Dim.	Millimeter Min.	Millimeter Max.	Inches Min.	Inches Max.
A	19.81	20.32	0.780	0.800
B	20.80	21.46	0.819	0.845
C	15.75	16.26	0.610	0.640
D	3.55	3.65	0.140	0.144
E	4.32	5.49	0.170	0.216
F	5.4	6.2	0.212	0.244
G	1.65	2.13	0.065	0.084
H	-	4.5	-	0.177
J	1.0	1.4	0.040	0.055
K	10.8	11.0	0.426	0.433
L	4.7	5.3	0.185	0.209
M	0.4	0.8	0.016	0.031
N	1.5	2.49	0.087	0.102