

Special Products

ATO™ Resistor



Specifications

Operating Temp.: -20°C to +85°C

Resistor Value: Optional

Power Rating: 1/4 W Max

Body Material: Thermoplastic

Term. Material: C.R.S. (Ni/Zn Plated)

Term. Retention: 25 N

ATO™ Diode



Specifications

Operating Temp.: -40°C to +85°C

Diode Rating: 1.0 A

Max P.I.V.: Optional

Body Material: Thermoplastic

Term. Material: C.R.S. (Ni/Zn Plated)

Term. Retention: 25 N

MINI™ Resistor



Specifications

Operating Temp.: -40°C to +85°C

Resistor Value: Optional


Power Rating: 1/4 Max

Body Material: Thermoplastic

Term. Material: C.R.S. (Ni/Zn Plated)

Term. Retention: 25 N

MINI™ Diode



Specifications

Operating Temp.: -40°C to +85°C

Diode Rating: 1.0 A

Max P.I.V.: Optional

Body Material: Thermoplastic

Term. Material: C.R.S. (Ni/Zn Plated)

Term. Retention: 25 N

ATO™ Shunt



Specifications


Operating Temp.: -40°C to +125°C

Maximum Continuous Load Rating: 35 A

Body Material: Thermoplastic
(UL 94V0 Rated)

Term. Material: Brass Tin Plated

MINI™ Shunt



Specifications

Operating Temp.: -40°C to +85°C

Maximum Continuous Load Rating: 20 A

Body Material: Thermoplastic
(UL 94V0 Rated)

Term. Material: Brass Tin Plated