

**SURFACE MOUNT
SUPER FAST RECTIFIERS**

REVERSE VOLTAGE - **400** to **200** Volts
FORWARD CURRENT - **1.0** Ampere


FEATURES

- Glass passivated chip
- Super fast switching for high efficiency
- For surface mounted applications
- Low forward voltage drop and high current capability
- Low reverse leakage current
- Plastic material has UL flammability classification 94V-0

MECHANICAL DATA

- Case : Molded plastic
- Polarity : Color band denotes cathode
- Weight : 0.003 ounces, 0.093 grams
- Marking : U1GB , U1JB

SMB



SMB		
DIM.	MIN.	MAX.
A	4.06	4.57
B	3.30	3.94
C	1.96	2.21
D	0.15	0.31
E	5.21	5.59
F	0.05	0.20
G	2.01	2.62
H	0.76	1.52

All Dimensions in millimeter

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	MURS140	MURS160	UNIT
Maximum Recurrent Peak Reverse Voltage	VRRM	400	600	V
Maximum RMS Voltage	VRMS	280	420	V
Maximum DC Blocking Voltage	VDC	400	600	V
Maximum Average Forward Rectified Current @TL =135°C	I(AV)	1.0		A
Peak Forward Surge Current 8.3ms single half sine-wave super imposed on rated load (JEDEC METHOD)	IFSM	35		A
Maximum forward Voltage at 1.0A DC	VF	1.25		V
Maximum DC Reverse Current @TJ =25°C at Rated DC Blocking Voltage @TJ =150°C	IR	5.0	150	uA
Maximum Reverse Recovery Time (Note 1)	T _{RR}	50		ns
Typical Junction Capacitance Note 2)	C _J	10		pF
Typical Thermal Resistance (Note 3)	R _{θJL}	15		°C/W
Operating Temperature Range	T _J	-55 to +150		°C
Storage Temperature Range	T _{STG}	-55 to +175		°C

- NOTES : 1. Reverse Recovery Test Conditions :IF=0.5A,IR=1.0A,IRR=0.25A.
2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
3. Thermal Resistance junction to Lead.

