

GLASS PASSIVATED BRIDGE RECTIFIERS

REVERSE VOLTAGE - **50 to 1000** Volts
FORWARD CURRENT - **6.0** Amperes


FEATURES

- Rating to 1000V PRV
- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique
- The plastic material has UL flammability classification 94V-0
- UL recognized file # E95060

MECHANICAL DATA

- Polarity : Symbols molded on body
- Weight : 0.16 ounces, 4.6 grams
- Mounting position : Any

KBJ



KBJ		
DIM.	MIN.	MAX.
A	24.80	25.20
B	14.70	15.30
C	3.90	4.10
D	4.40	4.80
E	3.40	3.80
F	3.10 \varnothing	3.40 \varnothing
G	3.30	3.70
H	0.90	1.10
I	1.50	1.90
J	17.2	17.80
K	7.30	7.70
L	2.50	2.90
M	0.60	0.80
N	9.30	9.70
O	3.0 x 45°	
P	3.10 \varnothing	3.40 \varnothing

All Dimensions in millimeter

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	KBJ 6005G	KBJ 601G	KBJ 602G	KBJ 604G	KBJ 606G	KBJ 608G	KBJ 610G	UNIT
Maximum Recurrent Peak Reverse Voltage	VRRM	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	VRMS	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	VDC	50	100	200	400	600	800	1000	V
Maximum Average Forward (with heatsink Note 2) Rectified Current @TC=110°C (without heatsink)	I(AV)					6.0			A
						2.8			
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC METHOD)	IFSM					170			A
Maximum forward Voltage at 3.0A DC	VF					1.0			V
Maximum DC Reverse Current @TJ=25°C at Rated DC Blocking Voltage @TJ=125°C	IR					5.0			uA
						500			
I ² t Rating for fusing (t < 8.3ms)	I ² t					120			A ² S
Typical Junction Capacitance per element (Note 1)	CJ					80			pF
Typical Thermal Resistance (Note 2)	R θ JC					1.5			°C/W
Operating Temperature Range	TJ					-55 to +150			°C
Storage Temperature Range	TSTG					-55 to +150			°C

NOTES : 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
2. Unit Mounted on 75mm x 75mm x 1.6mm Cu Plate Heatsink.

REV. 2, 01-Dec-2000, KBDFO4

