

MAXIM

Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches

General Description

The MAX4541–MAX4544 are precision, dual analog switches designed to operate from a single +2.7V to +12V supply. Low power consumption (5 μ W) makes these parts ideal for battery-powered equipment. These switches offer low leakage currents (100pA max) and fast switching speeds ($t_{ON} = 150$ ns max, $t_{OFF} = 100$ ns max).

When powered from a +5V supply, the MAX4541–MAX4544 offer 2 Ω max matching between channels, 60 Ω max on-resistance (RON), and 6 Ω max RON flatness.

These switches also offer 5pC max charge injection and a minimum of 2000V ESD protection per Method 3015.7.

The MAX4541/MAX4542/MAX4543 are dual single-pole/single-throw (SPST) devices and the MAX4544 is a single-pole/double-throw (SPDT) device. The MAX4541 has two normally open (NO) switches and the MAX4542 has two normally closed (NC) switches. The MAX4543 has one NO and one NC switch and can be used as an SPDT, while the MAX4544 is an SPDT. The MAX4541/MAX4542/MAX4543 are available in tiny SOT23-8 packages, and the MAX4544 is available in a SOT23-6 package.

Applications

Battery-Operated Systems	Test Equipment
Sample-and-Hold Circuits	Communications Systems
Heads-Up Displays	+3V/+5V DACs and ADCs
Guidance and Control Systems	PBX, PABX
Audio and Video Switching	Cell Phones
Military Radios	Ultrasound
	Pagers

Features

- ◆ Low RON: 60 Ω max (33 Ω typ)
- ◆ RON Matching Between Channels: 2 Ω max
- ◆ RON Flatness: 6 Ω max
- ◆ Guaranteed Charge Injection: 5pC max
- ◆ +2.7V to +12V Single-Supply Operation
- ◆ Low Power Consumption: <5 μ W
- ◆ Low Leakage Current Over Temperature: 10nA max at +85°C
- ◆ Fast Switching: $t_{ON} = 35$ ns, $t_{OFF} = 25$ ns
- ◆ Guaranteed Break-Before-Make (MAX4543/MAX4544 only)
- ◆ TTL/CMOS-Logic Compatible
- ◆ Pin Compatible with MAX323/MAX324/MAX325
- ◆ MAX4541/42/43 Available in SOT23-8
MAX4544 Available in SOT23-6

Ordering Information




PART	TEMP. RANGE	PIN-PACKAGE	TOP MARK
MAX4541CUA	0°C to +70°C	8 μ MAX	—
MAX4541CSA	0°C to +70°C	8 SO	—
MAX4541CPA	0°C to +70°C	8 Plastic DIP	—
MAX4541C/D	0°C to +70°C	Dice*	—
MAX4541EKA-T	-40°C to +85°C	8 SOT23	AAAE
MAX4541EUA	-40°C to +85°C	8 μ MAX	—
MAX4541ESA	-40°C to +85°C	8 SO	—
MAX4541EPA	-40°C to +85°C	8 Plastic DIP	—

Ordering Information continued at end of data sheet.

*Dice are specified at $T_A = +25^\circ\text{C}$.

Pin Configurations/Functional Diagrams/Truth Tables

TOP VIEW



*NOTE: SOT23-6 PACKAGE HAS LETTERING NEAREST PIN 6

N.C. = NOT INTERNALLY CONNECTED
MAX4541/MAX4542/MAX4543
APPEAR AT END OF DATA SHEET.

MAX4544		
LOGIC	NC	NO
0	ON	OFF
1	OFF	ON

SWITCHES SHOWN FOR "0" INPUT

MAXIM

Maxim Integrated Products 1

For free samples and the latest literature, visit www.maxim-ic.com or phone 1-800-998-8800.
For small orders, phone 1-800-835-8769.

MAX4541–MAX4544

Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches

ABSOLUTE MAXIMUM RATINGS

Voltage Referenced to GND

V ₊	-0.3V to +13V
IN _– , COM _– , NC _– , NO _– (Note 1).....	-0.3V to (V ₊ + 0.3V)
Continuous Current (any terminal).....	±10mA
Peak Current, COM _– , NO _– , NC _– (pulsed at 1ms, 10% duty cycle max).....	±20mA
ESD per Method 3015.7	>2000V
SOT23-6 (derate 7.1mW/°C above +70°C).....	571mW
SOT23-8 (derate 5.3mW/°C above +70°C).....	421mW

Note 1: Signals on NC, NO, COM, or IN exceeding V₊ or V_– are clamped by internal diodes. Limit forward diode current to maximum current rating.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS—Single +5V Supply

(V₊ = +5V ± 10%, GND = 0, V_{INH} = 2.4V, V_{INL} = 0.8V, TA = T_{MIN} to T_{MAX}, unless otherwise noted.) (Notes 2, 3)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
ANALOG SWITCH						
Analog Signal Range	V _{COM} , V _{NO} , V _{NC}	(Note 4)	0	V ₊		V
On-Resistance	R _{ON}	V ₊ = 4.5V, I _{COM} = 1.0mA, V _{NO} or V _{NC} = 3.5V	TA = +25°C	30	60	Ω
			TA = T _{MIN} to T _{MAX}		75	
On-Resistance Match Between Channels (Note 5)	ΔR _{ON}	V ₊ = 5V, I _{COM} = 1.0mA, V _{NO} or V _{NC} = 3.5V	TA = +25°C	0.8	2	Ω
			TA = T _{MIN} to T _{MAX}		4	
On-Resistance Flatness (Note 6)	R _{FLAT(ON)}	V ₊ = 5V; I _{COM} = 1.0mA; V _{NO} or V _{NC} = 1V, 2V, 3V	TA = +25°C	2	6	Ω
			TA = T _{MIN} to T _{MAX}		8	
NO or NC Off-Leakage Current (Note 7)	I _{NO(OFF)} or I _{NC(OFF)}	V ₊ = 5.5V; V _{COM} = 1V, 4.5V; V _{NO} or V _{NC} = 4.5V, 1V	TA = +25°C	-0.1	0.01	nA
			TA = T _{MIN} to T _{MAX} C, E	-5	5	
COM Off-Leakage Current (Note 7)	I _{COM(OFF)}	V ₊ = 5.5V; V _{COM} = 4.5V, 1V; V _{NO} or V _{NC} = 1V, 4.5V	TA = +25°C	-0.1	0.1	nA
			TA = T _{MIN} to T _{MAX} C, E	-5	5	
COM On-Leakage Current (Note 7)	I _{COM(ON)}	V ₊ = 5.5V; V _{COM} = 1V, 4.5V or V _{NO} or V _{NC} = 1V, 4.5V, or floating	TA = +25°C	-0.2	0.2	nA
			TA = T _{MIN} to T _{MAX} C, E	-10	10	

Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches

ELECTRICAL CHARACTERISTICS—Single +5V Supply (continued)

($V_+ = +5V \pm 10\%$, GND = 0, $V_{INH} = 2.4V$, $V_{INL} = 0.8V$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted.) (Notes 2, 3)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
DYNAMIC							
Turn-On Time	t_{ON}	V_{NO} or $V_{NC} = 3V$, Figure 2	$T_A = +25^\circ C$	35	100	ns	
			$T_A = T_{MIN}$ to T_{MAX}		240		
Turn-Off Time	t_{OFF}	V_{NO} or $V_{NC} = 3V$, Figure 2	$T_A = +25^\circ C$	25	75	ns	
			$T_A = T_{MIN}$ to T_{MAX}		150		
Break-Before-Make Time Delay (Note 4)	t_D	MAX4543/MAX4544 only, $R_L = 300\Omega$, $C_L = 35pF$		2	10		ns
Charge Injection (Note 4)	Q	$C_L = 1.0nF$, $V_{GEN} = 0$, $R_{GEN} = 0$, $T_A = +25^\circ C$, Figure 4			1	5	pC
Off-Isolation (Note 8)	OIRR	$R_L = 50\Omega$, $C_L = 5pF$, $f = 1MHz$, $T_A = +25^\circ C$, Figure 5			-76		dB
Crosstalk (Note 9)		$R_L = 50\Omega$, $C_L = 5pF$, $f = 1MHz$, $T_A = +25^\circ C$, Figure 6			-90		dB
NC or NO Capacitance	C_{OFF}	$f = 1MHz$, $T_A = +25^\circ C$, Figure 7			8		pF
COM Off-Capacitance	$C_{COM(OFF)}$	$f = 1MHz$, $T_A = +25^\circ C$, Figure 7			8		pF
COM On-Capacitance	$C_{COM(ON)}$	$f = 1MHz$, $T_A = +25^\circ C$, Figure 7	MAX4541/2/3		13	pF	
			MAX4544		20		
SUPPLY							
Power-Supply Range	V_+			2.7	12		V
Positive Supply Current	I_+	$V_+ = 5.5V$, $V_{IN} = 0$ or V_+ , all channels on or off		-1	0.0001	1	μA
LOGIC INPUT							
Input Voltage Low	V_{INL}				0.8		V
Input Voltage High	V_{INH}			2.4			V

Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches

ELECTRICAL CHARACTERISTICS—Single +3.3V Supply

($V_+ = +3.0V$ to $+3.6V$, $GND = 0$, $V_{INH} = 2.4V$, $V_{INL} = 0.8V$, $T_A = T_{MIN}$ to T_{MAX} , unless otherwise noted.) (Notes 2, 3)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
ANALOG SWITCH							
Analog Signal Range	V_{COM} , V_{NO} , V_{NC}	(Note 3)		0	V_+		V
Channel On-Resistance	R_{ON}	$V_+ = 3V$, $I_{COM} = 1.0mA$, V_{NO} or $V_{NC} = 1.5V$	$T_A = +25^\circ C$	50	125		Ω
			$T_A = T_{MIN}$ to T_{MAX}			275	
DYNAMIC							
Turn-On Time (Note 3)	t_{ON}	V_{NO} or $V_{NC} = 1.5V$	$T_A = +25^\circ C$	80	400		ns
			$T_A = T_{MIN}$ to T_{MAX}			500	
Turn-Off Time (Note 3)	t_{OFF}	V_{NO} or $V_{NC} = 1.5V$	$T_A = +25^\circ C$	50	125		ns
			$T_A = T_{MIN}$ to T_{MAX}			175	
Break-Before-Make Time Delay (Note 3)	t_D	MAX4543/MAX4544 only, $R_L = 300\Omega$, $C_L = 35pF$, $T_A = +25^\circ C$		2	30		ns
Charge Injection (Note 3)	Q	$C_L = 1.0nF$, $V_{GEN} = 0$, $R_{GEN} = 0$, $T_A = +25^\circ C$		1	5	pC	
SUPPLY							
Positive Supply Current	I_+	$V_+ = 3.6V$, $V_{IN} = 0$ or V_+ , all channels on or off		-1	1	μA	

Note 2: SOT-packaged parts are 100% tested at $+25^\circ C$ only and guaranteed by correlation at the full hot rated temperature.

Note 3: The algebraic convention, where the most negative value is a minimum and the most positive value a maximum, is used in this data sheet.

Note 4: Guaranteed by design.

Note 5: $\Delta R_{ON} = \Delta R_{ON\ max} - \Delta R_{ON\ min}$.

Note 6: Flatness is defined as the difference between the maximum and minimum value of on-resistance as measured over the specified analog signal range.

Note 7: Leakage parameters are 100% tested at maximum rated hot temperature and guaranteed by correlation at $+25^\circ C$.










Note 8: Off Isolation = $20\log_{10} [V_{COM} / (V_{NC} \text{ or } V_{NO})]$, V_{COM} = output, V_{NC} or V_{NO} = input to off switch.

Note 9: Between the two switches, MAX4541/MAX4542/MAX4543 only.

Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches

Typical Operating Characteristics

($T_A = +25^\circ\text{C}$, unless otherwise noted.)



Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches

Pin Description

PIN								NAME	FUNCTION		
MAX4541		MAX4542		MAX4543		MAX4544					
DIP/SO/ μMAX	SOT23-8	DIP/SO/ μMAX	SOT23-8	DIP/SO/ μMAX	SOT23-8	DIP/SO/ μMAX	SOT23-6				
1	1	—	—	1	1	—	—	NO1	Analog Switch 1—Normally Open		
2	8	2	8	2	8	—	—	COM1	Analog Switch 1—Common		
3	3	3	3	3	3	—	—	IN2	Digital Control Input 2		
4	6	4	6	4	6	4	3	GND	Ground—Negative Supply Input		
5	5	—	—	—	—	—	—	NO2	Analog Switch 2—Normally Open		
6	4	6	4	6	4	—	—	COM2	Analog Switch 2—Common		
7	7	7	7	7	7	—	—	IN1	Digital Control Input 1		
8	2	8	2	8	2	8	2	V+	Positive Supply Voltage Input		
—	—	1	1	—	—	—	—	NC1	Analog Switch 1—Normally Closed		
—	—	5	5	5	5	—	—	NC2	Analog Switch 2—Normally Closed		
—	—	—	—	—	—	1	6	NO	Analog Switch—Normally Open		
—	—	—	—	—	—	2	5	COM	Analog Switch—Common		
—	—	—	—	—	—	3	4	NC	Analog Switch—Normally Closed		
—	—	—	—	—	—	5, 6	—	N.C.	Not Connected (open circuit)		
—	—	—	—	—	—	7	1	IN	Digital Control Input		




Figure 1. Overvoltage Protection Using Two External Blocking Diodes

Applications Information

Logic Levels

The MAX4541–MAX4544 are TTL compatible when powered from a single +5V supply. When powered from other supply voltages, TTL compatibility is guaranteed and the logic inputs can be driven Rail-to-Rail®. For example, with a +12V supply, IN1 and IN2 can be driven low to 0 and high to 12V. With a +3.3V supply, IN1 and IN2 should be driven low to 0 and high to 3.3V.

Driving IN1 and IN2 rail-to-rail minimizes power consumption.

Analog Signal Levels

Analog signals that range over the entire supply voltage (V+ to GND) can be switched with very little change in on-resistance over the entire voltage range (see *Typical Operating Characteristics*). All the switches are bidirectional, so the NO_, NC_, and COM_ pins can be used as either inputs or outputs.

Rail-to-Rail is a registered trademark of Nippon Motorola, Ltd.

Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches

Power-Supply Sequencing and Overvoltage Protection

Do not exceed the absolute maximum ratings because stresses beyond the listed ratings may cause permanent damage to the devices.

Proper power-supply sequencing is recommended for all CMOS devices. Always apply V₊ before applying analog signals or logic inputs, especially if the analog or logic signals are not current limited. If this sequencing is not possible, and if the analog or logic inputs are not current limited to <10mA, add a small-signal diode (D1) as shown in Figure 1. If the analog signal can dip below GND, add D2. Adding protection diodes reduces the analog signal range to a diode drop (about 0.7V) below V₊ (for D1), and to a diode drop above ground (for D2). Leakage is unaffected by adding the diodes. On-resistance increases by a small amount at low supply voltages. Maximum supply voltage (V₊) must not exceed 13V.

Adding protection diodes causes the logic thresholds to be shifted relative to the power-supply rails. This can be significant when low supply voltages (+5V or less) are used. With a +5V supply, TTL compatibility is not guaranteed when protection diodes are added. Driving IN1 and IN2 all the way to the supply rails (i.e., to a diode drop higher than the V₊ pin, or to a diode drop lower than the GND pin) is always acceptable.

Protection diodes D1 and D2 also protect against some overvoltage situations. With Figure 1's circuit, if the supply voltage is below the absolute maximum rating, and if a fault voltage up to the absolute maximum rating is applied to an analog signal pin, no damage will result.

Test Circuits/Timing Diagrams




Figure 2. Switching Time

Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches

Test Circuits/Timing Diagrams (continued)

MAXIM





Figure 3a. Break-Before-Make Interval (MAX4543 only)

MAXIM





Figure 3b. Break-Before-Make Interval (MAX4544 only)

MAXIM





Figure 4. Charge Injection

Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches

Test Circuits/Timing Diagrams (continued)




Figure 5. Off-Isolation




Figure 6. Crosstalk




Figure 7. Channel Off/On-Capacitance

Chip Information

TRANSISTOR COUNT: 76

Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches


Ordering Information (continued)

PART	TEMP. RANGE	PIN-PACKAGE	TOP MARK
MAX4542CUA	0°C to +70°C	8 µMAX	—
MAX4542CSA	0°C to +70°C	8 SO	—
MAX4542CPA	0°C to +70°C	8 Plastic DIP	—
MAX4542C/D	0°C to +70°C	Dice*	—
MAX4542EKA-T	-40°C to +85°C	8 SOT23	AAAF
MAX4542EUA	-40°C to +85°C	8 µMAX	—
MAX4542ESA	-40°C to +85°C	8 SO	—
MAX4542EPA	-40°C to +85°C	8 Plastic DIP	—
MAX4543CUA	0°C to +70°C	8 µMAX	—
MAX4543CSA	0°C to +70°C	8 SO	—
MAX4543CPA	0°C to +70°C	8 Plastic DIP	—
MAX4543C/D	0°C to +70°C	Dice*	—
MAX4543EKA-T	-40°C to +85°C	8 SOT23	AAAG
MAX4543EUA	-40°C to +85°C	8 µMAX	—
MAX4543ESA	-40°C to +85°C	8 SO	—
MAX4543EPA	-40°C to +85°C	8 Plastic DIP	—
MAX4544CUA	0°C to +70°C	8 µMAX	—
MAX4544CSA	0°C to +70°C	8 SO	—
MAX4544CPA	0°C to +70°C	8 Plastic DIP	—
MAX4544C/D	0°C to +70°C	Dice*	—
MAX4544EUT-T	-40°C to +85°C	6 SOT23	AAAM
MAX4544EUA	-40°C to +85°C	8 µMAX	—
MAX4544ESA	-40°C to +85°C	8 SO	—
MAX4544EPA	-40°C to +85°C	8 Plastic DIP	—

*Dice are specified at $T_A = +25^\circ\text{C}$.

Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches


Pin Configurations/Functional Diagrams/Truth Tables (continued)




MAX4541-MAX4544

Low-Voltage, Single-Supply Dual SPST/SPDT Analog Switches

Package Information



6LSDT.EPS



8LSDT.BLEPS

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

12 **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**