

FEATURES:

- RAD-PAK® technology radiation-hardened against natural space radiation
- Total dose hardness:
 - > 50 Krad (Si), depending upon space mission
- Excellent Single Event Effects:
 - SEL_{TH} : > 110 MeV/mg/cm²
 - SEU_{TH} : > 110 MeV/mg/cm²
- Package: 28-pin RAD-PAK® flat pack
- Guaranteed on-resistance matching between channels: < 5Ω max
- Low on-resistance < 100Ω max
- Guaranteed flat on-resistance over specified signal range: 7Ω max
- Guaranteed Charge Injection: < 10 pC
- $I_{NO(OFF)}$ Leakage < 2.5 nA at +85°C
- $I_{COM(OFF)}$ Leakage < 20 nA at +85°C
- ESD Protection > 2000V
- Single-supply operation (+4.5V to +30V)
- Bipolar-supply operation (±4.5V to ±20V)
- Low power consumption, < 1.25 mW
- Rail-to-rail signal handling
- TTL/CMOS-logic compatible

Maxwell Technologies' 306 high-performance, high-precision, monolithic, CMOS analog multiplexer features a greater than 50 krad (Si) total dose tolerance, depending upon space mission. The patented radiation-hardened RAD-PAK® technology incorporates radiation shielding in the microcircuit package. Using Maxwell's radiation hardened RAD-PAK packaging technology, this single-ended 1-of-16 device offers very low (less than 100Ω) on-resistance which is matched to within 5Ω between channels and remains flat over the specified analog signal range. The 306 also offers low leakage over temperature and fast switching speeds. The 306 operates with a single +4.5V to +30V supply, or bipolar ±4.5V to ±20V supplies, while retaining TTL/CMOS-logic input compatibility and fast switching.

Maxwell Technologies' patented Rad-Pak packaging technology incorporates radiation shielding in the microcircuit package. It eliminates the need for box shielding while providing the required radiation shielding for a lifetime in orbit or a space mission. In a GEO orbit, Rad-Pak provides greater than 50 krad (Si) total radiation dose tolerance, dependent upon space mission. This product is available with packaging and screening up to Class S.

DESCRIPTION:

TABLE 1. PINOUT DESCRIPTION

| PIN | SYMBOL | DESCRIPTION |
|----------|----------|-------------------------------|
| 1 | V+ | Positive Supply Voltage Input |
| 2, 3, 13 | NC | No Internal Connections |
| 4-11 | NO16-NO9 | Analog Inputs-bidirectional |
| 12 | GND | Ground |
| 14-17 | A3-A0 | Address Inputs |
| 18 | EN | Enable Inputs |
| 19-26 | NO1-NO8 | Analog Inputs-bidirectional |
| 27 | V- | Negative Supply Voltage Input |
| 28 | COM | Output-bidirectional |

TABLE 2. 306 ABSOLUTE MAXIMUM RATINGS

| Parameter | Symbol | Min | Max | Units |
|---|---------------|--------------|----------|-------|
| Voltage Referenced to V- V+ GND | V_{CC} | -0.3 -0.3 | 44 25 | V |
| Digital Inputs, NO, COM ¹ | | V- -2 | V+ +2 | V |
| Continuous Current any terminal ² | | | 30 | mA |
| Peak Current, NO or COM (pulsed at 1ms, 10% duty cycle max) | | | 100 | mA |
| Thermal Impedance | Θ_{JC} | -- | 3.62 | °C/W |
| Operating Temperature Range: | T_A | -55 | +125 | °C |
| Storage Temperature Range: | T_S | -65 | +150 | °C |

1. Signals on NO, COM, A0, A1, A2, A3, or EN exceeding V+ or V- are clamped by internal diodes. Limit forward current to maximum current ratings.

2. Or 30mA (whichever occurs first)

TABLE 3. DELTA LIMITS

| PARAMETER | VARIATION |
|-----------|------------------------------------|
| I+ | ±10% of specified value in table 5 |
| I- | ±10% of specified value in table 5 |

TABLE 4. 306 ELECTRICAL CHARACTERISTICS — SINGLE SUPPLY
 (V+ = +12V, V- = 0V, GND = 0V, V_{AH} = +2.4V, V_{AL} = +0.8V, T_A = -55 TO +125°C, UNLESS OTHERWISE SPECIFIED.)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN ¹ | TYP ¹ | MAX ¹ | UNITS | |
|----------------------------------|-------------------------------------|--|------------------|------------------|------------------|-------|----|
| SWITCH | | | | | | | |
| Analog Signal Range ² | V _{NO} V _{COM} | | 0 | -- | 12 | V | |
| On-Resistance | R _{ON} | I _{NO} = -1.0mA V _{COM} = 3V or 10V | | | | | |
| | | | | -- | 120 | 175 | Ω |
| DYNAMIC ² | | | | | | | |
| Transition Time | t _{TRANS} | V _{NO1} = 8V V _{NO8} = 0V V _{IN} = 2.4V Figure 9 | | | | | |
| | | | | -- | 130 | 450 | nA |
| Enable Turn-ON Time | t _{ON(EN)} | V _{INH} = 2.4V V _{INL} = 0V V _{NO1} = 5V Figure 11 | | | | | |
| | | | | -- | -- | 600 | ns |
| Enable Turn-OFF Time | t _{OFF(EN)} | V _{INH} = 2.4V V _{INL} = 0V V _{NO1} = 5V Figure 11 | | | | | |
| | | | | -- | -- | 300 | ns |
| Charge Injection | Q | CL = 1.0nF V _{NO} = 0V V _S = 0V | | | | | |
| | | | | -- | -- | 10 | pC |

1. The Algebraic convention where the most negative value is a minimum and the most positive value a maximum is used in this data sheet.
2. Guaranteed by design.

TABLE 5. 306 ELECTRICAL CHARACTERISTICS - DUAL SUPPLIES

(V+ = +15V, V- = -15V, GND = 0V, V_{AH} = +2.4V, V_{AL} = +0.8V, T_A = -55 TO +125°C, UNLESS OTHERWISE SPECIFIED.)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNITS | |
|---|-------------------------------------|---|--------------------------------|------|-------|-------|----|
| SWITCH | | | | | | | |
| Analog Signal Range ¹ | V _{NO} V _{COM} | | -15 | -- | 15 | V | |
| On-Resistance | R _{ON} | I _{NO} = -1.0 mA V _{COM} = ±10V | T _A = +25°C | -- | 60 | 100 | Ω |
| | | | T _A = -55 TO +125°C | | | 125 | |
| On-Resistance Matching Between Channels ^{2, 3} | ΔR _{ON} | I _{NO} = -1.0 mA V _{COM} = ±10V | T _A = +25°C | -- | 1.5 | 5 | Ω |
| | | | T _A = -55 TO +125°C | | | 8 | |
| On-Resistance Flatness ² | R _{FLAT} | I _{NO} = -1.0 mA V _{COM} = +5V or 0V | T _A = +25°C | -- | 1.8 | 7 | Ω |
| | | | T _A = -55 TO +125°C | | | 10 | |
| NO-Off Leakage Current ⁴ | I _{NO(OFF)} | V _{COM} = ±10 V _{NO} = ±10V V _{EN} = 0V | T _A = -55 TO +125°C | -5.0 | -- | 5.0 | nA |
| COM-Off Leakage Current ⁴ | I _{COM(OFF)} | V _{COM} = ±10 V _{NO} = ±10V V _{EN} = 0V | T _A = -55 TO +125°C | -40 | -- | 40 | nA |
| COM-On Leakage Current ⁴ | I _{COM(ON)} | V _{COM} = ±10 V _{NO} = ±10V sequence each switch on | T _A = -55 TO +125°C | -50 | -- | 50 | nA |
| INPUT | | | | | | | |
| Input Current with Input Voltage High | I _{AH} | V _A = 2.4V or 15V | | -1.0 | -- | 1.0 | μA |
| Input Current with Input Voltage Low | I _{AL} | V _{EN} = 0V or 2.4V, V _A = 0V | | -1.0 | -- | 1.0 | μA |
| SUPPLY | | | | | | | |
| Power-Supply Range | | | | ±4.5 | -- | ±20 | V |
| Positive Supply Current | I+ | V _{EN} = V _A = 0V or 4.5V | T _A = +25°C | -- | 16 | 30 | μA |
| | | | T _A = -55 TO +125°C | | | 75 | |
| | | V _{EN} = 2.4V, V _{A(ALL)} = 0V or 2.4 | T _A = +25°C | | 0.075 | 0.5 | mA |
| | | | T _A = -55 TO +125°C | | | 1 | |
| Negative Supply Current | I- | V _{EN} = 2.4V, V _A = 0V or 2.4V | T _A = +25°C | -1 | -- | 1 | μA |
| | | | T _A = -55 TO +125°C | -10 | | 10 | |
| DYNAMIC | | | | | | | |
| Transition Time | t _{TRANS} | Figure 10 | T _A = +25°C | -- | 110 | 300 | ns |
| | | | T _A = -55 TO +125°C | | | 400 | |
| Break-Before-Make Interval | t _{OPEN} | Figure 12 | T _A = +25°C | 10 | 40 | | ns |
| Enable Turn-On Time | t _{ON(EN)} | Figure 11 | T _A = +25°C | -- | 130 | 200 | ns |
| | | | T _A = -55 TO +125°C | | | 400 | |

| PARAMETER | SYMBOL | TEST CONDITIONS | | MIN | TYP | MAX | UNITS |
|-------------------------------|-----------------------|--|--|-----|-----|-----|-------|
| Enable Turn-Off Time | $t_{\text{OFF(EN)}}$ | Figure 11 | $T_A = +25^\circ\text{C}$ | -- | 55 | 150 | ns |
| | | | $T_A = -55 \text{ TO } +125^\circ\text{C}$ | | | 300 | |
| Charge Injection ¹ | Q | $C_L = 1.0 \text{ nF}$, $V_{\text{NO}} = 0\text{V}$, $R_S = 0\Omega$, Figure 13 | $T_A = +25^\circ\text{C}$ | -- | 2 | 10 | pC |
| Off Isolation ⁵ | V_{ISO} | $V_{\text{EN}} = 0\text{V}$, $R_L = 1 \text{ k}\Omega$, $f = 100 \text{ kHz}$, Figure 14 | $T_A = +25^\circ\text{C}$ | -- | -69 | -- | dB |
| Crosstalk Between Channels | V_{CT} | $V_{\text{EN}} = 2.4\text{V}$, $f = 100 \text{ kHz}$, $V_{\text{GEN}} = 1\text{V p-p}$, $R_L = 1 \text{ k}\Omega$, Figure 15 | $T_A = +25^\circ\text{C}$ | -- | -92 | -- | dB |
| Logic Input Capacitance | C_{IN} | $f = 1 \text{ MHz}$ | $T_A = +25^\circ\text{C}$ | -- | 8 | -- | pF |
| NO-Off Capacitance | $C_{\text{NO(OFF)}}$ | $f = 1 \text{ MHz}$ $V_{\text{EN}} = V_{\text{NO}} = 0\text{V}$ Figure 16 | $T_A = +25^\circ\text{C}$ | -- | 8 | -- | pF |
| COM-Off Capacitance | $C_{\text{COM(OFF)}}$ | $f = 1 \text{ MHz}$ $V_{\text{EN}} = 2.4\text{V}$ Figure 16 | $T_A = +25^\circ\text{C}$ | -- | 130 | -- | pF |
| COM-On Capacitance | $C_{\text{COM(ON)}}$ | $f = 1 \text{ MHz}$ $V_{\text{EN}} = 0.8\text{V}$ Figure 16 | $T_A = +25^\circ\text{C}$ | -- | 140 | -- | pF |

1. Guaranteed by design.
2. Characterized and not 100% tested.
3. $\Delta\text{RON} = \text{RON}_{(\text{MAX})} - \text{RON}_{(\text{MIN})}$. On-resistance match between channels and flatness are guaranteed only with specified voltages. Flatness is defined as the difference between the maximum and minimum value of on-resistance as measured at the extremes of the specified analog signal range.
4. Leakage parameters are 100% tested at the maximum rated hot temperature and guaranteed by correlation at $+25^\circ\text{C}$.
5. Off isolation = $20\log V_{\text{COM}}/V_{\text{NO}}$, where V_{COM} = output and V_{NO} = input to off switch.

FIGURE 1. ON-RESISTANCE VS. V_{COM} (DUAL SUPPLIES)




FIGURE 2. ON-RESISTANCE VS. V_{COM} AND TEMPERATURE (DUAL SUPPLIES)




FIGURE 3. ON-RESISTANCE VS. V_{COM} (SINGLE SUPPLY)




FIGURE 4. ON-RESISTANCE VS. V_{COM} AND TEMPERATURE (SINGLE SUPPLY)




FIGURE 5. OFF LEAKAGE VS. TEMPERATURE




FIGURE 6. ON LEAKAGE VS. TEMPERATURE




FIGURE 7. CHARGE INJECTION VS. V_{COM}




FIGURE 8. SUPPLY CURRENT VS. TEMPERATURE




FIGURE 9. OVERVOLTAGE PROTECTION USING EXTERNAL BLOCKING DIODES




FIGURE 10. TRANSITION TIME




FIGURE 11. ENABLE SWITCHING TIME




FIGURE 12. BREAK-BEFORE-MAKE INTERVAL




FIGURE 13. CHARGE INJECTION




FIGURE 14. OFF ISOLATION




FIGURE 15. CROSSTALK




FIGURE 16. NO/COM CAPACITANCE





FIGURE 17. PACKAGE OUTLINE DIAGRAM



28-PIN RAD-PAK® FLAT PACKAGE

| SYMBOL | DIMENSIONS | | |
|--------|------------|------|------|
| | MIN | NOM | MAX |
| A | .190 | .207 | .224 |
| b | .015 | .017 | .022 |
| c | .004 | .005 | .009 |
| D | -- | .720 | .740 |
| E | .380 | .410 | .420 |
| E1 | -- | -- | .440 |
| E2 | .180 | .250 | -- |
| E3 | .030 | .080 | -- |
| e | .050 BSC | | |
| L | .360 | .370 | .380 |
| Q | .062 | .073 | .081 |
| S1 | .000 | .027 | -- |
| N | 28 | | |

F28-02
All dimensions in inches

Important Notice:

These data sheets are created using the chip manufacturers published specifications. Maxwell Technologies verifies functionality by testing key parameters either by 100% testing, sample testing or characterization.

The specifications presented within these data sheets represent the latest and most accurate information available to date. However, these specifications are subject to change without notice and Maxwell Technologies assumes no responsibility for the use of this information.

Maxwell Technologies' products are not authorized for use as critical components in life support devices or systems without express written approval from Maxwell Technologies.

Any claim against Maxwell Technologies must be made within 90 days from the date of shipment from Maxwell Technologies. Maxwell Technologies' liability shall be limited to replacement of defective parts.

Product Ordering Options

