


### DESCRIPTION

MSB74D is high brightness output red LED lamp encapsulated in a 1.2mm x 3.4mm rectangular bars with red diffused lens.



- All dimension in mm(inch)
- No Scale
- Tol. : +/-0.3mm

### ABSOLUTE MAXIMUM RATINGS

Power Dissipation @ Ta=25°C

Forward Current, DC (IF)

Reverse Voltage

Operating & Storage Temperature Range

Lead Temperature

40mW

15mA

5V

-55 to +100°C

260°C

### ELECTRO-OPTICAL CHARACTERISTIC (Ta=25°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	CONDITIONS
Forward Voltage	VF			3.0	V	IF=20mA
Reverse Breakdown Voltage	BVR	5			V	IR=100 μA
Luminous Intensity	IV	0.22	0.35		mcd	IF=10mA
Peak Wavelength	λp		700		nm	IF=20mA
Spectral Line Half Width	Δλ		100		nm	IF=20mA



MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex:43510 Micro Hx. Tel: 2343 0181-5

Rev A