


PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.

MITSUBISHI Pch POWER MOSFET

FX3ASJ-3



HIGH-SPEED SWITCHING USE

FX3ASJ-3



- 4V DRIVE
- V_{DSS} -150V
- $r_{DS(ON)}$ (MAX) 1.2Ω
- I_D -3A
- Integrated Fast Recovery Diode (TYP.) 80ns

OUTLINE DRAWING Dimensions in mm

① GATE
 ② DRAIN
 ③ SOURCE
 ④ DRAIN

MP-3

APPLICATION

Motor control, Lamp control, Solenoid control
 DC-DC converter, etc.

MAXIMUM RATINGS (Tc = 25°C)

Symbol	Parameter	Conditions	Ratings	Unit
V_{DSS}	Drain-source voltage	$V_{GS} = 0V$	-150	V
V_{GSS}	Gate-source voltage	$V_{DS} = 0V$	± 20	V
I_D	Drain current		-3	A
I_{DM}	Drain current (Pulsed)		-12	A
I_{DA}	Avalanche drain current (Pulsed)	$L = 100\mu H$	-3	A
I_S	Source current		-3	A
I_{SM}	Source current (Pulsed)		-12	A
P_D	Maximum power dissipation		30	W
T_{ch}	Channel temperature		-55 ~ +150	°C
T_{stg}	Storage temperature		-55 ~ +150	°C
—	Weight	Typical value	0.26	g

Jan.1999


PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.

ELECTRICAL CHARACTERISTICS (T_{ch} = 25°C)


Symbol	Parameter	Test conditions	Limits			Unit
			Min.	Typ.	Max.	
V (BR) DSS	Drain-source breakdown voltage	I _D = -1mA, V _{GS} = 0V	-150	—	—	V
I _{GSS}	Gate-source leakage current	V _{GS} = ±20V, V _{DS} = 0V	—	—	±0.1	μA
I _{DSS}	Drain-source leakage current	V _{DS} = -150V, V _{GS} = 0V	—	—	-0.1	mA
V _{GS} (th)	Gate-source threshold voltage	I _D = -1mA, V _{DS} = -10V	-1.0	-1.5	-2.0	V
r _{DS} (ON)	Drain-source on-state resistance	I _D = -1A, V _{GS} = -10V	—	0.93	1.20	Ω
r _{DS} (ON)	Drain-source on-state resistance	I _D = -1A, V _{GS} = -4V	—	1.02	1.32	Ω
V _{DS} (ON)	Drain-source on-state voltage	I _D = -1A, V _{GS} = -10V	—	-0.93	-1.20	V
y _{fs}	Forward transfer admittance	I _D = -1A, V _{DS} = -5V	—	3.0	—	S
C _{iss}	Input capacitance	V _{DS} = -10V, V _{GS} = 0V, f = 1MHz	—	1170	—	pF
C _{oss}	Output capacitance		—	81	—	pF
C _{rss}	Reverse transfer capacitance		—	31	—	pF
t _d (on)	Turn-on delay time		—	9	—	ns
t _r	Rise time	V _{DD} = -80V, I _D = -1A, V _{GS} = -10V, R _{GEN} = R _{GS} = 50Ω	—	7	—	ns
t _d (off)	Turn-off delay time		—	82	—	ns
t _f	Fall time		—	33	—	ns
V _{SD}	Source-drain voltage		I _S = -1A, V _{GS} = 0V	—	-1.0	-1.5
R _{th} (ch-c)	Thermal resistance	Channel to case	—	—	4.17	°C/W
t _{rr}	Reverse recovery time	I _S = -3A, di _s /dt = 100A/μs	—	80	—	ns

PERFORMANCE CURVES


POWER DISSIPATION DERATING CURVE




MAXIMUM SAFE OPERATING AREA



OUTPUT CHARACTERISTICS (TYPICAL)




OUTPUT CHARACTERISTICS (TYPICAL)




PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.


ON-STATE VOLTAGE VS. GATE-SOURCE VOLTAGE (TYPICAL)




ON-STATE RESISTANCE VS. DRAIN CURRENT (TYPICAL)




TRANSFER CHARACTERISTICS (TYPICAL)




FORWARD TRANSFER ADMITTANCE VS. DRAIN CURRENT (TYPICAL)



CAPACITANCE VS. DRAIN-SOURCE VOLTAGE (TYPICAL)



SWITCHING CHARACTERISTICS (TYPICAL)



PRELIMINARY
 Notice: This is not a final specification.
 Some parametric limits are subject to change.

