


# Product Preview

## 2M x 2 Bit Fast Static Random Access Memory with ECL I/O

The MCM101525 is a 4,194,304 bit static random access memory organized as 2,097,152 words of 2 bits. This device features complementary outputs. This circuit is fabricated using high performance silicon-gate BiCMOS technology. Asynchronous design eliminates the need for external clocks or timing strobes. The MCM101525 is available in a 400 mil, 36 lead TAB.


- Fast Access Times: 12, 15 ns
- Equal Address and Chip Select Access Time
- Power Operation: - 195 mA Maximum, Active AC

### MCM101525



**TB PACKAGE**  
**400 MIL TAB**  
**CASE 984A-01**

#### BLOCK DIAGRAM



#### PIN ASSIGNMENT

A10	1	36	A1
A11	2	35	A2
A12	3	34	A3
A13	4	33	A8
A14	5	32	A19
$\bar{S}$	6	31	NC
D0	7	30	A20
Q0	8	29	$\bar{Q1}$
VCC	9	28	VEE
VEE	10	27	VCC
$\bar{Q0}$	11	26	Q1
VEE	12	25	D1
$\bar{W}$	13	24	NC
A0	14	23	A9
A15	15	22	A4
A16	16	21	A5
A17	17	20	A6
A18	18	19	A7

#### PIN NAMES

A0 - A20	Address Inputs	$\bar{W}$	Write Enable
$\bar{S}$	Chip Select	D0 - D1	Data Input
Q0 - Q1	Data Output	$\bar{Q0}$ and $\bar{Q1}$	Complementary Data Out
NC	No Connection	VEE	Power Supply
VCC	Ground		

This document contains information on a new product under development. Motorola reserves the right to change or discontinue this product without notice.

**TRUTH TABLE** (X = Don't Care)

$\bar{S}$	$\bar{W}$	Operation	Data	Output	Current
H	X	Not Enabled	X	L	—
L	H	Read	X	$Q/\bar{Q}$	$I_{EE}$
L	L	Write	X	L	$I_{EE}$

**ABSOLUTE MAXIMUM RATINGS** (See Note)

Rating	Symbol	Value	Unit
$V_{EE}$ Pin Potential (to Ground)	$V_{EE}$	- 7.0 to + 0.5	V
Voltage Relative to $V_{CC}$ for Any Pin Except $V_{EE}$	$V_{in}, V_{out}$	$V_{EE} - 0.5$ to + 0.5	V
Output Current (per I/O)	$I_{out}$	- 50	mA
Power Dissipation	$P_D$	2.0	W
Temperature Under Bias	$T_{bias}$	- 30 to + 85	°C
Operating Temperature	$T_J$	0 to + 60	°C
Storage Temperature — Plastic	$T_{stg}$	- 55 to + 125	°C

NOTE: Permanent device damage may occur if ABSOLUTE MAXIMUM RATINGS are exceeded. Functional operation should be restricted to the OPERATING CONDITIONS. Exposure to higher than recommended voltages for extended periods of time could affect device reliability.

This device contains circuitry to protect the inputs against damage due to high static voltages or electric fields; however, it is advised that normal precautions be taken to avoid application of any voltage higher than maximum rated voltages to these high impedance circuits.

This BiCMOS memory circuit has been designed to meet the dc and ac specifications shown in the tables, after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse air flow of at least 500 linear feet per minute is maintained.

**DC OPERATING CONDITIONS AND CHARACTERISTICS**

( $V_{CC} = 0$  V,  $V_{EE} = - 5.2$  V  $\pm$  5%,  $T_J = 0$  to + 60°C, Unless Otherwise Noted)

**DC OPERATING CONDITIONS AND SUPPLY CURRENTS**

Parameter	Symbol	Min	Typ	Max	Unit
Supply Voltage (Operating Voltage Range)	$V_{EE}$	- 5.46	- 5.2	- 4.94	V
Input High Voltage	$V_{IH}$	- 1165	—	- 880	mV
Input Low Voltage	$V_{IL}$	- 1810	—	- 1475	mV
Output High Voltage	$V_{OH}$	- 1025	—	- 880	mV
Output Low Voltage	$V_{OL}$	- 1810	—	- 1620	mV
Input Low Current	$I_{IL}$	- 50	—	—	$\mu$ A
Input High Current	$I_{IH}$	—	—	220	$\mu$ A
Chip Select Input Low Current	$I_{IL}(CS)$	0.5	—	170	$\mu$ A
Operating Power Supply Current: $t_{AVAV} = 20$ ns (All Outputs Open)*	$I_{EE}$	—	—	- 195	mA
Quiescent Power Supply Current: $f_0 = 0$ MHz (Outputs Open)	$I_{EEQ}$	—	—	- 150	mA
Voltage Compensation ( $V_{OH}$ )	$\Delta V_{OH}/\Delta V_{EE}$	$\pm 35$ mV/V @ - 4.94 to - 5.46 V			
Voltage Compensation ( $V_{OL}$ )	$\Delta V_{OL}/\Delta V_{EE}$	$\pm 60$ mV/V @ - 4.94 to - 5.46 V			

\* Address Increment

**RISE/FALL TIME CHARACTERISTICS**

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Output Rise Time	$t_r$	20% to 80%	0.5	1.0	1.5	ns
Output Fall Time	$t_f$	20% to 80%	0.5	1.0	1.5	ns

**CAPACITANCE** ( $f = 1.0$  MHz,  $T_A = 25^\circ$ C, Periodically Sampled Rather Than 100% Tested)

Parameter	Symbol	Typ	Max	Unit	
Input Capacitance	Address and Data	$C_{in}$	3.5	7	pF
	$\bar{S}, \bar{W}$	$C_{ck}$	4	7	
Output Capacitance	$\bar{Q}, Q$	$C_{out}$	4	8	pF

**AC OPERATING CONDITIONS AND CHARACTERISTICS**  
 ( $V_{EE} = -5.2\text{ V} \pm 5\%$ ,  $V_{CC} = 0\text{ V}$ ,  $T_J = 0\text{ to }+60^\circ\text{C}$ , Unless Otherwise Noted)

Input Pulse Levels . . . . .  $-1.7\text{ V to }-0.9\text{ V}$  (See Figure 1)  
 Input Rise/Fall Time . . . . .  $1\text{ ns}$   
 Input Timing Measurement Reference Level . . . . .  $50\%$

Output Timing Measurement Reference Level . .  $V_{OH} = -1165\text{ mV}$   
 $V_{OL} = -1475\text{ mV}$   
 Output Load (AC Test Circuit) . . . . . See Figure 2


**READ CYCLE TIMING** (See Notes 1 and 2)

Parameter	Symbol	MCM101525-12		MCM101525-15		Unit	Notes
		Min	Max	Min	Max		
Read Cycle Time	$t_{AVAV}$	12	—	15	—	ns	2, 3
Address Access Time	$t_{AVQV}$	—	12	—	15	ns	
Chip Select Access Time	$t_{SLQV}$	—	12	—	15	ns	6
Select High to Output Low	$t_{SHQL}$	0	8	0	9	ns	
Output Hold from Address Change	$t_{AXQX}$	4	—	4	—	ns	
Power Up Time	$t_{SLIEEH}$	0	—	0	—	ns	4
Power Down Time	$t_{SHIEEL}$	—	12	—	15	ns	4


**NOTES:**

- $\bar{W}$  is high for read cycle.
- Product sensitivities to noise require proper grounding and decoupling of power supplies during read and write cycles.
- All read cycle timings are referenced from the last valid address to the first transitioning address.
- This parameter is sampled and not 100% tested.
- Device is continuously selected ( $\bar{S} \leq V_{IL}$ ).
- Addresses valid prior to or coincident with  $\bar{S}$  going low.

**AC TEST CONDITIONS**




**Figure 1. Input Levels**




**Figure 2. AC Test Circuit**

**READ CYCLE 1** (See Notes 1, 2, and 5)



**READ CYCLE 2** (See Note 6)





**WRITE CYCLE 1** ( $\bar{W}$  Controlled, See Notes 1 and 2)

Parameter	Symbol	MCM101525–12		MCM101525–15		Unit	Notes
		Min	Max	Min	Max		
Write Cycle Time	$t_{AVAV}$	12	—	15	—	ns	3
Address Setup Time	$t_{AVWL}$	1	—	1	—	ns	
Address Valid to End of Write	$t_{AVWH}$	9	—	10	—	ns	
Write Pulse Width	$t_{WLWH}$ , $t_{WLSH}$	8	—	9	—	ns	
Data Valid to End of Write	$t_{DVWH}$	8	—	9	—	ns	
Data Hold Time	$t_{WHDX}$	1	—	1	—	ns	
Write High to Output Active	$t_{WHQX}$	4	—	4	—	ns	4
Write High to Output Valid	$t_{WHQV}$	—	13	—	16	ns	
Write Recovery Time	$t_{WHAX}$	1	—	1	—	ns	
Write Low to Output Low	$t_{WLQL}$	0	8	0	9	ns	

**NOTES:**

1. A write occurs during the overlap of  $\bar{S}$  low and  $\bar{W}$  low.
2. Product sensitivities to noise require proper grounding and decoupling of power supplies during read and write cycles.
3. All write cycle timings are referenced from the last valid address to the first transitioning address.
4. This parameter is sampled and not 100% tested.



Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters can and do vary in different applications. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.


**WRITE CYCLE 2** ( $\overline{S}$  Controlled, See Notes 1 and 2)

Parameter	Symbol	MCM101525-12		MCM101525-15		Unit	Notes
		Min	Max	Min	Max		
Write Cycle Time	$t_{AVAV}$	12	—	15	—	ns	3
Address Setup Time	$t_{AVSL}$	1	—	1	—	ns	
Address Valid to End of Write	$t_{AVSH}$	9	—	10	—	ns	
Write Pulse Width	$t_{SLSH}$ $t_{SLWH}$	8	—	9	—	ns	
Data Valid to End of Write	$t_{DVSH}$	8	—	9	—	ns	
Chip Select Set-Up Time	$t_{SLWL}$	0	—	0	—	ns	
Data Hold Time	$t_{SHDX}$	1	—	1	—	ns	
Write Recovery Time	$t_{SHAX}$	1	—	1	—	ns	


NOTES:

1. A write occurs during the overlap of  $\overline{S}$  low and  $\overline{W}$  low.
2. Product sensitivities to noise require proper grounding and decoupling of power supplies during read and write cycles.
3. All write cycle timings are referenced from the last valid address to the first transitioning address.

**WRITE CYCLE 2** ( $\overline{S}$  Controlled, See Notes 1 and 2)





**ORDERING INFORMATION**  
(Order by Full Part Number)



Full Part Numbers — MCM101525TB12  
MCM101525TB15

# PACKAGE DIMENSIONS



TB PACKAGE  
400 MIL TAB  
CASE 984A-01



- NOTES:  
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.  
2. CONTROLLING DIMENSION: MILLIMETER.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	18.14 REF		0.714 REF	
B	8.03 REF		0.316 REF	
C	26.95 BSC		1.061 BSC	
C1	26.95 BSC		1.061 BSC	
J	—	0.25	—	0.010
K	—	0.71	—	0.028
P	3.00 REF		0.118 REF	
R	2.39 REF		0.094 REF	
S	50.00 REF		1.969 REF	
S1	50.00 REF		1.969 REF	
U	6.00 REF		0.236 REF	
U1	6.00 REF		0.236 REF	
V	39.40 REF		1.551 REF	
W	45.68 REF		1.798 REF	
Y	38.00 REF		1.496 REF	
Z	1.15	1.25	0.045	0.049
AA	16.21	16.31	0.638	0.642
AB	11.20	11.30	0.441	0.445
AC	8.99	9.09	0.354	0.358
AD	0.15	0.21	0.006	0.008
AE	0.762 BSC		0.030 BSC	
AF	0.18	0.28	0.007	0.011
AG	21.31	21.24	0.832	0.836
AH	35.00 REF		1.378 REF	
AJ	25.40 REF		1.000 REF	
AK	26.95 BSC		1.061 BSC	
AL	34.98 REF		1.377 REF	
AR	0.65	0.75	0.026	0.030
AS	0.50 BSC		0.020 BSC	
AT	0.60	0.70	0.024	0.028
AU	26.95 REF		1.061 REF	
AV	25.35	25.45	0.998	1.002
AV1	25.35	25.45	0.998	1.002

TB PACKAGE  
400 MIL TAB  
CASE 984A-01 (cont.)



BOTTOM VIEW

Literature Distribution Centers:

USA: Motorola Literature Distribution; P.O. Box 20912; Phoenix, Arizona 85036.

EUROPE: Motorola Ltd.; European Literature Centre; 88 Tanners Drive, Blakelands, Milton Keynes, MK14 5BP, England.

JAPAN: Nippon Motorola Ltd.; 4-32-1, Nishi-Gotanda, Shinagawa-ku, Tokyo 141, Japan.

ASIA PACIFIC: Motorola Semiconductors H.K. Ltd.; Silicon Harbour Center, No. 2 Dai King Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong.



CODELINE TO BE PLACED HERE

MCM101525/D

