

TENTATIVE (UNDER DEVELOPMENT)


TOSHIBA LED LAMP

## TLRE1002A (T02), TLSE1002A (T02), TLOE1002A (T02) TLYE1002A (T02), TLGE1002A (T02), TLPGE1002A (T02)

PANEL CIRCUIT INDICATOR

Unit in mm

- 2.0 × 1.25 × 1.1 mm (L × W × H)  
TL□E1002A (T02) Series
- InGaAlP LED
- It can be manufactured high-luminosity of equipment or reduce of electric power consumption by change in the high-luminosity LED from general-luminosity one.
- Colors : Red, Orange, Yellow, Green, Pure Green
- Can be mounted using surface mounter.
- Reflow soldering is possible.
- Standard embossed taping  
4 mm pitch : T02 (3000 pcs / reel)
- Applications : As backlighting source for battery-powered equipment  
As pilot light for compact equipment  
In low-power electronic equipment, etc.



Weight : 2 mg

### LINE-UP

| PRODUCT NAME | COLOR      | MATERIAL |
|--------------|------------|----------|
| TLRE1002A    | Red        | InGaAlP  |
| TLSE1002A    | Red        | InGaAlP  |
| TLOE1002A    | Orange     | InGaAlP  |
| TLYE1002A    | Yellow     | InGaAlP  |
| TLGE1002A    | Green      | InGaAlP  |
| TLPGE1002A   | Pure-Green | InGaAlP  |

961001EAC1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

MAXIMUM RATINGS (Ta = 25°C)

| PRODUCT NAME | FORWARD CURRENT (DC) I <sub>F</sub> (mA) | REVERSE VOLTAGE V <sub>R</sub> (V) | POWER DISSIPATION P <sub>D</sub> (mW) | OPERATION TEMPERATURE T <sub>opr</sub> (°C) | STORAGE TEMPERATURE T <sub>stg</sub> (°C) |
|--------------|--|------------------------------------|---------------------------------------|---|---|
| TLRE1002A    | 25                                       | 4                                  | 60                                    | -25~85                                      | -30~85                                    |
| TLSE1002A    |  |                                    | 60                                    |   |   |
| TLOE1002A    |  |                                    | 60                                    |   |   |
| TLYE1002A    |  |                                    | 60                                    |   |   |
| TLGE1002A    |  |                                    | 60                                    |   |   |
| TLPGE1002A   |  |                                    | 60                                    |   |   |

ELECTRICAL CHARACTERISTICS (Ta = 25°C)






| PRODUCT NAME | FORWARD VOLTAGE V <sub>F</sub> |      |     | I <sub>F</sub> | REVERSE CURRENT I <sub>R</sub> |                |
|--------------|--------------------------------|------|-----|----------------|--------------------------------|----------------|
|              | MIN                            | TYP. | MAX |                | MAX                            | V <sub>R</sub> |
| TLRE1002A    | —                              | 1.9  | 2.4 | 20             | 50                             | 4              |
| TLSE1002A    | —                              | 1.9  | 2.4 |                |                                |                |
| TLOE1002A    | —                              | 2.0  | 2.4 |                |                                |                |
| TLYE1002A    | —                              | 2.0  | 2.4 |                |                                |                |
| TLGE1002A    | —                              | 2.0  | 2.4 |                |                                |                |
| TLPGE1002A   | —                              | 2.1  | 2.4 |                |                                |                |
| UNIT         | V                              |      |     | mA             | μA                             | V              |

OPTICAL CHARACTERISTICS (Ta = 25°C)

| PRODUCT NAME | LUMINOUS INTENSITY I <sub>v</sub> |      |     |                | EMISSION SPECTRUM                       |      |     |    |                                    |     |      |                |
|--------------|-----------------------------------|------|-----|----------------|---|------|-----|----|------------------------------------|-----|------|----------------|
|              | MIN                               | TYP. | MAX | I <sub>F</sub> | Peak Emission Wavelength λ <sub>p</sub> |      |     | Δλ | Dominant Wavelength λ <sub>d</sub> |     |      | I <sub>F</sub> |
|              |                                   |      |     |                | MIN                                     | TYP. | MAX |    | TYP.                               | MIN | TYP. |                |
| TLRE1002A    | (27.2)                            | 70   | —   | 20             | —                                       | 644  | —   | 18 | —                                  | 630 | —    | 20             |
| TLSE1002A    | (47.6)                            | 135  | —   | 20             | —                                       | 623  | —   | 17 | —                                  | 613 | —    | 20             |
| TLOE1002A    | (47.6)                            | 150  | —   | 20             | —                                       | 612  | —   | 15 | —                                  | 605 | —    | 20             |
| TLYE1002A    | (27.2)                            | 105  | —   | 20             | —                                       | 590  | —   | 13 | —                                  | 587 | —    | 20             |
| TLGE1002A    | (27.2)                            | 70   | —   | 20             | —                                       | 574  | —   | 11 | —                                  | 571 | —    | 20             |
| TLPGE1002A   | (4.76)                            | 18   | —   | 20             | —                                       | 562  | —   | 11 | —                                  | 558 | —    | 20             |
| UNIT         | mcd                               |      |     | mA             | nm                                      |      |     | nm | nm                                 |     |      | mA             |

(Note) : This visible LED lamp also emits some IR light.  
 If a photodetector is located near the LED lamp, please ensure that it will not be affected by this IR light.





TLRE1002A-1



TLRE1002A-2  
[RADIATION PATTERN]


Ta = 25°C

Ta = 25°C




TLSE1002A-1


$I_F - V_F$




$I_V - I_F$




$I_V - T_c$



RELATIVE LUMINOUS INTENSITY - WAVELENGTH







$I_F - T_a$



TLSE1002A-2  
[RADIATION PATTERN]


Ta = 25°C

Ta = 25°C




TLOE1002A-1


$I_F - V_F$




$I_V - I_F$




$I_V - T_c$



RELATIVE LUMINOUS INTENSITY - WAVELENGTH







$I_F - T_a$



**TLOE1002A-2**  
[RADIATION PATTERN]






Ta = 25°C

Ta = 25°C









**TLYE1002A-1**



TLYE1002A-2  
[RADIATION PATTERN]


Ta = 25°C

Ta = 25°C




TLGE1002A-1


$I_F - V_F$




$I_V - I_F$




$I_V - T_c$



RELATIVE LUMINOUS INTENSITY - WAVELENGTH







$I_F - T_a$








TLGE1002A-2  
[RADIATION PATTERN]

Ta = 25°C

Ta = 25°C







TLPGE1002A-1



TLPGE1002A-2  
[RADIATION PATTERN]

Ta = 25°C

Ta = 25°C



**PACKAGING**

The LED devices is packed in an aluminum envelope with silica gel to avoid moisture absorption. The optical characteristics may be affected by exposure to moisture in the air before soldering and it should be stored under the following condition.

- Temperature : 5~30°C
- Relative Humidity : 60% or lower

Baking is required if the device have been stored with unopened for more than 6 months or if the aluminum envelope has been opened for more than 168 h.


Recommended baking condition is 60°C for 12 h minimum in the dry atmosphere.

**MOUNTING METHOD**

**SOLDERING**

- Reflow soldering

Temperature profile



- Second time reflow soldering

In case of second reflow soldering, it should be performed within 168 h after first reflow under the above conditions.

Storage conditions before second reflow soldering : 30°C, 60% RH or lower


- Do not perform flow soldering.
- Make any necessary soldering corrections manually.  
(Do not do this more than once for any given pin.)

Soldering iron : 25 W

Temperature : no more than 300°C

Time : within 3 s

- Recommended soldering pattern



**POST SOLDER CLEANING**

When cleaning after soldering is needed, the following condition must be adhered to.

- Cleaning solvents : AK225 or Alcohol
- Temperature : 50°C (max) for 30 s (max) or 30°C (max) for 3 minutes (max)
- Ultrasonic : 300 W max

**PRECAUTION FOR MOUNTING**

- Do not apply force to the plastic part of the LED in high temperature conditions.
- Do not apply friction using a hard materials for avoid injuring the plastic part of the LED.
- Keep the LED away from any other parts when assembling boards into the set.


**TAPING SPECIFICATIONS**

This specification lays out the 4 mm pitch embossed-tape packing requirements for 2.0 mm (L) × 1.25 mm (W) × 1.1 mm (H) size surface-mount LED lamp.

**1. Product Naming System**

The type of package used for shipment is denoted by a symbol suffix after the product number. The method of classification is as below. (this method, however does not apply to products whose electrical characteristics differ from standard Toshiba specifications)

- (1) Tape Type : T02 (4 mm pitch)
- (2) Example



**2. Related Matter**

**(1) Electro-optical Characteristics**

Please refer to the each technical datasheet for electro-optical characteristics of tape packed products

**(2) Handling Precautions**

Tape material protected against static electricity. However, static electricity may occur depending on quantity of charged static electricity and a device may attach to a tape, or a device may be unstable when peeling a tape cover.


- a) In process, taping materials may sustain an electrostatic charge, use an ionizer to neutralize the ions.
- b) For transport and temporary storage of devices, use containers (boxes, jigs, bags) that are made of anti-static materials or of materials that dissipate electrostatic electricity.



3. Tape Dimensions


(Unit in mm)

| SYMBOL         | DIMENSION | TOLERANCE | SYMBOL         | DIMENSION | TOLERANCE |
|----------------|-----------|-----------|----------------|-----------|-----------|
| D              | 1.50      | +0.1 / -0 | P <sub>2</sub> | 2.00      | ±0.05     |
| E              | 1.75      | ±0.1      | W              | 8.00      | ±0.3      |
| P <sub>0</sub> | 4.00      | ±0.1      | P              | 4.00      | ±0.1      |
| t              | 0.25      | ±0.05     | A <sub>0</sub> | 1.45      | ±0.1      |
| F              | 3.50      | ±0.05     | B <sub>0</sub> | 2.25      | ±0.1      |
| D <sub>1</sub> | 1.10      | ±0.1      | K <sub>0</sub> | 1.30      | ±0.05     |




4. Reel Dimensions

Unit in mm



5. Leader and Trailer



6. Packing Form

(1) Number of Devices per Reel and Carton

|        |               |
|--------|---------------|
| Reel   | 3000 devices  |
| Carton | 15000 devices |

(2) Packing : Silica gel and reel are packed into sealed aluminum pack.


7. Notation Method

(1) Example : TLRE1002A (T02)

P/N :

|        |               |      |            |
|--------|---------------|------|------------|
| TYPE   | TLRE1002A     |      |            |
| ADD. C | (T02)         | Q'TY | 3000 pcs   |
| NOTE   | (rank symbol) |      | Lot Number |

(2) Label location :



Aluminum pack : Attached to center of one side