


TOSHIBA LED LAMP

S4F43Q1 (T10), S4F43Z1 (T10)

PANEL CIRCUIT INDICATOR

Unit in mm

- Surface Mount Device
- 3.2 (L) × 2.8 (W) × 3.4 (H) mm Size
- φ2.8 mm Diameter Lens-top Type
- InGaAlP LED (High-Bright type)
- Line-up
2 Colors : Green, Pure Green
- Available of Automounting Machine Use
- Low Drive Current, High Intensity Light Emission
- Clear luminescence is obtained.
- High Operating Temperature : $T_{opr} \cdot T_{stg} \quad -40 \sim 100^{\circ}\text{C}$
- Standard Embossed Taping
8 mm Pitch : T10 (500 pcs / reel)
- Applications : Automotive use, Message Signboard, Backlight, etc.



Weight : 42 mg

LINE-UP

| PRODUCT NAME | COLOR | MATERIAL |
|--------------|------------|----------|
| S4F43Q1 | Green | InGaAlP |
| S4F43Z1 | Pure Green | InGaAlP |

MAXIMUM RATINGS (Ta = 25°C)

| PRODUCT NAME | FORWARD CURRENT I _F (mA) | REVERSE VOLTAGE V _R (V) | POWER DISSIPATION P _D (mW) | OPERATING TEMPERATURE T _{opr} (°C) | STORAGE TEMPERATURE T _{stg} (°C) |
|--------------|--|---------------------------------------|--|--|--|
| S4F43Q1 | 50 | 4 | 140 | -40~100 | -40~100 |
| S4F43Z1 | 50 | 4 | 140 | | |

961001EAC1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

| PRODUCT NAME | FORWARD VOLTAGE V_F | | | | REVERSE CURRENT I_R | |
|--------------|--------------------------|------|-----|-------|--------------------------|-------|
| | MIN | TYP | MAX | I_F | MAX | V_R |
| S4F43Q1 | — | 2.27 | 2.8 | 20 | 50 | 4 |
| S4F43Z1 | — | 2.27 | 2.8 | 20 | 50 | 4 |
| Unit | V | | | mA | μ A | V |

OPTICAL CHARACTERISTICS-1 (Ta = 25°C)





| PRODUCT NAME | LUMINOUS INTENSITY I_V | | | |
|--------------|-----------------------------|------|-----|-------|
| | MIN | TYP. | MAX | I_F |
| S4F43Q1 | 85 | 250 | — | 20 |
| S4F43Z1 | 27.2 | 60 | — | 20 |
| Unit | mcd | | | mA |

OPTICAL CHARACTERISTICS-2 (Ta = 25°C)



| PRODUCT NAME | EMISSION SPECTRUM | | | | | | | I_F |
|--------------|--------------------------------------|------|-----|-----------------|---------------------------------|------|-----|-------|
| | Peak Emission Wavelength λ_p | | | $\Delta\lambda$ | Dominant Wavelength λ_d | | | |
| | MIN | TYP. | MAX | | MIN | TYP. | MAX | |
| S4F43Q1 | — | 574 | — | 11 | — | 571 | — | 20 |
| S4F43Z1 | — | 562 | — | 11 | — | 558 | — | 20 |
| UNIT | nm | | | nm | nm | | | mA |

(Note) : This visible LED lamp also emits some IR light.
 If a photodetector is located near the LED lamp, please ensure that it will not be affected by this IR light.





S4F43Q1





RADIATION PATTERN



S4F43Z1




RADIATION PATTERN



SOLDERING


Reflow soldering

Temperature profile



(*) Reflow is permitted just one time.

Recommended soldering pattern



RECOMMENDATION FOR MANUAL SOLDERING

- Soldering iron : Less than 25 W
- Temperature : Lower than 300°C
- Time : Within 3 s

POST SOLDERING CLEANING

When cleaning after soldering is needed, the following condition must be adhered to.

- Cleaning solvents : AK225 or Alcohol
- Temperature : 50°C (max) for 30 s (max) or 30°C (max) for 3 minutes (max)
- Ultrasonic : 300 W max

PACKAGING

This LED device is packed in an aluminum envelope with silica gel to avoid moisture absorption. The optical characteristics may be affected by exposure to moisture in the air before soldering and it should be stored under the following conditions.

- Temperature : 5~30°C
- Relative Humidity : 60% or lower

Baking is required if the device have been stored with unopened for more than 6 months or if the aluminum envelope has been opened for more than 168 h.
Recommended baking condition is 60°C for 12 h minimum in the dry atmosphere.

PRECAUTION FOR MOUNTING

Do not apply force to the plastic part of the LED in high temperature conditions.
Do not apply friction using a hard materials for avoid injuring the plastic part of the LED.
Keep the LED away from any other parts when assembling boards into the set.


TAPING SPECIFICATIONS

1. Taping Number

- (1) Name : T10
 - (2) Example : S4F43□ (T10)
- └─ Tape Specification
└─ Device Identifier


2. Dimension of tape

| ITEM | DIMENSIONS | TOLERANCE | ITEM | DIMENSIONS | TOLERANCE |
|----------------|------------|-----------|----------------|------------|-----------|
| D | 1.5 | +0.1 / -0 | P ₂ | 2.0 | ±0.05 |
| E | 1.75 | ±0.1 | W | 12.0 | ±0.3 |
| P ₀ | 4.0 | ±0.1 | P | 8.0 | ±0.1 |
| t | 0.3 | ±0.05 | A ₀ | 2.9 | ±0.1 |
| F | 5.5 | ±0.05 | B ₀ | 3.7 | ±0.1 |
| D ₁ | 1.5 | +0.1 / -0 | K ₀ | 3.6 | ±0.1 |




3. Dimension of reel

(Unit in mm)



4. Leading part

(Unit in mm)



5. Packing Form

(1) Number of Devices per Reel and Carton

| | |
|--------|--------------|
| Reel | 500 devices |
| Carton | 2500 devices |

(2) Packing : Silica gel and reel are packed into sealed aluminum pack.


6. Notation Method

(1) Example : S4F43Q1 (T09)

P/N :

| | | | |
|--------|---------------|------|------------|
| TYPE | S4F43Q1 | | |
| ADD. C | (T09) | Q'TY | 500 pcs |
| NOTE | (rank symbol) | | Lot Number |

(2) Label location :



Aluminum pack : Attached to center of one side