

30W L-BAND POWER GaAs FET N-CANNEL GaAs MES FET

DESCRIPTION

The NES1821B-30 is power GaAs FET which provides high output power and high gain in the 1.8-2.1 GHz band.

Internal input matching circuits are designed to optimize performance. The device has a $0.8 \mu\text{m}$ gate length for increased linear gain. To reduce thermal resistance, the device uses PHS (Plated Heat Sink) technology.

The device incorporates WSi (tungsten silicide) gate for high reliability and SiO_2 glassivation for surface stability.

FEATURES

- High output power
- High gain
- High power added efficiency
- Internally matched input
- High reliability


ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$)

Drain to Source Voltage	V_{DS}	15	V
Gate to Source Voltage	V_{GS}	-7	V
Gate to Drain Voltage	V_{GD}	-18	V
Drain Current	I_D	27	A
Gate Current	I_G	180	mA
Total Power Dissipation	$P_T^{(*)}$	110	W
Channel Temperature	T_{ch}	175	$^\circ\text{C}$
Storage Temperature	T_{stg}	-65 to +175	$^\circ\text{C}$

* $T_C = 25^\circ\text{C}$

Caution Please handle this device at static-free workstation, because this is an electrostatic sensitive device.

PACKAGE DIMENSIONS (UNIT: mm)



ELECTRICAL CHARACTERISTICS (T_A = 25 °C)

CHARACTERISTICS	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
Saturated Drain Current	I _{DSS}	--	18.0	--	A	V _{DS} = 2.5 V, V _{GS} = 0 V
Pinch-off Voltage	V _P	-4.0	-2.6	--	V	V _{DS} = 2.5 V, I _D = 80 mA
Thermal Resistance	R _{th}	--	1.4	1.7	°C/W	Channel to Case
Output Power	P _O *1	44.5	45.0	--	dBm	freq. = 1.96 GHz
Linear Gain	GL	11.0	13.0	--	dB	V _{DS} = 10 V I _D = 1.0 A set
Drain Current	I _D *2	--	2.5	--	A	R _g = 30 Ω *3

*1 PIN = 35.5 dBm

*2 P_O = 37 dBm

RECOMMENDING OPERATING LIMITS

R _g *3 (Ω)	V _{DS} (V)	T _{ch} (°C)	G.C.P *4
30	to 10	to 125	to 3 dB comp


Note

*3 R_g is the series resistance between the gate supply and the FET gate.

*4 G.C.P: Gain Compression Point

TYPICAL RF PERFORMANCE

f = 1.96 GHz, Vd = 10 V, Id = 1 A set, Rg = 30 Ω



S-PARAMETER

V_{DS} = 10 V, I_{DS} = 1 A set

FREQUENCY MHz	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
1 600.000	0.793	114.8	1.210	-18.4	0.027	-92.7	0.903	144.0
1 610.000	0.786	113.9	1.235	-20.1	0.028	-94.2	0.904	143.5
1 620.000	0.779	113.0	1.256	-21.2	0.029	-95.7	0.908	143
1 630.000	0.774	112.2	1.286	-21.8	0.030	-97.7	0.909	142.5
1 640.000	0.766	111.3	1.337	-22.3	0.032	-100.4	0.912	141.8
1 650.000	0.758	110.4	1.412	-23	0.033	-103.3	0.914	141.3
1 660.000	0.752	109.4	1.511	-24.7	0.034	-106.6	0.919	140.7
1 670.000	0.744	108.5	1.616	-27.7	0.035	-109.7	0.920	140.0
1 680.000	0.736	107.4	1.711	-32.0	0.036	-112.6	0.924	139.3
1 690.000	0.728	106.4	1.768	-36.8	0.036	-114.6	0.927	138.5
1 700.000	0.720	105.3	1.791	-41.4	0.036	-116.1	0.929	137.6
1 710.000	0.710	104.2	1.783	-45.5	0.037	-116.8	0.931	136.9
1 720.000	0.698	103.0	1.758	-48.3	0.039	-117.4	0.934	136.0
1 730.000	0.688	101.9	1.748	-49.8	0.041	-118.1	0.936	134.9
1 740.000	0.675	100.6	1.763	-50.2	0.045	-119.6	0.938	133.8
1 750.000	0.662	99.3	1.822	-49.9	0.049	-122.5	0.940	132.7
1 760.000	0.646	98.0	1.947	-50.1	0.052	-126.5	0.940	131.4
1 770.000	0.631	96.5	2.136	-51.7	0.055	-131.1	0.939	130.2
1 780.000	0.614	94.9	2.350	-55.6	0.057	-136.0	0.937	128.6
1 790.000	0.593	93.3	2.547	-61.2	0.059	-140.2	0.934	127.0
1 800.000	0.571	91.6	2.682	-67.6	0.060	-143.8	0.929	125.2
1 810.000	0.546	89.8	2.742	-73.9	0.062	-146.4	0.923	123.4
1 820.000	0.519	87.9	2.749	-79.0	0.065	-148.6	0.916	121.3
1 830.000	0.488	85.9	2.748	-83.0	0.068	-151.0	0.907	119.1
1 840.000	0.453	83.9	2.771	-86.0	0.073	-154.1	0.891	116.5
1 850.000	0.411	81.9	2.846	-88.3	0.080	-158.1	0.870	113.6
1 860.000	0.362	80.3	3.006	-90.9	0.086	-163.4	0.845	110.5
1 870.000	0.307	79.5	3.249	-94.8	0.093	-169.5	0.814	107.1
1 880.000	0.243	80.9	3.544	-100.6	0.098	-175.9	0.774	103.2
1 890.000	0.176	88.9	3.819	-108.4	0.104	177.3	0.721	99.1
1 900.000	0.124	113.0	4.028	-117.1	0.109	170.1	0.651	94.9
1 910.000	0.134	152.3	4.143	-125.9	0.113	162.4	0.569	90.6
1 920.000	0.208	172.6	4.189	-134.3	0.117	154.1	0.470	87.5
1 930.000	0.307	177.0	4.201	-142.6	0.118	145.0	0.360	86.5
1 940.000	0.410	175.3	4.179	-151.0	0.117	135.9	0.253	91.9
1 950.000	0.511	170.6	4.110	-159.7	0.115	127.2	0.174	112.1
1 960.000	0.602	164.9	3.967	-168.2	0.111	118.9	0.168	147.0
1 970.000	0.678	158.9	3.762	-176.3	0.107	111.1	0.230	168.2
1 980.000	0.739	152.9	3.531	176.3	0.101	103.6	0.312	175.3
1 990.000	0.787	147.3	3.299	169.6	0.094	96.5	0.391	176.5
2 000.000	0.822	142.2	3.081	163.3	0.088	90.5	0.462	175.3
2 010.000	0.848	137.5	2.850	157.0	0.081	85.3	0.524	173.4
2 020.000	0.865	133.2	2.607	151.2	0.076	81.0	0.576	171.2
2 030.000	0.880	129.2	2.363	146.2	0.071	77.2	0.623	168.9
2 040.000	0.887	125.7	2.129	142.6	0.068	73.5	0.661	166.6
2 050.000	0.892	122.5	1.927	140.2	0.065	69.3	0.695	164.6
2 060.000	0.895	119.4	1.772	138.9	0.062	64.3	0.724	162.6
2 070.000	0.898	116.5	1.670	138.0	0.059	58.7	0.747	160.7
2 080.000	0.897	113.8	1.613	136.6	0.054	53.5	0.768	158.7
2 090.000	0.896	111.1	1.583	134.1	0.050	49.2	0.788	157.1
2 100.000	0.894	108.7	1.546	130.3	0.045	45.9	0.804	155.5
2 110.000	0.891	106.3	1.485	125.4	0.041	44.6	0.819	154.0
2 120.000	0.887	103.9	1.386	120.2	0.038	43.6	0.831	152.7
2 130.000	0.884	101.7	1.265	116.0	0.036	43.7	0.842	151.3
2 140.000	0.879	99.5	1.141	113.2	0.035	43.5	0.851	150
2 150.000	0.875	97.2	1.031	112.1	0.035	42.4	0.860	148.7
2 160.000	0.871	95.1	0.949	112.6	0.035	39.7	0.871	147.5
2 170.000	0.865	93.0	0.897	114	0.034	35.5	0.879	146.4
2 180.000	0.861	90.9	0.880	115.0	0.033	30.5	0.885	145.4
2 190.000	0.856	88.6	0.888	114.7	0.030	26.0	0.892	144.2

[MEMO]

[MEMO]

[MEMO]

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Corporation. NEC Corporation assumes no responsibility for any errors which may appear in this document.

NEC Corporation does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from use of a device described herein or any other liability arising from use of such device. No license, either express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Corporation or others.

While NEC Corporation has been making continuous effort to enhance the reliability of its semiconductor devices, the possibility of defects cannot be eliminated entirely. To minimize risks of damage or injury to persons or property arising from a defect in an NEC semiconductor device, customers must incorporate sufficient safety measures in its design, such as redundancy, fire-containment, and anti-failure features.

NEC devices are classified into the following three quality grades:

"Standard", "Special", and "Specific". The Specific quality grade applies only to devices developed based on a customer designated "quality assurance program" for a specific application. The recommended applications of a device depend on its quality grade, as indicated below. Customers must check the quality grade of each device before using it in a particular application.

Standard: Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots

Special: Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)

Specific: Aircrafts, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems or medical equipment for life support, etc.

The quality grade of NEC devices is "Standard" unless otherwise specified in NEC's Data Sheets or Data Books. If customers intend to use NEC devices for applications other than those specified for Standard quality grade, they should contact an NEC sales representative in advance.

Anti-radioactive design is not implemented in this product.