


FRD Type :10ELS1

FEATURES

OUTLINE DRAWING

- * Miniature Size
- * Fast Recovery and Low Price
- * High Surge Capability
- * 100volts through 600volts Types Available
- * 26mm and 52mm Inside Tape Spacing



Maximum Ratings

Approx Net Weight:0.17g

Rating		Symbol	10ELS1			Unit		
Repetitive Peak Reverse Voltage		V _{RRM}	100			V		
Non-repetitive Peak Reverse Voltage		V _{RSM}	250			V		
Average Rectified Output Current	P.C.Board Mounted *	I _O	1	T _a =26°C	Half Sine Wave Resistive Load	A		
RMS Forward Current		I _{F(RMS)}	1.57			A		
Surge Forward Current		I _{FSM}	30	Half Sine Wave, 1cycle, Non-repetitive		A		
Operating Junction Temperature Range		T _{jw}	- 40 to + 150			°C		
Storage Temperature Range		T _{stg}	- 40 to + 150			°C		

Electrical • Thermal Characteristics

Characteristics	Symbol	Conditions	Min	Typ	Max	Unit
Peak Reverse Current	I _{RM}	T _j = 25°C, V _{RM} = V _{RRM}	-	-	10	µA
Peak Forward Voltage	V _{FM}	T _j = 25°C, I _{FM} = 1 A	-	-	1.1	V
Reverse Recovery Time	trr	I _{FM} = 1 A, -di/dt= 50 A/µs, T _a = 25°C	-	-	150	ns
Thermal Resistance	R _{th(j-a)}	Without Fin or P.C.Board*	-	-	100	°C/W

*:L=3mm, Print Lands = 7x7 mm, Both Sides

10ELS1 OUTLINE DRAWING (Dimensions in mm)

