


# SBD Type :11EQ09

## FEATURES

- \* Miniature Size
- \* Low Forward Voltage drop
- \* Low Power Loss, High Efficiency
- \* High Surge Capability
- \* 40 Volts thru 100 Volts Types Available
- \* 26mm&52mm Inside Tape Spacing Package Available

## OUTLINE DRAWING



©

## Maximum Ratings

Approx Net Weight:0.21g

Rating		Symbol	11EQ09			Unit	
Repetitive Peak Reverse Voltage		V <sub>RRM</sub>	90			V	
Average Rectified Output Current	Without Fin or P.C.Board	I <sub>O</sub>	1.0	T <sub>a</sub> =30°C*	50Hz Half Sine Wave Resistive Load	A	
	P.C.Board mounted		1.0	T <sub>a</sub> =60°C*			
RMS Forward Current		I <sub>F(RMS)</sub>	1.57			A	
Surge Forward Current		I <sub>FSM</sub>	40	50Hz Half Sine Wave,1cycle, Non-repetitive			
Operating JunctionTemperature Range		T <sub>jw</sub>	- 40 to + 150			°C	
Storage Temperature Range		T <sub>stg</sub>	- 40 to + 150			°C	

## Electrical • Thermal Characteristics

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Current	I <sub>RM</sub>	T <sub>j</sub> = 25°C, V <sub>RM</sub> = V <sub>RRM</sub>	-	-	0.5	mA
Peak Forward Voltage	V <sub>FM</sub>	T <sub>j</sub> = 25°C, I <sub>FM</sub> = 1.0A	-	-	0.85	V
Thermal Resistance (Junction to Ambient)	R <sub>th(j-a)</sub>	Without Fin or P.C.Board	-	-	140	°C/W
		P.C.Board mounted			105	

\*:Print Lands=5x5mm,Both Sides

11EQ09 OUTLINE DRAWING (Dimensions in mm)

