


SBD Type : EA20QS10

OUTLINE DRAWING

FEATURES

- * TO-251AA Case
- * Low Forward Voltage drop
- * Low Power Loss
- * High Surge Capability
- * 40 Volts thru 100 Volts Types Available



Maximum Ratings

Approx Net Weight:0.35g


| Rating | Symbol | EA20QS10 | | | Unit |
|--------------------------------------|--------------|---------------|---|------------------------------------|-------------|
| Repetitive Peak Reverse Voltage | V_{RRM} | 100 | | | V |
| Average Rectified Output Current | I_O | 1.7 | $T_a=28^{\circ}C$ | 50Hz Half Sine Wave Resistive Load | A |
| | | 1.7 | $T_c=138^{\circ}C$ | | |
| RMS Forward Current | $I_{F(RMS)}$ | 2.67 | | | A |
| Surge Forward Current | I_{FSM} | 40 | 50Hz Half Sine Wave, 1cycle, Non-repetitive | | A |
| Operating Junction Temperature Range | T_{jw} | - 40 to + 150 | | | $^{\circ}C$ |
| Storage Temperature Range | T_{stg} | - 40 to + 150 | | | $^{\circ}C$ |

Electrical • Thermal Characteristics

| Characteristics | | Symbol | Conditions | Min | Typ | Max | Unit |
|----------------------|---------------------|---------------|-----------------------------------|-----|-----|------|---------------|
| Peak Reverse Current | | I_{RM} | $T_j=25^{\circ}C, V_{RM}=V_{RRM}$ | - | - | 1.0 | mA |
| Peak Forward Voltage | | V_{FM} | $T_j=25^{\circ}C, I_{FM}= 2 A$ | - | - | 0.85 | V |
| Thermal Resistance | Junction to Ambient | $R_{th(j-a)}$ | P.C.Board mounted * | - | - | 80 | $^{\circ}C/W$ |
| | Junction to Case | $R_{th(j-c)}$ | - | - | - | 7 | $^{\circ}C/W$ |

* Print Land = 20x20 mm

EA20QS10 OUTLINE DRAWING (Dimensions in mm)



Single Chip

