

SINGLE-SUPPLY DUAL OPERATIONAL AMPLIFIER

■ GENERAL DESCRIPTION

The NJM2141 is a high gain, high output current dual operational amplifier in ultra miniature surface mount package, which drive $\pm 25\text{mA}$ at extremely low operating voltages ($V^+/V^- = \pm 2\text{V}$).

The NJM2141 realize wide bandwidth, low noise, high slew rate and low distortion, which is suitable for audio, telecommunication and instrumentation applications.

■ PACKAGE OUTLINE




NJM2141R

■ FEATURES

- Operating Voltage $(\pm 2\text{V} \sim \pm 10\text{V})$
- Slew Rate $(3\text{V}/\mu\text{s typ.})$
- Bandwidth (8MHz typ.)
- High Output Current $(I_o = 25\text{mA})$
- Bipolar Technology
- Package Outline VSP8


■ PIN CONFIGURATION



PIN FUNCTION

1. A OUTPUT
2. A- INPUT
3. A+ INPUT
4. V^-
5. B+ INPUT
6. B- INPUT
7. B OUTPUT
8. V^+

■ EQUIVALENT CIRCUIT (1/2 Shown)



■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V ⁺ /V ⁻	±10	V
Differential Input Voltage	V _{ID}	±15	V
Input Voltage	V _{IC}	±7.5(note 1)	V
Power Dissipation	P _D	320	mW
Operating Temperature Range	T _{opr}	-20~75	°C
Storage Temperature Range	T _{stg}	-40~125	°C







(note 1) : When input voltage is less than ±7.5V, the absolute maximum control voltage is equal to the input voltage.

■ ELECTRICAL CHARACTERISTICS

(V⁺/V⁻=5V, Ta=25°C)






PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Input Offset Voltage	V _{IO}	R _S =0Ω	—	0.5	6	mV
Input Offset Current	I _{IO}		—	5	200	nA
Input Bias Current	I _B		—	80	500	nA
Input Resistance	R _{IN}		0.3	2.5		MΩ
Large Signal Voltage Gain	A _V	R _L ≥2kΩ, V _O =±4V	86	100	—	dB
Maximum Output Voltage Swing1	V _{OM1}	R _L ≥2kΩ	+4.0 -3.5	+5.0 -4.5	—	V
Maximum Output Voltage Swing2	V _{OM2}	V ⁺ /V ⁻ =±9V, I _O =25mA	+4.0 -4.0	+6.0 -5.0	—	V
Input Common Mode Voltage Range	V _{ICM}		±4.0	±4.5	—	V
Common Mode Rejection Ratio	CMR	R _S ≤10kΩ	70	90	—	dB
Supply Voltage Rejection Ratio	SVR	R _S ≤10kΩ	76.5	90	—	dB
Operating Current	I _{CC}		—	2.7	5.7	mA
Slew Rate	SR		—	3	—	V/μs
Gain Bandwidth Product	GB		—	8	—	MHz
Equivalent Input Noise Voltage	V _{NI}	RIAA, R _S =2kΩ, 39kHz LPF	—	1.2	—	μV _{rms}

■ TYPICAL CHARACTERISTICS



4

TYPICAL CHARACTERISTICS



MEMO

[CAUTION]

The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.