

LM119/LM219/LM319 High Speed Dual Comparator

General Description

The LM119 series are precision high speed dual comparators fabricated on a single monolithic chip. They are designed to operate over a wide range of supply voltages down to a single 5V logic supply and ground. Further, they have higher gain and lower input currents than devices like the LM710. The uncommitted collector of the output stage makes the LM119 compatible with RTL, DTL and TTL as well as capable of driving lamps and relays at currents up to 25 mA.

The LM319A offers improved precision over the standard LM319, with tighter tolerances on offset voltage, offset current, and voltage gain.

Features


- Two independent comparators

- Operates from a single 5V supply
- Typically 80 ns response time at $\pm 15V$
- Minimum fan-out of 2 each side
- Maximum input current of 1 μA over temperature
- Inputs and outputs can be isolated from system ground
- High common mode slew rate

Although designed primarily for applications requiring operation from digital logic supplies, the LM119 series are fully specified for power supplies up to $\pm 15V$. It features faster response than the LM111 at the expense of higher power dissipation. However, the high speed, wide operating voltage range and low package count make the LM119 much more versatile than older devices like the LM711.

The LM119 is specified from $-55^{\circ}C$ to $+125^{\circ}C$, the LM219 is specified from $-25^{\circ}C$ to $+85^{\circ}C$, and the LM319A and LM319 are specified from $0^{\circ}C$ to $+70^{\circ}C$.

Connection Diagram



Note 1: Also available per SMD# 8601401 or JM38510/10306

Top View
Order Number **LM119J, LM119J/883** (Note 1),
LM219J, LM319J, LM319AM, LM319M,
LM319AN or LM319N
See NS Package Number **J14A, M14A or N14A**

Absolute Maximum Ratings (Note 8)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

| | |
|---|----------------|
| Total Supply Voltage | 36V |
| Output to Negative Supply Voltage | 36V |
| Ground to Negative Supply Voltage | 25V |
| Ground to Positive Supply Voltage | 18V |
| Differential Input Voltage | ±5V |
| Input Voltage (Note 2) | ±15V |
| ESD rating (1.5 kΩ in series with 100 pF) | 800V |
| Power Dissipation (Note 3) | 500 mW |
| Output Short Circuit Duration | 10 sec |
| Storage Temperature Range | -65°C to 150°C |

| | |
|---------------------------------------|-------|
| Lead Temperature (Soldering, 10 sec.) | 260°C |
| Soldering Information | |
| Dual-In-Line Package | |
| Soldering (10 seconds) | 260°C |
| Small Outline Package | |
| Vapor Phase (60 seconds) | 215°C |
| Infrared (15 seconds) | 220°C |

See AN-450 "Surface Mounting Methods and Their Effect on Product Reliability" for other methods of soldering surface mount devices.

Operating Temperature Range

| | |
|-------|----------------|
| LM119 | -55°C to 125°C |
| LM219 | -25°C to 85°C |

Electrical Characteristics (Note 4)

| Parameter | Conditions | LM119/LM219 | | | Units |
|-------------------------------|--|-------------|------|------|-------|
| | | Min | Typ | Max | |
| Input Offset Voltage (Note 5) | $T_A = 25^\circ\text{C}$, $R_S \leq 5\text{k}$ | | 0.7 | 4.0 | mV |
| Input Offset Current (Note 5) | $T_A = 25^\circ\text{C}$ | | 30 | 75 | nA |
| Input Bias Current | $T_A = 25^\circ\text{C}$ | | 150 | 500 | nA |
| Voltage Gain | $T_A = 25^\circ\text{C}$ (Note 7) | 10 | 40 | | V/mV |
| Response Time (Note 6) | $T_A = 25^\circ\text{C}$, $V_S = \pm 15\text{V}$ | | 80 | | ns |
| Saturation Voltage | $V_{IN} \leq -5\text{ mV}$, $I_{OUT} = 25\text{ mA}$ $T_A = 25^\circ\text{C}$ | | 0.75 | 1.5 | V |
| Output Leakage Current | $V_{IN} \geq 5\text{ mV}$, $V_{OUT} = 35\text{V}$ $T_A = 25^\circ\text{C}$ | | 0.2 | 2 | μA |
| Input Offset Voltage (Note 5) | $R_S \leq 5\text{k}$ | | | 7 | mV |
| Input Offset Current (Note 5) | | | | 100 | nA |
| Input Bias Current | | | | 1000 | nA |
| Input Voltage Range | $V_S = \pm 15\text{V}$ $V^+ = 5\text{V}$, $V^- = 0$ | -12 | ±13 | +12 | V |
| Saturation Voltage | $V^+ \geq 4.5\text{V}$, $V^- = 0$ $V_{IN} \leq -6\text{ mV}$, $I_{SINK} \leq 3.2\text{ mA}$ $T_A \geq 0^\circ\text{C}$ $T_A \leq 0^\circ\text{C}$ | | 0.23 | 0.4 | V |
| | | | | 0.6 | V |
| Output Leakage Current | $V_{IN} \geq 5\text{ mV}$, $V_{OUT} = 35\text{V}$, $V^- = V_{GND} = 0\text{V}$ | | 1 | 10 | μA |
| Differential Input Voltage | | | | ±5 | V |
| Positive Supply Current | $T_A = 25^\circ\text{C}$, $V^+ = 5\text{V}$, $V^- = 0$ | | 4.3 | | mA |
| Positive Supply Current | $T_A = 25^\circ\text{C}$, $V_S = \pm 15\text{V}$ | | 8 | 11.5 | mA |
| Negative Supply Current | $T_A = 25^\circ\text{C}$, $V_S = \pm 15\text{V}$ | | 3 | 4.5 | mA |

Note 2: For supply voltages less than ±15V the absolute maximum input voltage is equal to the supply voltage.

Note 3: The maximum junction temperature of the LM119 is 150°C, while that of the LM219 is 110°C. For operating at elevated temperatures, devices in the H10 package must be derated based on a thermal resistance of 160°C/W, junction to ambient, or 19°C/W, junction to case. The thermal resistance of the J14 and N14 packages is 100°C/W, junction to ambient.

Note 4: These specifications apply for $V_S = \pm 15\text{V}$, and the Ground pin at ground, and $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$, unless otherwise stated. With the LM219, however, all temperature specifications are limited to $-25^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$. The offset voltage, offset current and bias current specifications apply for any supply voltage from a single 5V supply up to ±15V supplies. Do not operate the device with more than 16V from ground to V_S .

Note 5: The offset voltages and offset currents given are the maximum values required to drive the output within a volt of either supply with a 1 mA load. Thus, these parameters define an error band and take into account the worst case effects of voltage gain and input impedance.

Note 6: The response time specified (see definitions) is for a 100 mV input step with 5 mV overdrive.

Note 7: Output is pulled up to 15V through a 1.4 kΩ resistor.

Note 8: Refer to RETS119X for LM119H/883 and LM119J/883 specifications.

Absolute Maximum Ratings

LM319A/319 (Note 8)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/ Distributors for availability and specifications.

| | |
|---|--------|
| Total Supply Voltage | 36V |
| Output to Negative Supply Voltage | 36V |
| Ground to Negative Supply Voltage | 25V |
| Ground to Positive Supply Voltage | 18V |
| Differential Input Voltage | ±5V |
| Input Voltage (Note 9) | ±15V |
| Power Dissipation (Note 10) | 500 mW |
| Output Short Circuit Duration | 10 sec |
| ESD rating (1.5 kΩ in series with 100 pF) | 800V |

| | |
|---------------------------------------|----------------|
| Storage Temperature Range | -65°C to 150°C |
| Lead Temperature (Soldering, 10 sec.) | 260°C |
| Soldering Information | |
| Dual-In-Line Package | |
| Soldering (10 sec.) | 260°C |
| Small Outline Package | |
| Vapor Phase (60 sec.) | 215°C |
| Infrared (15 sec.) | 220°C |

See AN-450 "Surface Mounting Methods and Their Effect on Product Reliability" for other methods of soldering surface mount devices.

Operating Temperature Range

| | |
|---------------|-------------|
| LM319A, LM319 | 0°C to 70°C |
|---------------|-------------|

Electrical Characteristics (Note 11)

| Parameter | Conditions | LM319A | | | LM319 | | | Units |
|--------------------------------|---|--------|------|------|-------|------|------|-------|
| | | Min | Typ | Max | Min | Typ | Max | |
| Input Offset Voltage (Note 12) | $T_A = 25^\circ\text{C}$, $R_S \leq 5\text{k}$ | | 0.5 | 1.0 | | 2.0 | 8.0 | mV |
| Input Offset Current (Note 12) | $T_A = 25^\circ\text{C}$ | | 20 | 40 | | 80 | 200 | nA |
| Input Bias Current | $T_A = 25^\circ\text{C}$ | | 150 | 500 | | 250 | 1000 | nA |
| Voltage Gain | $T_A = 25^\circ\text{C}$ (Note 14) | 20 | 40 | | 8 | 40 | | V/mV |
| Response Time (Note 13) | $T_A = 25^\circ\text{C}$, $V_S = \pm 15\text{V}$ | | 80 | | | 80 | | ns |
| Saturation Voltage | $V_{IN} \leq -10\text{ mV}$, $I_{OUT} = 25\text{ mA}$ $T_A = 25^\circ\text{C}$ | | 0.75 | 1.5 | | 0.75 | 1.5 | V |
| Output Leakage Current | $V_{IN} \geq 10\text{ mV}$, $V_{OUT} = 35\text{V}$, $V^- = V_{GND} = 0\text{V}$, $T_A = 25^\circ\text{C}$ | | 0.2 | 10 | | 0.2 | 10 | μA |
| Input Offset Voltage (Note 12) | $R_S \leq 5\text{k}$ | | | 10 | | | 10 | mV |
| Input Offset Current (Note 12) | | | | 300 | | | 300 | nA |
| Input Bias Current | | | | 1000 | | | 1200 | nA |
| Input Voltage Range | $V_S = \pm 15\text{V}$ $V^+ = 5\text{V}$, $V^- = 0$ | 1 | ±13 | 3 | 1 | ±13 | 3 | V |
| Saturation Voltage | $V^+ \geq 4.5\text{V}$, $V^- = 0$ $V_{IN} \leq -10\text{ mV}$, $I_{SINK} \leq 3.2\text{ mA}$ | | 0.3 | 0.4 | | 0.3 | 0.4 | V |
| Differential Input Voltage | | | | ±5 | | | ±5 | V |
| Positive Supply Current | $T_A = 25^\circ\text{C}$, $V^+ = 5\text{V}$, $V^- = 0$ | | 4.3 | | | 4.3 | | mA |
| Positive Supply Current | $T_A = 25^\circ\text{C}$, $V_S = \pm 15\text{V}$ | | 8 | 12.5 | | 8 | 12.5 | mA |
| Negative Supply Current | $T_A = 25^\circ\text{C}$, $V_S = \pm 15\text{V}$ | | 3 | 5 | | 3 | 5 | mA |

Note 9: For supply voltages less than ±15 the absolute maximum input voltage is equal to the supply voltage.

Note 10: The maximum junction temperature of the LM319A and LM319 is 85°C. For operating at elevated temperatures, devices in the H10 package must be derated based on a thermal resistance of 160°C/W, junction to ambient, or 19°C/W, junction to case. The thermal resistance of the N14 and J14 package is 100°C/W, junction to ambient. The thermal resistance of the M14 package is 115°C/W, junction to ambient.

Note 11: These specifications apply for $V_S = \pm 15\text{V}$, and $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$, unless otherwise stated. The offset voltage, offset current and bias current specifications apply for any supply voltage from a single 5V supply up to ±15V supplies. Do not operate the device with more than 16V from ground to V_S .


Note 12: The offset voltages and offset currents given are the maximum values required to drive the output within a volt of either supply with a 1 mA load. Thus, these parameters define an error band and take into account the worst case effects of voltage gain and input impedance.

Note 13: The response time specified is for a 100 mV input step with 5 mV overdrive.

Note 14: Output is pulled up to 15V through a 1.4 kΩ resistor.


Typical Performance Characteristics LM119A/LM119/LM219

Input Currents




DS005705-10

Common Mode Limits




DS005705-11

Transfer Function




DS005705-12

Response Time for Various Input Overdrives




DS005705-13

Response Time for Various Input Overdrives




DS005705-14

Input Characteristics




DS005705-15

Response Time for Various Input Overdrives




DS005705-16

Response Time for Various Input Overdrives



DS005705-17


Output Saturation Voltage




DS005705-18

Typical Performance Characteristics LM119A/LM119/LM219 (Continued)


Supply Current



Supply Current




Output Limiting Characteristics




Typical Performance Characteristics LM319A, LM319


Input Currents




Supply Currents




Transfer Function




Response Time for Various Input Overdrives



Response Time for Various Input Overdrives




Input Characteristics




Typical Performance Characteristics LM319A, LM319 (Continued)

Response Time for Various Input Overdrives




DS005705-28

Response Time for Various Input Overdrives




DS005705-29

Output Saturation Voltage




DS005705-30

Supply Current




DS005705-31

Common Mode Limits




DS005705-32

Output Limiting Characteristics




DS005705-33


Schematic Diagram



Typical Applications (Note 15)



Note 15: Pin numbers are for metal can package.




$$V_{OUT} = 5V \text{ for}$$

$$V_{LT} \leq V_{IN} \leq V_{UT}$$

$$V_{OUT} = 0 \text{ for}$$


$$V_{IN} \leq V_{LT} \text{ or } V_{IN} \geq V_{UT}$$

Connection Diagrams




Case is connected to pin 5 (V⁻)

Top View
Order Number LM119H, LM119H/883 (Note 1),
or LM319H
See NS Package Number H10C





Order Number LM119W/883
See NS Package Number W10A

Physical Dimensions inches (millimeters) unless otherwise noted






Metal Can Package (H)
Order Number LM119H, LM119H/883, LM319AH or LM319H
NS Package Number H10C







Cavity Dual-In-Line Package (J)
Order Number LM119J, LM119J/883, LM219J, LM319AJ or LM319J
NS Package Number J14A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



M14A (REV. H)


Dual-In-Line Package (M)
Order Number LM319AM or LM319M
NS Package Number M14A



N14A (REV. F)

Molded Dual-In-Line Package (N)
Order Number LM319AN or LM319N
NS Package Number N14A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



Order Number LM119W/883, LM119WG/883
NS Package Number W10A, WG10A

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

National Semiconductor Corporation
 Americas
 Tel: 1-800-272-9959
 Fax: 1-800-737-7018
 Email: support@nsc.com

www.national.com

National Semiconductor Europe
 Fax: +49 (0) 1 80-530 85 86
 Email: europe.support@nsc.com
 Deutsch Tel: +49 (0) 1 80-530 85 85
 English Tel: +49 (0) 1 80-532 78 32
 Français Tel: +49 (0) 1 80-532 93 58
 Italiano Tel: +49 (0) 1 80-534 16 80

National Semiconductor Asia Pacific Customer Response Group
 Tel: 65-2544466
 Fax: 65-2504466
 Email: sea.support@nsc.com

National Semiconductor Japan Ltd.
 Tel: 81-3-5639-7560
 Fax: 81-3-5639-7507