



**ELECTRONICS, INC.**  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089

## NTE16000-ECG thru NTE16022-ECG Polymeric Positive Temperature Coefficient (PTC) Resettable Fuses

### ELECTRICAL CHARACTERISTICS

| NTE Type No. | Diag. No. | V max. Volts | I max. Amps | I <sub>Hold</sub> | I <sub>Trip</sub> | Initial resistance |       | 1 Hour (R <sub>1</sub> ) Post-Trip Resistance | Max. Time To Trip at 5*I <sub>h</sub> | Tripped Power Dissipation |
|--------------|-----------|--------------|-------------|-------------------|-------------------|--------------------|-------|---|---------------------------------------|---------------------------|
|              |           |              |             | Amperes at 23°C   |                   | Ohms at 23°C       |       | Ohms at 23°C                                  | Seconds at 23°C                       | Watts at 23°C             |
|              |           |              |             | Hold              | Trip              | Min.               | Max.  | Max.  |                                       |                           |
| 16000-ECG    | 629       | 60           | 40          | 0.10              | 0.20              | 2.50               | 4.50  | 7.50  | 4.0                                   | 0.38                      |
| 16001-ECG    | 629       | 60           | 40          | 0.17              | 0.34              | 2.00               | 3.20  | 8.00  | 3.0                                   | 0.48                      |
| 16002-ECG    | 629       | 60           | 40          | 0.20              | 0.40              | 1.50               | 2.84  | 4.40  | 2.2                                   | 0.40                      |
| 16003-ECG    | 629       | 60           | 40          | 0.25              | 0.50              | 1.00               | 1.95  | 3.00  | 2.5                                   | 0.45                      |
| 16004-ECG    | 629       | 60           | 40          | 0.30              | 0.60              | 0.76               | 1.36  | 2.10  | 3.0                                   | 0.50                      |
| 16005-ECG    | 629       | 60           | 40          | 0.40              | 0.80              | 0.52               | 0.86  | 1.29  | 3.8                                   | 0.55                      |
| 16006-ECG    | 629       | 60           | 40          | 0.50              | 1.00              | 0.41               | 0.77  | 1.17  | 4.0                                   | 0.75                      |
| 16007-ECG    | 629       | 60           | 40          | 0.65              | 1.30              | 0.27               | 0.48  | 0.72  | 5.3                                   | 0.90                      |
| 16008-ECG    | 629       | 60           | 40          | 0.75              | 1.50              | 0.18               | 0.40  | 0.60  | 6.3                                   | 0.90                      |
| 16009-ECG    | 629       | 60           | 40          | 0.90              | 1.80              | 0.14               | 0.31  | 0.47  | 7.2                                   | 1.00                      |
| 16010-ECG    | 630       | 30           | 40          | 0.90              | 1.80              | 0.07               | 0.12  | 0.22  | 5.9                                   | 0.60                      |
| 16011-ECG    | 629       | 30           | 40          | 1.10              | 2.20              | 0.10               | 0.18  | 0.27  | 6.6                                   | 0.70                      |
| 16012-ECG    | 629       | 30           | 40          | 1.35              | 2.70              | 0.065              | 0.115 | 0.17  | 7.3                                   | 0.80                      |
| 16013-ECG    | 629       | 30           | 40          | 1.60              | 3.20              | 0.055              | 0.105 | 0.15  | 8.0                                   | 0.90                      |
| 16014-ECG    | 629       | 30           | 40          | 1.85              | 3.70              | 0.04               | 0.07  | 0.11  | 8.7                                   | 1.00                      |
| 16015-ECG    | 630       | 30           | 40          | 2.50              | 5.00              | 0.025              | 0.048 | 0.07  | 10.3                                  | 1.20                      |
| 16016-ECG    | 630       | 30           | 40          | 3.00              | 6.00              | 0.02               | 0.05  | 0.08  | 10.8                                  | 2.00                      |
| 16017-ECG    | 630       | 30           | 40          | 4.00              | 8.00              | 0.01               | 0.03  | 0.05  | 12.7                                  | 2.50                      |
| 16018-ECG    | 630       | 30           | 40          | 5.00              | 10.00             | 0.01               | 0.03  | 0.05  | 14.5                                  | 3.00                      |
| 16019-ECG    | 630       | 30           | 40          | 6.00              | 12.00             | 0.005              | 0.02  | 0.04  | 16.0                                  | 3.50                      |
| 16020-ECG    | 630       | 30           | 40          | 7.00              | 14.00             | 0.005              | 0.02  | 0.03  | 17.5                                  | 3.80                      |
| 16021-ECG    | 630       | 30           | 40          | 8.00              | 16.00             | 0.005              | 0.02  | 0.03  | 18.8                                  | 4.00                      |
| 16022-ECG    | 630       | 30           | 40          | 9.00              | 18.00             | 0.005              | 0.01  | 0.02  | *20.0                                 | 4.20                      |

\* Tested at 40 Amps.


### TECHNICAL DATA

|   |  |                                |
|---|--|--------------------------------|
| Operating/Storage Temperature                       | -40°C to +85°C   |                                |
| Maximum Device Surface Temperature in Tripped State | +125°C   |                                |
| Passive Aging                                       | +85°C, 1000 Hours                                      | ±5% Typical Resistance Change  |
| Humidity Aging                                      | +85°C, 85% R.H. 1000 Hours                             | ±5% Typical Resistance Change  |
| Thermal Shock                                       | +125°C/-40°C 10 Times                                  | ±10% Typical Resistance Change |
| Mechanical Shock                                    | MIL-STD-202, Method 213, Condition 1 (100g, 6 Seconds) | No Resistance Change           |
| Solvent Resistance                                  | MIL-STD-202, Method 215                                | No Change                      |
| Vibration   | MIL-STD-883C, Method 2007.1, Condition A               | No Change                      |

## TEST PROCEDURES AND REQUIREMENTS

| Test               | Test Condition                           | Accept/Reject Criteria                      |
|--------------------|--|---|
| Visual/Mechanical  | Verify Dimensions and Materials          | Per PF Physical Description                 |
| Resistance         | In Still Air @ +23°C                     | $R_{min} \leq R \leq R_{max}$               |
| Time to Trip       | 5 Times $I_{Hold}$ , $V_{max}$ , +23°C   | $T \leq \text{Max. Time to Trip (Seconds)}$ |
| Hold Current       | 30 Min. at $I_{Hold}$                    | No trip                                     |
| Trip Cycle Life    | $V_{max}$ , $I_{max}$ , 100 Cycles       | No Arcing or Burning                        |
| Trip Endurance     | $V_{max}$ , 48 Hours                     | No Arcing or Burning                        |
| Solvent Resistance | MIL-STD-202, Method 215                  | No Change                                   |
| Vibration          | MIL-STD-883C, Method 2007.1, Condition A | No Change                                   |

## TYPICAL TIME TO TRIP AT +23°




## THERMAL DERATING CHART – $I_{HOLD}$ (Amps) \*

| NTE Type No. | Ambient Operating Temperature |       |       |       |       |       |       |       |       |
|--------------|-------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|
|              | -40°C                         | -20°C | 0°C   | +23°C | +40°C | +50°C | +60°C | +70°C | +85°C |
| NTE16000-ECG | 0.16                          | 0.14  | 0.12  | 0.10  | 0.08  | 0.07  | 0.06  | 0.05  | 0.04  |
| NTE16001-ECG | 0.26                          | 0.23  | 0.20  | 0.17  | 0.14  | 0.12  | 0.11  | 0.09  | 0.07  |
| NTE16002-ECG | 0.31                          | 0.27  | 0.24  | 0.20  | 0.16  | 0.14  | 0.13  | 0.11  | 0.08  |
| NTE16003-ECG | 0.39                          | 0.34  | 0.30  | 0.25  | 0.20  | 0.18  | 0.16  | 0.14  | 0.10  |
| NTE16004-ECG | 0.47                          | 0.41  | 0.36  | 0.30  | 0.24  | 0.22  | 0.19  | 0.16  | 0.12  |
| NTE16005-ECG | 0.62                          | 0.54  | 0.48  | 0.40  | 0.32  | 0.29  | 0.25  | 0.22  | 0.16  |
| NTE16006-ECG | 0.78                          | 0.68  | 0.60  | 0.50  | 0.41  | 0.36  | 0.32  | 0.27  | 0.20  |
| NTE16007-ECG | 1.01                          | 0.88  | 0.77  | 0.65  | 0.53  | 0.47  | 0.41  | 0.35  | 0.26  |
| NTE16008-ECG | 1.16                          | 1.02  | 0.89  | 0.75  | 0.61  | 0.54  | 0.47  | 0.41  | 0.30  |
| NTE16009-ECG | 1.40                          | 1.22  | 1.07  | 0.90  | 0.73  | 0.65  | 0.57  | 0.49  | 0.36  |
| NTE16010-ECG | 1.40                          | 1.22  | 1.07  | 0.90  | 0.73  | 0.65  | 0.57  | 0.49  | 0.36  |
| NTE16011-ECG | 1.60                          | 1.43  | 1.27  | 1.10  | 0.91  | 0.85  | 0.75  | 0.67  | 0.57  |
| NTE16012-ECG | 1.96                          | 1.76  | 1.55  | 1.35  | 1.12  | 1.04  | 0.92  | 0.82  | 0.70  |
| NTE16013-ECG | 2.32                          | 2.08  | 1.84  | 1.60  | 1.33  | 1.23  | 1.09  | 0.98  | 0.83  |
| NTE16014-ECG | 2.68                          | 2.41  | 2.13  | 1.85  | 1.54  | 1.42  | 1.26  | 1.13  | 0.96  |
| NTE16015-ECG | 3.63                          | 3.25  | 2.88  | 2.50  | 2.08  | 1.93  | 1.70  | 1.53  | 1.30  |
| NTE16016-ECG | 4.35                          | 3.90  | 3.45  | 3.00  | 2.49  | 2.31  | 2.04  | 1.83  | 1.56  |
| NTE16017-ECG | 5.80                          | 5.20  | 4.60  | 4.00  | 3.32  | 3.08  | 2.72  | 2.44  | 2.08  |
| NTE16018-ECG | 7.25                          | 6.50  | 5.75  | 5.00  | 4.15  | 3.85  | 3.40  | 3.05  | 2.60  |
| NTE16019-ECG | 8.70                          | 7.80  | 6.90  | 6.00  | 4.98  | 4.62  | 4.08  | 3.66  | 3.12  |
| NTE16020-ECG | 10.15                         | 9.10  | 8.05  | 7.00  | 5.81  | 5.39  | 4.76  | 4.27  | 3.64  |
| NTE16021-ECG | 11.60                         | 10.40 | 9.20  | 8.00  | 6.64  | 6.16  | 5.44  | 4.88  | 4.16  |
| NTE16022-ECG | 13.05                         | 11.70 | 10.35 | 9.00  | 7.47  | 6.99  | 6.12  | 5.49  | 4.68  |

\*  $I_{Trip} = 2 \cdot I_{Hold}$

**DIMENSIONAL OUTLINE DRAWINGS**



NOTE: Shape changes from round to square starting with NTE16016-ECG.

**PRODUCT DIMENSIONS** (Dimensions are in inches(mm))


| NTE Type No. | A           |              | B           |            | C          |            | D          |            | E         |             | Physical Characteristic |  |  |
|--------------|-------------|--------------|-------------|------------|------------|------------|------------|------------|-----------|-------------|-------------------------|--|--|
|              | Max.        | Max.         | Nom.        | Tol. ±     | Min.       | Max.       | Min.       | Max.       | Diag. No. | Lead Dia.   | Material                |  |  |
| NTE16000-ECG | .290 (7.4)  | .500 (12.7)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .122 (3.1) | .300 (7.6) | .122 (3.1) | 629       | .020 (0.51) | Sn/NiCu                 |  |  |
| NTE16001-ECG | .290 (7.4)  | .500 (12.7)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .122 (3.1) | .300 (7.6) | .122 (3.1) | 629       | .020 (0.51) | Sn/CuFe                 |  |  |
| NTE16002-ECG | .290 (7.4)  | .500 (12.7)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .122 (3.1) | .300 (7.6) | .122 (3.1) | 629       | .020 (0.51) | Sn/CuFe                 |  |  |
| NTE16003-ECG | .290 (7.4)  | .500 (12.7)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .122 (3.1) | .300 (7.6) | .122 (3.1) | 629       | .020 (0.51) | Sn/CuFe                 |  |  |
| NTE16004-ECG | .290 (7.4)  | .530 (13.4)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .122 (3.1) | .300 (7.6) | .122 (3.1) | 629       | .020 (0.51) | Sn/CuFe                 |  |  |
| NTE16005-ECG | .290 (7.4)  | .540 (13.7)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .122 (3.1) | .300 (7.6) | .122 (3.1) | 629       | .020 (0.51) | Sn/CuFe                 |  |  |
| NTE16006-ECG | .310 (7.9)  | .540 (13.7)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .122 (3.1) | .300 (7.6) | .122 (3.1) | 629       | .020 (0.51) | Sn/Cu                   |  |  |
| NTE16007-ECG | .380 (9.7)  | .600 (15.2)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .122 (3.1) | .300 (7.6) | .122 (3.1) | 629       | .020 (0.51) | Sn/Cu                   |  |  |
| NTE16008-ECG | .410 (10.4) | .630 (16.0)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .122 (3.1) | .300 (7.6) | .122 (3.1) | 629       | .020 (0.51) | Sn/Cu                   |  |  |
| NTE16009-ECG | .460 (11.7) | .660 (16.7)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .122 (3.1) | .300 (7.6) | .122 (3.1) | 629       | .020 (0.51) | Sn/Cu                   |  |  |
| NTE16010-ECG | .290 (7.4)  | .480 (12.2)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 630       | .020 (0.51) | Sn/Cu                   |  |  |
| NTE16011-ECG | .350 (8.9)  | .550 (14.0)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 629       | .020 (0.51) | Sn/Cu                   |  |  |
| NTE16012-ECG | .350 (8.9)  | .750 (18.9)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 629       | .020 (0.51) | Sn/Cu                   |  |  |
| NTE16013-ECG | .400 (10.2) | .660 (16.8)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 629       | .020 (0.51) | Sn/Cu                   |  |  |
| NTE16014-ECG | .470 (12.0) | .720 (18.4)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 629       | .020 (0.51) | Sn/Cu                   |  |  |
| NTE16015-ECG | .470 (12.0) | .720 (18.3)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 630       | .030 (0.81) | Sn/Cu                   |  |  |
| NTE16016-ECG | .470 (12.0) | .720 (18.3)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 630       | .030 (0.81) | Sn/Cu                   |  |  |
| NTE16017-ECG | .570 (14.4) | .970 (24.8)  | .200 (5.1)  | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 630       | .030 (0.81) | Sn/Cu                   |  |  |
| NTE16018-ECG | .690 (17.4) | .980 (24.9)  | .400 (10.2) | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 630       | .030 (0.81) | Sn/Cu                   |  |  |
| NTE16019-ECG | .760 (19.3) | 1.260 (31.9) | .400 (10.2) | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 630       | .030 (0.81) | Sn/Cu                   |  |  |
| NTE16020-ECG | .870 (22.1) | 1.170 (29.8) | .400 (10.2) | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 630       | .030 (0.81) | Sn/Cu                   |  |  |
| NTE16021-ECG | .960 (24.2) | 1.300 (32.9) | .400 (10.2) | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 630       | .030 (0.81) | Sn/Cu                   |  |  |
| NTE16022-ECG | .960 (24.2) | 1.300 (32.9) | .400 (10.2) | .027 (0.7) | .300 (7.6) | .120 (3.0) | .300 (7.6) | .120 (3.0) | 630       | .030 (0.81) | Sn/Cu                   |  |  |

## RESETTABLE CIRCUIT PROTECTION

When it comes to Polymeric Positive Temperature Coefficient (PPTC) circuit protection, you now have a choice.

Polymeric fuses are made from a conductive plastic formed into thin sheets, with electrodes attached to either side. The conductive plastic is manufactured from a non-conductive crystalline polymer and a highly conductive carbon black. The electrodes ensure even distribution of power through the device, and provide a surface for leads to be attached or for custom mounting.

The phenomenon that allows conductive plastic materials to be used for resettable overcurrent protection devices is that they exhibit a very large non-linear Positive Temperature Coefficient (PTC) effect when heated. PTC is a characteristic that many materials exhibit whereby resistance increases with temperature. What makes the polymeric conductive plastic material unique is the magnitude of its resistance increase. At a specific transition temperature, the increase in resistance is so great that it is typically expressed on a log scale.



## HOW POLYMERIC RESETTABLE OVERCURRENT PROTECTORS WORK

The conductive carbon black filler material in the polymeric device is dispersed in a polymer that has a crystalline structure. The crystalline structure densely packs the carbon particles into its crystalline boundary so they are close enough together to allow current to flow through the polymer insulator via these carbon "chains".

When the conductive plastic material is at normal room temperature, there are numerous carbon chains forming conductive paths through the material.

Under fault conditions, excessive current flows through the polymeric device.  $I^2R$  heating causes the conductive plastic material's temperature to rise. As this self heating continues, the material's temperature continues to rise until it exceeds its phase transformation temperature. As the material passes through this phase transformation temperature, the densely packed crystalline polymer matrix changes to an amorphous structure. This phase change is accompanied by a small expansion. As the conductive particles move apart from each other, most of them no longer conduct current and the resistance of the device increases sharply.

The material will stay "hot", remaining in this high resistance state as long as the power is applied. The device will remain latched, providing continuous protection, until the fault is cleared and the power is removed. Reversing the phase transformation allows the carbon chains to re-form as the polymer re-crystallizes. The resistance quickly returns to its original value.

## PRODUCT SELECTION

To select the correct polymeric circuit protection device, complete the information listed below for application, and then refer to the resettable overcurrent protector data sheets.

1. Determine the normal operating current:  
\_\_\_\_\_ amps
2. Determine the maximum circuit voltage ( $V_{max}$ ):  
\_\_\_\_\_ volts
3. Determine the fault current ( $I_{max}$ ):  
\_\_\_\_\_ amps
4. Determine the operating temperature range:  
Minimum Temperature: \_\_\_\_\_ °C  
Maximum Temperature: \_\_\_\_\_ °C
5. Select a product family so that the maximum rating for  $V_{max}$  and  $I_{max}$  is higher than the maximum circuit voltage and fault current in the application.
6. Using the  $I_{Hold}$  vs. Temperature Table on the product family data sheet, select the polymeric device at the maximum operating temperature with an  $I_{Hold}$  greater than or equal to the normal operating current.
7. Verify that the selected device will trip under fault conditions by checking in the  $I_{Trip}$  table that the fault current is greater than  $I_{Trip}$  for the selected device, at the lowest operating temperature.
8. Order samples and test in application.

## APPLICATIONS

The benefits of polymeric Resettable Overcurrent Protectors are being recognized by more and more design engineers, and new applications are being discovered every day.

The use of polymeric types of devices have been widely accepted in the following applications and industries:

- Personal computers
- Laptop computers
- Personal digital assistants
- Transformers
- Small and medium electric motors
- Audio equipment and speakers
- Test and measurement equipment
- Security and fire alarm systems
- Personal care products
- Point-of-sale equipment
- Industrial controls
- Automotive electronics and harness protection
- Marine electronics
- Battery-operated toys