


Advanced Information
SMARTDISCRETES™
Internally Clamped, N-Channel IGBT


This Logic Level Insulated Gate Bipolar Transistor (IGBT) features Gate–Emitter ESD protection, Gate–Collector overvoltage protection from SMARTDISCRETES™ monolithic circuitry for usage as an **Ignition Coil Driver**.

- Temperature Compensated Gate–Collector Clamp Limits Stress Applied to Load
- Integrated ESD Diode Protection
- Low Threshold Voltage to Interface Power Loads to Logic or Microprocessors
- Low Saturation Voltage
- High Pulsed Current Capability



MGP20N40CL

**20 AMPERES
VOLTAGE CLAMPED
N-CHANNEL IGBT
V_{CE(on)} = 1.8 VOLTS
400 VOLTS (CLAMPED)**



**CASE 221A-09
STYLE 9
TO-220AB**

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Collector–Emitter Voltage	V _{CES}	CLAMPED	V _{dc}
Collector–Gate Voltage	V _{CGR}	CLAMPED	V _{dc}
Gate–Emitter Voltage	V _{GE}	CLAMPED	V _{dc}
Collector Current — Continuous @ T _C = 25°C	I _C	20	A _{dc}
Reversed Collector Current – pulse width < 100 μs	I _{CR}	12	A _{pk}
Total Power Dissipation @ T _C = 25°C (TO-220)	P _D	150	Watts
Electrostatic Voltage — Gate–Emitter	ESD	3.5	kV
Operating and Storage Temperature Range	T _J , T _{stg}	–55 to 175	°C

THERMAL CHARACTERISTICS

Thermal Resistance — Junction to Case – (TO-220) — Junction to Ambient	R _{θJC} R _{θJA}	1.0 62.5	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 5 seconds	T _L	260	°C
Mounting Torque, 6–32 or M3 screw	10 lbf•in (1.13 N•m)		

UNCLAMPED INDUCTIVE SWITCHING CHARACTERISTICS

Single Pulse Collector–Emitter Avalanche Energy @ Starting T _J = 25°C @ Starting T _J = 150°C	E _{AS}	550 150	mJ
--	-----------------	------------	----

SMARTDISCRETES is a trademark of Motorola, Inc.

This document contains information on a new product. Specifications and information herein are subject to change without notice.

MGP20N40CL

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector-to-Emitter Breakdown Voltage (I _{Clamp} = 10 mA, T _J = -40 to 150°C)	V _{(BR)CES}	370	405	430	V _{dc}
Zero Gate Voltage Collector Current (V _{CE} = 350 V, V _{GE} = 0 V, T _J = 150°C) (V _{CE} = 15 V, V _{GE} = 0 V, T _J = 150°C)	I _{CES}	— —	— —	500 100	μA
Resistance Gate-Emitter (T _J = -40 to 150°C)	R _{GE}	10k	16k	30k	Ω
Gate-Emitter Breakdown Voltage (I _G = 2 mA)	V _{(BR)GES}	11	13	15	± V
Collector-Emitter Reverse Leakage (V _{CE} = -15 V, T _J = 150°C)	I _{ECS}	—	—	50	mA
Collector-Emitter Reversed Breakdown Voltage (I _E = 75 mA)	V _{(BR)ECS}	26	40	120	V

ON CHARACTERISTICS (1)

Gate Threshold Voltage (V _{CE} = V _{GE} , I _C = 1 mA) (V _{CE} = V _{GE} , I _C = 1 mA, T _J = 150°C)	V _{GE(th)}	1.0 0.75	1.7 —	2.2 1.8	V
Collector-Emitter On-Voltage (V _{GE} = 5 V, I _C = 5 A) (V _{GE} = 5 V, I _C = 10 A) (V _{GE} = 5 V, I _C = 10 A _{dc} , T _J = 150°C)	V _{CE(on)}	— — —	1.1 1.4 1.4	1.4 1.9 1.8	V
Forward Transconductance (V _{CE} > 5.0 V, I _C = 10 A)	g _{fe}	10	18	—	S

DYNAMIC CHARACTERISTICS

Input Capacitance	(V _{CE} = 25 V _{dc} , V _{GE} = 0 V _{dc} , f = 1.0 MHz)	C _{ies}	—	2800	—	pF
Output Capacitance		C _{oes}	—	200	—	
Transfer Capacitance		C _{res}	—	25	—	

SWITCHING CHARACTERISTICS (1)

Total Gate Charge	(V _{CC} = 280 V, I _C = 20 A, V _{GE} = 5 V)	Q _g	—	45	80	nC
Gate-Emitter Charge		Q _{ge}	—	8.0	—	
Gate-Collector Charge		Q _{gc}	—	20	—	
Turn-Off Delay Time	(V _{CC} = 320 V, I _C = 20 A, L = 200 μH, R _G = 1 KΩ)	t _{d(off)}	—	14	—	μs
Fall Time		t _f	—	4.0	—	
Turn-On Delay Time	(V _{CC} = 14 V, I _C = 20 A, L = 200 μH, R _G = 1 KΩ)	t _{d(on)}	—	2.0	—	μs
Rise Time		t _r	—	6.0	—	

(1) Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 1. Output Characteristics




Figure 2. Output Characteristics




Figure 3. Transfer Characteristics




Figure 4. Collector-to-Emitter Saturation Voltage versus Junction Temperature




Figure 5. Capacitance Variation

MGP20N40CL




Figure 6. Gate-to-Emitter Voltage versus Total Charge




Figure 7. Latch Current versus Temperature





Figure 8. Thermal Response

PACKAGE DIMENSIONS



Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

Mfax is a trademark of Motorola, Inc.

How to reach us:

USA/EUROPE/Locations Not Listed: Motorola Literature Distribution;
 P.O. Box 5405, Denver, Colorado 80217. 1-303-675-2140 or 1-800-441-2447

JAPAN: Nippon Motorola Ltd.: SPD, Strategic Planning Office, 141,
 4-32-1 Nishi-Gotanda, Shagawa-ku, Tokyo, Japan. 03-5487-8488

Customer Focus Center: 1-800-521-6274

Mfax™: RMFAX0@email.sps.mot.com – TOUCHTONE 1-602-244-6609
 Motorola Fax Back System – US & Canada ONLY 1-800-774-1848
 – http://sps.motorola.com/mfax/

ASIA/PACIFIC: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,
 51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298

HOME PAGE: <http://motorola.com/sps/>

