



MOTOROLA

Order this document μA78S40/D

μA78S40

Universal Switching Regulator Subsystem


The μA78S40 is a switching regulator subsystem, consisting of a temperature compensated voltage reference, controlled-duty cycle oscillator with an active current limit circuit, comparator, high-current and high-voltage output switch, capable of 1.5 A and 40 V, pinned-out power diode and an uncommitted operational amplifier, which can be powered up or down independent of the IC supply. The switching output can drive external NPN or PNP transistors when voltages greater than the 40 V, or currents in excess of 1.5 A, are required. Some of the features are wide-supply voltage range, low standby current, high efficiency and low drift. The μA78S40 is available in commercial (0° to $+70^{\circ}\text{C}$), and automotive (-40° to $+85^{\circ}\text{C}$) temperature ranges.

Some of the applications include use in step-up, step-down, and inverting regulators, with extremely good results obtained in battery-operated systems.

- Output Adjustable from 1.25 V to 40 V
- Peak Output Current of 1.5 A Without External Transistor
- 80 dB Line and Load Regulation
- Operation from 2.5 V to 40 V Supply
- Low Standby Current Drain
- High Gain, High Output Current, Uncommitted Op Amp

UNIVERSAL SWITCHING REGULATOR SUBSYSTEM

SEMICONDUCTOR TECHNICAL DATA




P SUFFIX
PLASTIC PACKAGE
CASE 648

PIN CONNECTIONS

Diode Cathode	1	Switch Collector
Diode Anode	2	Driver Collector
Switch Emitter	3	I _{pk} Sense
Op Amp Output	4	V _{CC}
V _{CC} Op Amp	5	Timing Capacitor
Op Amp {	6	Ground
Noninv. Inv. Input	7	Comparator Inv. Input
Reference	8	Comparator Noninv. Input

(Top View)

Simplified Block Diagram



ORDERING INFORMATION

Device	Temperature Range	Package
μA78S40PC	T _A = 0° to +70°C	Plastic
μA78S40PV	T _A = -40° to +85°C	Plastic

μA78S40

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Power Supply Voltage	V _{CC}	40	V
Op Amp Power Supply Voltage	V _{CC} (Op Amp)	40	V
Common Mode Input Range (Comparator and Op Amp)	V _{ICR}	-0.3 to V _{CC}	V
Differential Input Voltage (Note 2)	V _{ID}	± 30	V
Output Short Circuit Duration (Op Amp)		Continuous	—
Reference Output Current	I _{ref}	10	mA
Voltage from Switch Collectors to Gnd		40	V
Voltage from Switch Emitters to Gnd		40	V
Voltage from Switch Collectors to Emitter		40	V
Voltage from Power Diode to Gnd		40	V
Reverse-Power Diode Voltage	V _{DR}	40	V
Current through Power Switch	I _{SW}	1.5	A
Current through Power Diode	I _D	1.5	A
Power Dissipation and Thermal Characteristics: Plastic Package (T _A = + 25°C) Derate above + 25°C (Note 1)	P _D 1/R _{θJA}	1500 14	mW mW/°C
Storage Temperature Range	T _{stg}	-65 to + 150	°C
Operating Temperature Range μA78S40V μA78S40C	T _A	-40 to +85 0 to +70	°C

NOTES: 1. T_{low} = -40° for μA78S40PV
 = 0° for μA78S40PC
 T_{high} = +85° for μA78S40PV
 = +70° for μA78S40PC

2. For supply voltages less than 30 V the maximum differential input voltage (Error Amp and Op Amp) is equal to the supply voltage.

ELECTRICAL CHARACTERISTICS (V_{CC} = V_{CC} (Op Amp) 5.0 V, T_A = T_{low} to T_{high}, unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
GENERAL					
Supply Voltage	V _{CC}	2.5	—	40	V
Supply Current (Op Amp V _{CC} , disconnected) (V _{CC} = 5.0 V) (V _{CC} = 40 V)	I _{CC}	— —	1.8 2.3	3.5 5.0	mA
Supply Current (Op Amp V _{CC} , connected) (V _{CC} = 5.0 V) (V _{CC} = 40 V)	I _{CC}	— —	— —	4.0 5.5	mA
REFERENCE					
Reference Voltage (I _{ref} = 1.0 mA)	V _{ref}	1.180	1.245	1.310	V
Reference Voltage Line Regulation (3.0 V ≤ V _{CC} ≤ 40 V, I _{ref} = 1.0 mA, T _A = 25°C)	Regline	—	0.04	0.2	mV/V
Reference Voltage Load Regulation (1.0 mA ≤ I _{ref} ≤ 10 mA, T _A = 25°C)	Regload	—	0.2	0.5	mV/mA

μA78S40

ELECTRICAL CHARACTERISTICS ($V_{CC} = V_{CC}$ (Op Amp) 5.0 V, $T_A = T_{low}$ to T_{high} , unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
OSCILLATOR					
Charging Current ($T_A = 25^\circ C$) ($V_{CC} = 5.0$ V) ($V_{CC} = 40$ V)	I_{chg}	20 20	— —	50 70	μA
Discharging Current ($T_A = 25^\circ C$) ($V_{CC} = 5.0$ V) ($V_{CC} = 40$ V)	I_{dis}	150 150	— —	250 350	μA
Oscillator Voltage Swing ($T_A = 25^\circ C$) ($V_{CC} = 5.0$ V)	V_{osc}	—	0.5	—	V
Ratio of Charge/Discharge Time	t_{chg}/t_{dis}	—	6.0	—	—
CURRENT LIMIT					
Current-Limit Sense Voltage ($T_A = 25^\circ C$) ($V_{CC} - V_{Ipk\ Sense}$)	V_{CLS}	250	—	350	mV
OUTPUT SWITCH					
Output Saturation Voltage 1 ($I_{SW} = 1.0$ A, Pin 15 tied to Pin 16)	V_{sat1}	—	0.93	1.3	V
Output Saturation Voltage 2 ($I_{SW} = 1.0$ A, $I_{15} = 50$ mA)	V_{sat2}	—	0.5	0.7	V
Output Transistor Current Gain ($T_A = 25^\circ C$) ($I_C = 1.0$ A, $V_{CE} = 5.0$ V)	h_{FE}	—	70	—	—
Output Leakage Current ($T_A = 25^\circ C$) ($V_{CE} = 40$ V)	$I_{C(off)}$	—	10	—	nA
POWER DIODE					
Forward Voltage Drop ($I_D = 1.0$ A)	V_D	—	1.25	1.5	V
Diode Leakage Current ($T_A = 25^\circ C$) ($V_{DR} = 40$ V)	I_{DR}	—	10	—	nA
COMPARATOR					
Input Offset Voltage ($V_{CM} = V_{ref}$)	V_{IO}	—	1.5	15	mV
Input Bias Current ($V_{CM} = V_{ref}$)	I_{IB}	—	35	200	nA
Input Offset Current ($V_{CM} = V_{ref}$)	I_{IO}	—	5.0	75	nA
Common Mode Voltage Range ($T_A = 25^\circ C$)	V_{ICR}	0	—	$V_{CC} - 2.0$	V
Power-Supply Rejection Ratio ($T_A = 25^\circ C$) ($3.0 \leq V_{CC} \leq 40$ V)	PSRR	70	96	—	dB
OUTPUT OPERATION AMPLIFIER					
Input Offset Voltage ($V_{CM} = 2.5$ V)	V_{IO}	—	4.0	15	mV
Input Bias Current ($V_{CM} = 2.5$ V)	I_{IB}	—	30	200	nA
Input Offset Current ($V_{CM} = 2.5$ V)	I_{IO}	—	5.0	75	nA
Voltage Gain + ($T_A = 25^\circ C$) ($R_L = 2.0$ kΩ to Gnd, 1.0 V ≤ $V_O \leq 2.5$ V)	A_{VOL+}	25	250	—	V/mV
Voltage Gain – ($T_A = 25^\circ C$) ($R_L = 2.0$ kΩ to V_{CC} (Op Amp), 1.0 V ≤ $V_O \leq 2.5$ V)	A_{VOL-}	25	250	—	V/mV
Common Mode Voltage Range ($T_A = 25^\circ C$)	V_{ICR}	0	—	$V_{CC} - 2.0$	V
Common Mode Rejection Ratio ($T_A = 25^\circ C$) ($V_{CM} = 0$ V to 3.0 V)	CMRR	76	100	—	dB
Power-Supply Rejection Ratio ($T_A = 25^\circ C$) (3.0 V ≤ V_{CC} (Op Amp) ≤ 40 V)	PSRR	76	100	—	dB
Output Source Current ($T_A = 25^\circ C$)	I_{Source}	75	150	—	mA
Output Sink Current ($T_A = 25^\circ C$)	I_{Sink}	10	35	—	mA
Slew Rate ($T_A = 25^\circ C$)	SR	—	0.6	—	V/μs
Output Low Voltage ($T_A = 25^\circ C$, $I_L = -5.0$ mA)	V_{OL}	—	—	1.0	V
Output High Voltage ($T_A = 25^\circ C$, $I_L = 50$ mA)	V_{OH}	V_{CC} (Op Amp) -3.0	—	—	V

μ A78S40

Figure 1. Output Switch On/Off Time versus Oscillator Timing Capacitor




Figure 2. Standby Supply Current versus Supply Voltage




Figure 3. Emitter-Follower Configuration Output Switch Saturation Voltage versus Emitter Current





Figure 4. Common-Emitter Configuration Output Switch Saturation Voltage versus Collector Current



μ A78S40

Figure 5. Step-Down Converter






Figure 6. Step-Up Converter



μA78S40

Figure 7. Inverting Converter



Design Formula Table

Calculation	Step-Down	Step-Up	Inverting
$\frac{t_{on}}{t_{off}}$	$\frac{V_{out} + V_F}{V_{in(min)} - V_{sat} - V_{out}}$	$\frac{V_{out} - V_F}{V_{in(min)}} \frac{V_{in(min)}}{V_{sat}}$	$\frac{V_{out} + V_F}{V_{in(min)} - V_{sat}}$
$(t_{on} + t_{off}) \text{ max}$	$\frac{I}{f_{min}}$	$\frac{I}{f_{min}}$	$\frac{I}{f_{min}}$
C_T	$4 \times 10^5 t_{on}$	$4 \times 10^5 t_{on}$	$4 \times 10^5 t_{on}$
$I_{pk(\text{switch})}$	$2 I_{out(\text{max})}$	$2 I_{out(\text{max})} \left(\frac{t_{on} - t_{off}}{t_{off}} \right)$	$2 I_{out(\text{max})} \left(\frac{t_{on} + t_{off}}{t_{off}} \right)$
R_{SC}	$\frac{0.33}{I_{pk(\text{switch})}}$	$\frac{0.33}{I_{pk(\text{switch})}}$	$\frac{0.33}{I_{pk(\text{switch})}}$
$L_{(\text{min})}$	$\left(\frac{V_{in(\text{min})} - V_{sat} - V_{out}}{I_{pk(\text{switch})}} \right) t_{on(\text{max})}$	$\left(\frac{V_{in(\text{min})} - V_{sat}}{I_{pk(\text{switch})}} \right) t_{on(\text{max})}$	$\left(\frac{V_{in(\text{min})} - V_{sat}}{I_{pk(\text{switch})}} \right) t_{on(\text{max})}$
C_O	$\frac{I_{pk(\text{switch})} (t_{on} + t_{off})}{8 V_{\text{ripple(pp)}}}$	$\approx \frac{I_{out} t_{on}}{V_{\text{ripple}}}$	$\approx \frac{I_{out} t_{on}}{V_{\text{ripple}}}$

V_{sat} = Saturation voltage of the output switch. V_F = Forward voltage drop of the ringback rectifier.

The following power supply characteristics must be chosen:

V_{in} – Nominal input voltage. If this voltage is not constant, then use $V_{in(max)}$ for step-down and $V_{in(min)}$ for step-up and inverting converter.

V_{out} – Desired output voltage: $V_{\text{out}} = 1.25 \left(1 + \frac{R_2}{R_1}\right)$ for step-down and step-up; $V_{\text{out}} = \frac{1.25 R_2}{R_1}$ for inverting.


I_{out} – Desired output current.

f_{min} – Minimum desired output switching frequency at the selected values for V_{in} and I_O.

V_{ripple(pp)} – Desired peak-to-peak output ripple voltage. In practice, the calculated value will need to be increased due to the capacitor's equivalent series resistance and board layout. The ripple voltage should be kept to a low value since it will directly effect the line and load regulation.

See Application Note AN920 for further information

μA78S40
OUTLINE DIMENSIONS



Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

How to reach us:

USA/EUROPE/Locations Not Listed: Motorola Literature Distribution;
P.O. Box 20912; Phoenix, Arizona 85036. 1-800-441-2447 or 602-303-5454

MFAX: RMFAX0@email.sps.mot.com – TOUCHTONE 602-244-6609
INTERNET: <http://Design-NET.com>

JAPAN: Nippon Motorola Ltd.; Tatsumi-SPD-JLDC, 6F Seibu-Butsuryu-Center,
3-14-2 Tatsumi Koto-Ku, Tokyo 135, Japan. 03-81-3521-8315

ASIA/PACIFIC: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,
51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298

