

# 2SB1502

## Silicon PNP epitaxial planar type Darlington

For power amplification


Complementary to 2SD2275

### Features


- Optimum for 55W HiFi output
- High forward current transfer ratio  $h_{FE}$ : 5000 to 30000
- Low collector to emitter saturation voltage  $V_{CE(sat)}$ : < 2.5V

### Absolute Maximum Ratings ( $T_C=25^\circ\text{C}$ )

Parameter	Symbol	Rated	Unit
Collector to base voltage	$V_{CBO}$	-120	V
Collector to emitter voltage	$V_{CEO}$	-100	V
Emitter to base voltage	$V_{EBO}$	-5	V
Peak collector current	$I_{CP}$	-8	A
Collector current	$I_C$	-5	A
Collector power dissipation	$P_C$	$T_C=25^\circ\text{C}$	60
		$T_a=25^\circ\text{C}$	3.5
Junction temperature	$T_j$	150	$^\circ\text{C}$
Storage temperature	$T_{stg}$	-55 to +150	$^\circ\text{C}$



### Internal Connection




### Electrical Characteristics ( $T_C=25^\circ\text{C}$ )

Parameter	Symbol	Conditions	min	typ	max	Unit
Collector cutoff current	$I_{CBO}$	$V_{CB} = -120\text{V}, I_E = 0$			-100	$\mu\text{A}$
	$I_{CEO}$	$V_{CE} = -100\text{V}, I_B = 0$			-100	$\mu\text{A}$
Emitter cutoff current	$I_{EBO}$	$V_{EB} = -5\text{V}, I_C = 0$			-100	$\mu\text{A}$
Collector to emitter voltage	$V_{CEO}$	$I_C = -30\text{mA}, I_B = 0$	-100			V
Forward current transfer ratio	$h_{FE1}$	$V_{CE} = -5\text{V}, I_C = -1\text{A}$	2000			
	$h_{FE2}^*$	$V_{CE} = -5\text{V}, I_C = -4\text{A}$	5000		30000	
Collector to emitter saturation voltage	$V_{CE(sat)}$	$I_C = -4\text{A}, I_B = -4\text{mA}$			-2.5	V
Base to emitter saturation voltage	$V_{BE(sat)}$	$I_C = -4\text{A}, I_B = -4\text{mA}$			-3.0	V
Transition frequency	$f_T$	$V_{CE} = -10\text{V}, I_C = -0.5\text{A}, f = 1\text{MHz}$		20		MHz
Turn-on time	$t_{on}$	$I_C = -4\text{A}, I_{B1} = -4\text{mA}, I_{B2} = 4\text{mA}, V_{CC} = -50\text{V}$		1.0		$\mu\text{s}$
Storage time	$t_{stg}$			0.8		$\mu\text{s}$
Fall time	$t_f$			1.0		$\mu\text{s}$


\* $h_{FE2}$  Rank classification

Rank	Q	S	P
$h_{FE2}$	5000 to 15000	7000 to 21000	8000 to 30000


$P_C - T_a$




$I_C - V_{CE}$




$V_{CE(sat)} - I_C$




$V_{BE(sat)} - I_C$




$h_{FE} - I_C$




$C_{ob} - V_{CB}$



$t_{on}, t_{stg}, t_f - I_C$



Area of safe operation (ASO)



$$R_{th(t)} \text{ --- } t$$

