

MA360J

Silicon epitaxial planer type

For UHF and VHF electronic tuners


■ Features

- Large capacity variation ratio
- Small series resistance r_D

■ Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Rating	Unit
Reverse voltage (DC)	V_R	30	V
Peak reverse voltage	V_{RM}^*	35	V
Forward current (DC)	I_F	20	mA
Junction temperature	T_j	150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +150	$^\circ\text{C}$

* $R_L=10\text{k}\Omega$



Marking Symbol : 6A


■ Electrical Characteristics ($T_a = 25^\circ\text{C}$)




Parameter	Symbol	Condition	min	typ	max	Unit
Reverse current (DC)	I_R	$V_R=28\text{V}$			10	nA
Diode capacitance	$C_{D(2V)}$	$V_R=2\text{V}, f=1\text{MHz}$	14.360		16.340	pF
	$C_{D(25V)}$	$V_R=25\text{V}, f=1\text{MHz}$	2.089		2.448	pF
	$C_{D(10V)}$	$V_R=10\text{V}, f=1\text{MHz}$	5.433		6.369	pF
	$C_{D(17V)}$	$V_R=17\text{V}, f=1\text{MHz}$	2.945		3.452	pF
Capacitance ratio	$C_{D(2V)}/C_{D(25V)}$		5.95		7.26	—
Diode capacitance deviation	ΔC	$C_D(2\text{V})(10\text{V})(17\text{V})(25\text{V})$			2	%
Series resistance	r_D^{*1}	$C_D=9\text{pF}, f=470\text{MHz}$			0.6	Ω

Note 1. Rated input/output frequency : 470MHz

2. *1 : r_D measurement device : YHP MODEL 4191A RF IMPEDANCE ANALYZER

■ Marking



$I_F - V_F$  $C_D - V_R$  $I_R - T_a$  $C_D - T_a$ 