

## 2SK3047

## Silicon N-Channel Power F-MOS FET

## ■ Features

- Avalanche energy capacity guaranteed:  $EAS > 15\text{mJ}$
- $V_{GSS} = \pm 30\text{V}$  guaranteed
- High-speed switching:  $t_f = 25\text{ns}$
- No secondary breakdown

## ■ Applications

- Contactless relay
- Diving circuit for a solenoid
- Driving circuit for a motor
- Control equipment
- Switching power supply


■ Absolute Maximum Ratings ( $T_C = 25^\circ\text{C}$ )

Parameter	Symbol	Ratings	Unit
Drain to Source breakdown voltage	$V_{DSS}$	800	V
Gate to Source voltage	$V_{GSS}$	$\pm 30$	V
Drain current	DC	$I_D$	$\pm 2$ A
	Pulse	$I_{DP}$	$\pm 4$ A
Avalanche energy capacity	$EAS^*$	15	mJ
Allowable power dissipation	$T_C = 25^\circ\text{C}$	$P_D$	30
	$T_a = 25^\circ\text{C}$		2
Channel temperature	$T_{ch}$	150	$^\circ\text{C}$
Storage temperature	$T_{stg}$	$-55$ to $+150$	$^\circ\text{C}$


\*  $L = 5\text{mH}$ ,  $I_L = 2.45\text{A}$ ,  $V_{DD} = 50\text{V}$ , 1 pulse

■ Electrical Characteristics ( $T_C = 25^\circ\text{C}$ )


Parameter	Symbol	Conditions	min	typ	max	Unit
Drain to Source cut-off current	$I_{DSS}$	$V_{DS} = 640\text{V}$ , $V_{GS} = 0$			0.1	mA
Gate to Source leakage current	$I_{GSS}$	$V_{GS} = \pm 30\text{V}$ , $V_{DS} = 0$			$\pm 1$	$\mu\text{A}$
Drain to Source breakdown voltage	$V_{DSS}$	$I_D = 1\text{mA}$ , $V_{GS} = 0$	800			V
Gate threshold voltage	$V_{th}$	$V_{DS} = 25\text{V}$ , $I_D = 1\text{mA}$	2		5	V
Drain to Source ON-resistance	$R_{DS(on)}$	$V_{GS} = 10\text{V}$ , $I_D = 1\text{A}$		4.8	7	$\Omega$
Forward transfer admittance	$ Y_{fs} $	$V_{DS} = 25\text{V}$ , $I_D = 1\text{A}$	0.7	1.1		S
Diode forward voltage	$V_{DSF}$	$I_{DR} = 2\text{A}$ , $V_{GS} = 0$			-1.3	V
Input capacitance (Common Source)	$C_{iss}$	$V_{DS} = 20\text{V}$ , $V_{GS} = 0$ , $f = 1\text{MHz}$		350		pF
Output capacitance (Common Source)	$C_{oss}$				60	pF
Reverse transfer capacitance (Common Source)	$C_{rss}$				25	pF
Turn-on time (delay time)	$t_{d(on)}$	$V_{GS} = 10\text{V}$ , $I_D = 1\text{A}$		15		ns
Rise time	$t_r$				20	ns
Turn-off time (delay time)	$t_{d(off)}$		$V_{DD} = 200\text{V}$ , $R_L = 200\Omega$		60	
Fall time	$t_f$				25	ns




Area of safe operation (ASO)




$P_D - T_a$




EAS —  $T_j$




$I_D - V_{DS}$




$I_D - V_{GS}$




$V_{th} - T_C$




$R_{DS(on)} - I_D$




$|Y_{fs}| - I_D$




$C_{iss}, C_{oss}, C_{rss} - V_{DS}$



$V_{DS}, V_{GS} - Q_g$



$t_{d(on)}, t_r, t_f, t_{d(off)} - I_D$



$R_{th(t)} - t$

