

Round Type

φ 3.0 mm Series

Conventional Part No.	Global Part No.	Lighting Color
LN277RPX	LNG277RKR	Red
LN377GPX	LNG377GKG	Green
LN477YPX	LNG477YKX	Amber
LN877RPX	LNG877RKD	Orange

Absolute Maximum Ratings (T_a = 25°C)

Lighting Color	P _D (mW)	I _F (mA)	I _{FP} (mA)*	V _R (V)	T _{opr} (°C)	T _{stg} (°C)
Red	70	25	150	4	-25 ~ +85	-30 ~ +100
Green	90	30	150	4	-25 ~ +85	-30 ~ +100
Amber	90	30	150	4	-25 ~ +85	-30 ~ +100
Orange	90	30	150	3	-25 ~ +85	-30 ~ +100

I_{FP}の条件は duty 10% ,Pulse width 1 msec. The condition of I_{FP} is duty 10%, Pulse width 1 msec

Electro-Optical Characteristics (T_a = 25°C)

Conventional Part No.	Lighting Color	Lens Color	I _O			V _F		λ _P	Δλ	I _F	I _R	
			Typ	Min	I _F	Typ	Max	Typ	Typ		Max	V _R
LN277RPX	Red	Red Diffused	1.5	0.5	15	2.2	2.8	700	100	20	5	4
LN377GPX	Green	Green Diffused	5.0	2.0	20	2.2	2.8	565	30	20	10	4
LN477YPX	Amber	Amber Diffused	10.0	3.5	20	2.2	2.8	590	30	20	10	4
LN877RPX	Orange	Red Diffused	5.0	2.0	20	2.1	2.8	630	40	20	10	3
Unit	—	—	mcd	mcd	mA	V	V	nm	nm	mA	μA	V

