

PE9704

Product Description

Peregrine's PE9704 is a high-performance integer-N PLL capable of frequency synthesis up to 3.0 GHz. The device is designed for superior phase noise performance while providing an order of magnitude reduction in current consumption, when compared with existing commercial space PLLs.

The PE9704 features a $\pm 10/11$ dual modulus prescaler, counters, a phase comparator, and a charge pump, as shown in Figure 1. Counter values are programmable through a serial interface, and can also be directly hard wired.

The PE9704 is optimized for commercial space applications. Single Event Latch-up (SEL) is physically impossible and Single Event Upset (SEU) is better than 10^{-9} errors per bit / day. Fabricated in Peregrine's patented UTSi® (Ultra Thin Silicon) CMOS technology, the PE9704 offers excellent RF performance and intrinsic radiation tolerance.

3.0 GHz Integer-N PLL for Rad Hard Applications

Features

- 3.0 GHz operation
- $\pm 10/11$ dual modulus prescaler
- Selectable for either charge pump or phase detector outputs
- Serial interface or hardwired programmable
- Ultra-low phase noise
- SEU < 10^{-9} errors / bit-day
- 100 Krad (Si) total dose
- 44-lead CQFJ

Figure 1. Block Diagram





Figure 2. Pin Configuration

Table 1. Pin Descriptions

Pin No.	Pin Name	Interface Mode	Type	Description
1	V _{DD}	Both	(Note 1)	Power supply input. Input may range from 2.85 V to 3.15 V. Bypassing recommended.
2	R ₀	Direct	Input	R Counter bit0
3	R ₁	Direct	Input	R Counter bit1
4	R ₂	Direct	Input	R Counter bit2
5	R ₃	Direct	Input	R Counter bit3
6	GND	Both	(Note 1)	Ground
7	R ₄	Direct	Input	R Counter bit4
8	R ₅	Direct	Input	R Counter bit5 (MSB)
9	M ₀	Direct	Input	M Counter bit0
10	M ₁	Direct	Input	M Counter bit1
11	V _{DD}	Both	(Note 1)	Same as pin 1
12	V _{DD}	Both	(Note 1)	Same as pin 1
13	M ₂	Direct	Input	M Counter bit2
14	M ₃	Direct	Input	M Counter bit3
15	F_WR	Serial	Input	Frequency register load enable input. Buffered data is transferred to the frequency register on F_WR rising edge.
	M ₄	Direct	Input	M Counter bit4
16	DATA	Serial	Input	Binary serial data input. Data is entered LSB first, and is clocked serially into the 20-bit frequency control register (E_WR "low") or the 8-bit enhancement register (E_WR "high") on the rising edge of CLOCK.
	M ₅	Direct	Input	M Counter bit5

Pin No.	Pin Name	Interface Mode	Type	Description
17	GND	Both		Ground
18	CLOCK	Serial	Input	Clock input. Data is clocked serially into either the 20-bit primary register (E_WR "low") or the 8-bit enhancement register (E_WR "high") on the rising edge of CLOCK.
	M ₆	Direct	Input	M Counter bit6
19	M ₇	Direct	Input	M Counter bit7
20	M ₈	Direct	Input	M Counter bit8 (MSB)
21	A ₀	Direct	Input	A Counter bit0
22	D _{MODE}	Both	Input	Selects direct interface mode (D _{MODE} =1) or serial interface mode (D _{MODE} =0)
23	V _{DD}	Both	(Note 1)	Same as pin 1
24	A ₁	Direct	Input	A Counter bit1
25	A ₂	Direct	Input	A Counter bit2
26	A ₃	Direct	Input	A Counter bit3 (MSB)
27	F _{IN}	Both	Input	RF prescaler input from the VCO. 3.0 GHz maximum frequency.
28	GND	Both		Ground.
29	GND	Both		Ground.
30	CP _{SEL}	Both	Output	Charge pump select input. Selects whether the charge pump output is enabled (CP _{SEL} =1), or the PD _U / PD _D outputs are enabled (CP _{SEL} =0).
31	V _{DD}	Both	(Note 1)	Same as pin 1
32	D _{OUT}	Serial	Output	Data Out. The Main Counter output, R Counter output, or dual modulus prescaler select (MSEL) can be routed to D _{OUT} through enhancement register programming.
33	V _{DD}	Both	(Note 1)	Same as pin 1
34	CP	Both	Output	Charge Pump output. Charge pump current is sourced for "up" when f _c leads f _p and sinked for "down" when f _c lags f _p . Active only when CP _{SEL} =1.
35	V _{DD}	Both	(Note 1)	Same as pin 1
36	PD _D	Both	Output	PD _D pulses down when f _p leads f _c . Active only when CP _{SEL} =0
37	PD _U	Both		PD _U pulses down when f _c leads f _p . Active only when CP _{SEL} =0
38	V _{DD}	Both	(Note 1)	Same as pin 1
39	C _{EXT}	Both	Output	Logical "NAND" of PD _U and PD _D , passed through an on-chip, 2 kΩ series resistor. Connecting C _{EXT} to an external capacitor will low pass filter the input to the inverting amplifier used for driving LD.
40	GND	Both		Ground
41	GND	Both		Ground
42	F _R	Both	Input	Reference frequency input
43	ENH	Both	Output, OD	Enhancement mode. When asserted low ("0"), enhancement register bits are functional.
44	LD	Serial	Input	Lock detect output, the open-drain logical inversion of C _{EXT} . When the loop is locked, LD is high impedance; otherwise LD is a logic low ("0").

Note 1: V_{DD} pins 1, 11, 12, 23, 31, 33, 35, and 38 are connected by diodes and must be supplied with the same positive voltage level.

Note 2: All digital input pins have 70 kΩ pull-down resistors to ground.

Table 2. Absolute Maximum Ratings

Symbol	Parameter/Conditions	Min	Max	Units
V_{DD}	Supply voltage	-0.3	4.0	V
V_i	Voltage on any input	-0.3	$V_{DD} + 0.3$	V
I_i	DC into any input	-10	+10	mA
I_o	DC into any output	-10	+10	mA
T_{stg}	Storage temperature range	-65	150	°C

Table 3. Operating Ratings

Symbol	Parameter/Conditions	Min	Max	Units
V_{DD}	Supply voltage	2.85	3.15	V
T_A	Operating ambient temperature range	-40	85	°C

Table 4. ESD Ratings

Symbol	Parameter/Conditions	Level	Units
V_{ESD}	ESD voltage (Human Body Model) – Note 1	1000	V

Note 1: Periodically sampled, not 100% tested. Tested per MIL-STD-883, M3015 C2

Electrostatic Discharge (ESD) Precautions

When handling this UTSi device, observe the same precautions that you would use with other ESD-sensitive devices. Although this device contains circuitry to protect it from damage due to ESD, precautions should be taken to avoid exceeding the rating specified in Table 4.

Latch-Up Avoidance

Unlike conventional CMOS devices, UTSi CMOS devices are immune to latch-up.

Table 5. DC Characteristics

$V_{DD} = 3.0\text{ V}$, $-40^\circ\text{ C} < T_A < 85^\circ\text{ C}$, unless otherwise specified

Symbol	Parameter	Conditions	Min	Typ	Max	Units
I_{DD}	Operational supply current; Prescaler disabled Prescaler enabled	$V_{DD} = 2.85\text{ to }3.15\text{ V}$		10 24	31	mA mA
Digital Inputs: All except F_R , F_{IN} (all digital inputs have 70k ohm pull-up resistors)						
V_{IH}	High level input voltage	$V_{DD} = 2.85\text{ to }3.15\text{ V}$	$0.7 \times V_{DD}$			V
V_{IL}	Low level input voltage	$V_{DD} = 2.85\text{ to }3.15\text{ V}$			$0.3 \times V_{DD}$	V
I_{IH}	High level input current	$V_{IH} = V_{DD} = 3.15\text{ V}$			+70	μA
I_{IL}	Low level input current	$V_{IL} = 0, V_{DD} = 3.15\text{ V}$	-1			μA
Reference Divider input: F_R						
I_{IHR}	High level input current	$V_{IH} = V_{DD} = 3.15\text{ V}$			+100	μA
I_{ILR}	Low level input current	$V_{IL} = 0, V_{DD} = 3.15\text{ V}$	-100			μA
Counter and phase detector outputs: f_c, f_p .						
V_{OLD}	Output voltage LOW	$I_{out} = 6\text{ mA}$			0.4	V
V_{OHD}	Output voltage HIGH	$I_{out} = -3\text{ mA}$	$V_{DD} - 0.4$			V
Lock detect outputs: C_{EXT}, LD						
V_{OLC}	Output voltage LOW, C_{EXT}	$I_{out} = 100\text{ mA}$			0.4	V
V_{OHC}	Output voltage HIGH, C_{EXT}	$I_{out} = -100\text{ mA}$	$V_{DD} - 0.4$			V
V_{OLLD}	Output voltage LOW, LD	$I_{out} = 6\text{ mA}$			0.4	V

Table 6. AC Characteristics
 $V_{DD} = 3.0\text{ V}$, $-40^\circ\text{ C} < T_A < 85^\circ\text{ C}$, unless otherwise specified

Symbol	Parameter	Conditions	Min	Max	Units
Control Interface and Latches (see Figures 1 and 3)					
f_{Clk}	CLOCK Serial data clock frequency	(Note 1)		10	MHz
t_{ClkH}	CLOCK Serial clock HIGH time		30		ns
t_{ClkL}	CLOCK Serial clock LOW time		30		ns
t_{DSU}	DATA set-up time after CLOCK rising edge		10		ns
t_{DHLd}	DATA hold time after CLOCK rising edge		10		ns
t_{PW}	F_WR, E_WR pulse width		30		ns
t_{CWR}	CLOCK rising edge to F_WR rising edge.		30		ns
t_{CE}	CLOCK falling edge to E_WR transition		30		ns
t_{WRC}	F_WR falling edge to CLOCK rising edge.		30		ns
t_{EC}	E_WR transition to CLOCK rising edge		30		ns
t_{MDO}	MSEL data out delay after F_{IN} rising edge	$C_L = 12\text{ pf}$		8	ns
Main Divider (Including Prescaler)					
F_{IN}	Operating frequency		500	3000	MHz
P_{Fin}	Input level range	External AC coupling	-5	5	dBm
Main Divider (Prescaler Bypassed)					
F_{IN}	Operating frequency		50	300	MHz
P_{Fin}	Input level range	External AC coupling	-5	5	dBm
Reference Divider					
F_{R}	Operating frequency	(Note 3)		100	MHz
P_{Fr}	Reference input power (Note 2)	Single-ended input	-2		dBm
Phase Detector					
f_c	Comparison frequency	(Note 3)		20	MHz
Charge Pump output: CP					
$I_{\text{CP - Source}}$	Drive current	$V_{\text{CP}} = V_{\text{DD}} / 2$	-2.6	-1.4	mA
$I_{\text{CP - Sink}}$	Drive current	$V_{\text{CP}} = V_{\text{DD}} / 2$	1.4	2.6	mA
I_{CPL}	Leakage current	$1.0\text{ V} < V_{\text{CP}} < V_{\text{DD}} - 1.0\text{ V}$	-1		μA
$I_{\text{CP - Source vs. } I_{\text{CP Sink}}}$	Sink vs. source mismatch	$V_{\text{CP}} = V_{\text{DD}} / 2$, $T_A = 25^\circ\text{ C}$		15	%
$I_{\text{CP vs. } V_{\text{CP}}}$	Output current magnitude variation vs. voltage	$1.0\text{ V} < V_{\text{CP}} < V_{\text{DD}} - 1.0\text{ V}$ $T_A = 25^\circ\text{ C}$		15	%

Note 1: f_{Clk} is verified during the functional pattern test. Serial programming sections of the functional pattern are clocked at 10 MHz to verify f_{Clk} specification.

Note 2: CMOS logic levels can be used to drive reference input if DC coupled. Voltage input needs to be a minimum of $0.5V_{\text{p-p}}$.

Note 3: Parameter is guaranteed through characterization only and is not tested.

Functional Description

The PE9704 consists of a prescaler, counters, a phase detector, and control logic. The dual modulus prescaler divides the VCO frequency by either 10 or 11, depending on the value of the modulus select. Counters “R” and “M” divide the reference and prescaler output, respectively, by integer values stored in a 20-bit register. An additional counter (“A”) is used in the modulus select logic. The phase-frequency detector generates up and down frequency control signals. The control logic includes a selectable chip interface. Data can be written via a serial bus or hardwired directly to the pins. There are also various operational and test modes and a lock detect output.

Main Counter Chain

Normal Operating Mode

Setting the PB control bit “low” enables the ÷10/11 prescaler. The main counter chain then divides the RF input frequency (F_{IN}) by an integer derived from the values in the “M” and “A” counters.

In this mode, the output from the main counter chain (f_p) is related to the VCO frequency (F_{IN}) by the following equation:

$$f_p = F_{IN} / [10 \times (M + 1) + A] \quad (1)$$

where $A \leq M + 1$, $1 \leq M \leq 511$

When the loop is locked, F_{IN} is related to the reference frequency (F_R) by the following equation:

$$F_{IN} = [10 \times (M + 1) + A] \times (F_R / (R+1)) \quad (2)$$

where $A \leq M + 1$, $1 \leq M \leq 511$

A consequence of the upper limit on A is that F_{IN} must be greater than or equal to $90 \times (F_R / (R+1))$ to obtain contiguous channels. The A counter can accept values as high as 15, but in typical operation it will cycle from 0 to 9 between increments in M.

Programming the M counter with the minimum allowed value of “1” will result in a minimum M counter divide ratio of “2”.

Prescaler Bypass Mode

Setting the frequency control register bit PB “high” allows F_{IN} to bypass the ÷10/11 prescaler. In this mode, the prescaler and A counter are powered down, and the input VCO frequency is divided by the M counter directly. This mode is only available when using the serial port to set the frequency control bits. The following equation relates F_{IN} to the reference frequency F_R :

$$F_{IN} = (M + 1) \times (F_R / (R+1)) \quad (3)$$

where $1 \leq M \leq 511$

Reference Counter

The reference counter chain divides the reference frequency F_R down to the phase detector comparison frequency f_c .

The output frequency of the 6-bit R Counter is related to the reference frequency by the following equation:

$$f_c = F_R / (R + 1) \quad (4)$$

where $0 \leq R \leq 63$

Note that programming R with “0” will pass the reference frequency (F_R) directly to the phase detector.

Register Programming

Serial Interface Mode

Serial Interface Mode is selected by setting the D_{MODE} input “low”.

While the E_WR input is “low”, serial data (DATA input), B_0 to B_{19} , is clocked into a buffer register on the rising edge of CLOCK, LSB (B_0) first. The contents from this buffer register are transferred into the frequency control register on the rising edge of F_WR according to the timing diagram shown in Figure 3. This data controls the counters as shown in Table 7.

While the E_WR input is “high”, serial data (DATA input), B_0 to B_7 , is clocked into a buffer register on the rising edge of CLOCK, LSB (B_0) first. The

contents from this buffer register are transferred into the enhancement register on the falling edge of E_WR according to the timing diagram shown in Figure 3. After the falling edge of E_WR , the data provides control bits as shown in Table 8. These bits are active when the \overline{Enh} input is “low”.

Direct Interface Mode

Direct Interface Mode is selected by setting the D_{MODE} input “high”. In this mode, the counter values are set directly at external pins as shown in Table 7 and Figure 2. All frequency control register bits are addressable except PB (it is not possible to bypass the $\div 10/11$ dual modulus prescaler in Direct Mode).

Table 7. Frequency Register Programming

Interface Mode	\overline{Enh}	D_{MODE}	R_5	R_4	M_8	M_7	PB	M_6	M_5	M_4	M_3	M_2	M_1	M_0	R_3	R_2	R_1	R_0	A_3	A_2	A_1	A_0
Serial*	1	0	B_0	B_1	B_2	B_3	B_4	B_5	B_6	B_7	B_8	B_9	B_{10}	B_{11}	B_{12}	B_{13}	B_{14}	B_{15}	B_{16}	B_{17}	B_{18}	B_{19}
Direct	1	1	R_5	R_4	M_8	M_7	0	M_6	M_5	M_4	M_3	M_2	M_1	M_0	R_3	R_2	R_1	R_0	A_3	A_2	A_1	A_0

* Data is clocked serially on CLOCK rising edge while E_WR is “low” and transferred to frequency register on F_WR rising edge.

↑
LSB (first in)

↑
MSB (last in)

Table 8. Enhancement Register Programming

Interface Mode	\overline{Enh}	D_{MODE}	Reserved*	Reserved*	fp output	Power down	Counter load	MSEL output	fc output	Reserved*
Serial**	0	X	B_0	B_1	B_2	B_3	B_4	B_5	B_6	B_7


* Program to 0

* Data is clocked serially on CLOCK rising edge while E_WR is “low” and transferred to frequency register on F_WR rising edge.

↑
LSB (first in)

↑
MSB (last in)

Figure 3. Serial Interface Mode Timing Diagram



Enhancement Register

The functions of the enhancement register bits are shown below. All bits are active high. Operation is undefined if more than one output is sent to D_{OUT} .

Table 9. Enhancement Register Bit Functionality

Bit Function	Description	
Bit 0	Reserved**	
Bit 1	Reserved**	
Bit 2	f_p output	Drives the M counter output onto the D_{OUT} output.
Bit 3	Power down	Power down of all functions except programming interface.
Bit 4	Counter load	Immediate and continuous load of counter programming.
Bit 5	MSEL output	Drives the internal dual modulus prescaler modulus select (MSEL) onto the D_{OUT} output.
Bit 6	f_c output	Drives the R counter output onto the D_{OUT} output
Bit 7	Reserved**	

** Program to 0

Phase Detector and Charge Pump

The phase detector is triggered by rising edges from the main counter (f_p) and the reference counter (f_c). It has two outputs, $PD_{\bar{U}}$, and $PD_{\bar{D}}$, which are available when the CP_{SEL} input pin is “low”. If the divided VCO leads the divided reference in phase or frequency (f_p leads f_c), $PD_{\bar{D}}$ pulses “low”. If the divided reference leads the divided VCO in phase or frequency (f_c leads f_p), $PD_{\bar{U}}$ pulses “low”. The width of either pulse is directly proportional to phase offset between the two input signals, f_p and f_c . The phase detector gain is 430 mV / radian.

$PD_{\bar{U}}$ and $PD_{\bar{D}}$ are designed to drive an active loop filter which controls the VCO tune voltage. $PD_{\bar{U}}$ pulses result in an increase in VCO frequency and $PD_{\bar{D}}$ results in a decrease in VCO frequency.

The signals from the phase detector are also routed to an internal charge pump. $PD_{\bar{U}}$ controls a current source at pin CP, and $PD_{\bar{D}}$ controls a current sink at pin CP. When using a positive Kv VCO, $PD_{\bar{U}}$ pulses (current source) will increase

the VCO frequency, and $PD_{\bar{D}}$ pulses (current sink) will decrease VCO frequency.

The current pulses from pin CP are available when the CP_{SEL} input pin is “high”, and are designed to drive a passive loop filter to provide a VCO tune voltage. Software tools for designing both passive and active loop filters can be found at Peregrine’s web site (www.peregrine-semi.com).


Lock Detect Output

A lock detect signal is provided at pin LD, via the pin C_{EXT} (see Figure 1). C_{EXT} is the logical “NAND” of $PD_{\bar{U}}$ and $PD_{\bar{D}}$ waveforms, driven through a series 2k ohm resistor. Connecting C_{EXT} to an external shunt capacitor provides integration of this signal.

The C_{EXT} signal is then sent to the LD pin through an internal inverting comparator with an open drain output. Thus LD is an “AND” function of $PD_{\bar{U}}$ and $PD_{\bar{D}}$.

Figure 4. Package Drawing

44-lead CQFJ



All dimensions are in mils

Table 10. Ordering Information

Order Code	Part Marking	Description	Package	Shipping Method
9704-01	PE9704 ES	Engineering Samples	44-pin CQFJ	40 units / Tray
9704-11	PE9704	Flight Units	44-pin CQFJ	40 units / Tray
9704-00	PE9704 EK	Evaluation Kit		1 / Box

Sales Offices

United States

Peregrine Semiconductor Corp.
6175 Nancy Ridge Drive
San Diego, CA 92121
Tel 1-858-455-0660
Fax 1-858-455-0770

Europe

Peregrine Semiconductor Europe
Aix-En-Provence Office
Parc Club du Golf, bat 9
13856 Aix-En-Provence Cedex 3
France
Tel 33-0-4-4239-3360
Fax 33-0-4-4239-7227

Japan

Peregrine Semiconductor K.K.
The Imperial Tower, 15th floor
1-1-1 Uchisaiwaicho, Chiyoda-ku
Tokyo 100-0011 Japan
Tel: 03-3507-5755
Fax: 03-3507-5601

Australia

Peregrine Semiconductor Australia
8 Herb Elliot Ave.
Homebush, NSW 2140
Australia
Tel: 011-61-2-9763-4111
Fax: 011-61-2-9746-1501

For a list of representatives in your area, please refer to our Web site at: <http://www.peregrine-semi.com>

Data Sheet Identification

Advance Information

The product is in a formative or design stage. The data sheet contains design target specifications for product development. Specifications and features may change in any manner without notice.

Preliminary Specification

The data sheet contains preliminary data. Additional data may be added at a later date. Peregrine reserves the right to change specifications at any time without notice in order to supply the best possible product.

Product Specification

The data sheet contains final data. In the event Peregrine decides to change the specifications, Peregrine will notify customers of the intended changes by issuing a PCN (Product Change Notice).

The information in this data sheet is believed to be reliable. However, Peregrine assumes no liability for the use of this information. Use shall be entirely at the user's own risk.

No patent rights or licenses to any circuits described in this data sheet are implied or granted to any third party.

Peregrine's products are not designed or intended for use in devices or systems intended for surgical implant, or in other applications intended to support or sustain life, or in any application in which the failure of the Peregrine product could create a situation in which personal injury or death might occur. Peregrine assumes no liability for damages, including consequential or incidental damages, arising out of the use of its products in such applications.

Peregrine products are protected under one or more of the following U.S. patents: 6,090,648; 6,057,555; 5,973,382; 5,973,363; 5,930,638; 5,920,233; 5,895,957; 5,883,396; 5,864,162; 5,863,823; 5,861,336; 5,663,570; 5,610,790; 5,600,169; 5,596,205; 5,572,040; 5,492,857; 5,416,043. Other patents may be pending or applied for.

UTSi, the Peregrine logotype, SEL Safe, and Peregrine Semiconductor Corp. are registered trademarks of Peregrine Semiconductor Corp. All PE product names and prefixes are trademarks of Peregrine Semiconductor Corp. Copyright © 2001 Peregrine Semiconductor Corp. All rights reserved.