

## Features

- Single-Supply Operation (+2V to +6V)
- Rail-to-Rail Analog Signal Dynamic Range
- Low On-Resistance (8Ω typ with 5V supply)  
Minimizes Distortion and Error Voltages
- $R_{ON}$  Matching Between Channels, 0.9 Ω typ
- On-Resistance Flatness, 3Ω typ
- Low Charge Injection Reduces Glitch Errors.  $Q = 7\text{pC}$  typ
- High Speed.  $t_{ON} = 8\text{ns}$  typ
- Very Good Off-Isolation: -55dB @ 10 MHz
- Wide -3dB Bandwidth: 230 MHz
- High-Current Channel Capability: >100mA
- TTL/CMOS Logic Compatible
- Low Power Consumption (0.5μW typ)
- Pin-compatible with DG40X, MAX38X

## Applications

- Audio, Video Switching and Routing
- Battery-Powered Communication Systems
- Computer Peripherals
- Telecommunications
- Portable Instrumentation
- Replaces Mechanical Relays

## Description

The PI5A381/383/385A are dual monolithic analog switches designed for single-supply operation. These high-precision devices are ideal for low-distortion audio, video signal switching and routing.


The PI5A381 is a dual single-pole single-throw (SPST), normally open (NO) switch. The PI5A383 is a dual single-pole double-throw (SPDT) switch. The PI5A385 is a dual double-pole single-throw (DPST), normally open (NO) function.

Each switch conducts current equally well in either direction when on. When off they block voltages up to the power-supply rails.

The PI5A381/383/385 are fully specified with +5V, and +3.3V supplies. With +5V, they guarantee <10Ω on-resistance. On-resistance matching between channels is within 2Ω. On-resistance flatness is less than 4Ω over the specified range. The PI5A38X family guarantees fast switching speeds ( $t_{ON} < 15\text{ns}$ ).

These products are available in the 16-pin narrow-body SOIC, QSOP, and PDIP packages for operation over the industrial (-40°C to +85 °C) temperature range.

## Functional Diagram, Pin Configurations and Truth Tables



Switches shown for Logic "0" input  
 NC = Normally Closed, NO = Normally Open, NIC = Not internally Connected

PI5A381A	
Logic	Switch
0	OFF
1	ON

PI5A383A		
Logic	SW1, SW2	SW3, SW4
0	OFF	ON
1	ON	OFF

PI5A385A	
Logic	Switch
0	OFF
1	ON



PI5A381A  
PI5A383A  
PI5A385A

## Absolute Maximum Ratings

Voltages Referenced to GND

$V_{CC}$ .....	-0.5V to +7V	Continuous Power Dissipation
$V_{IN}, V_{COM}, V_{NC}, V_{NO}$ (Note 1) .....	-0.5V to $V_{CC} + 2V$ or 30mA, whichever occurs first	PDIP (derate 10.5mW/ $^{\circ}C$ above 70 $^{\circ}C$ ) ..... 800mW
Current (any terminal except COM, NO, NC) .....	30mA	(derate 8.7mW/ $^{\circ}C$ above +70 $^{\circ}C$ ) ..... 650mW
Current, COM, NO, NC .....	100 mA	Storage Temperature ..... -65 $^{\circ}C$ to +150 $^{\circ}C$
(pulsed at 1ms, 10% duty cycle) .....	120mA	Lead Temperature(soldering, 10s) ..... +300 $^{\circ}C$

## Thermal Information

Narrow SO & QSOP	
(derate 8.7mW/ $^{\circ}C$ above +70 $^{\circ}C$ ) .....	650mW
Storage Temperature .....	-65 $^{\circ}C$ to +150 $^{\circ}C$
Lead Temperature(soldering, 10s) .....	+300 $^{\circ}C$

**Note 1 :** Signals on NC, NO, COM, or IN exceeding  $V_{CC}$  or GND are clamped by internal diodes. Limit forward diode current to 30mA.

**Caution:** Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied.

## Electrical Characteristics-Single 5.0V Supply

( $V_{CC} = 5V \pm 10\%$ , GND = 0V,  $V_{INH} = 2.4V$ ,  $V_{INL} = 0.8V$ )

Parameter	Symbol	Test Conditions	Temp( $^{\circ}C$ )	Min. <sup>(2)</sup>	Typ. <sup>(2)</sup>	Max. <sup>(2)</sup>	Unit
<b>Analog Switch</b>							
Analog Signal Range <sup>(3)</sup>	$V_{ANALOG}$		Full	0		$V_{CC}$	V
ON-Resistance	$R_{ON}$	$V_{CC} = 4.5V, I_{COM} = -30mA$ $V_{NO}$ or $V_{NC} = +2.5V$	25		8	10	$\Omega$
			Full			12	
On-Resistance Match Between Channels <sup>(4)</sup>	$\Delta R_{ON}$	$V_{CC} = 5V, I_{COM} = -30mA$ $V_{NO}$ or $V_{NC} = 1V, 2.5V, 4V$	25		0.9	2	
			Full			4	
On-ResistanceFlatness <sup>(5)</sup>	$R_{FLAT(ON)}$	$V_{CC} = 5V, I_{COM} = -30mA$ $V_{NO}$ or $V_{NC} = 1V, 2.5V, 4V$	25		3	4	
			Full			5	
NO or NC Off LeakageCurrent <sup>(6)</sup>	$I_{NO(OFF)}$ $I_{NC(OFF)}$	$V_{CC} = 5.5V, V_{COM} = 0V$ $V_{NO}$ or $V_{NC} = 4.5V$	25		0.05		
			Full	-80		80	
COM Off Leakage Current <sup>(6)</sup>	$I_{COM(OFF)}$	$V_{+} = 5.5V, V_{COM} = +4.5V$ $V_{NO}$ or $V_{NC} = \pm 0V$	25		0.05		
			Full	-80		80	
COM On Leakage Current <sup>(6)</sup>	$I_{COM(ON)}$	$V_{CC} = 5.5V, V_{COM} = +4.5V$ $V_{NO}$ or $V_{NC} = +4.5V$	25		0.07		
			Full	-80		80	



**PI5A381A  
PI5A383A  
PI5A385A**

### Electrical Characteristics-Single 5.0V Supply (continued)

( $V_{CC} = 5V \pm 10\%$ ,  $GND = 0V$ ,  $V_{INH} = 2.4V$ ,  $V_{INL} = 0.8V$ )

Parameter	Symbol	Conditions	Temp(°C)	Min <sup>(1)</sup>	Typ <sup>(2)</sup>	Max <sup>(1)</sup>	Unit
<b>Logic Input</b>							
Input High Voltage	$V_{INH}$	Guaranteed logic High Level	Full	2			V
Input Low Voltage	$V_{INL}$	Guaranteed logic Low Level				0.8	
Input Current with Input Voltage High	$I_{INH}$	$V_{IN} = 2.4V$ , all others = 0.8V		-1	0.005	1	$\mu A$
Input Current with Input Voltage Low	$I_{INL}$	$V_{IN} = 0.8V$ , all others = 2.4V		-1	0.005	1	
<b>Dynamic</b>							
Turn-On Time	$t_{ON}$	$V_{CC} = 5V$ , Figure 1	25	25		8	15
Turn-Off Time	$t_{OFF}$			Full			20
Charge Injection <sup>(3)</sup>	Q			25		3.5	7
Off Isolation	OIRR			Full			10
Crosstalk <sup>(8)</sup>	$I_{COM(OFF)}$	$R_L = 50\Omega$ , $C_L = 5pF$ , $f = 10MHz$ , Figure 4	25		7	10	pC
NC or NO Capacitance	$C_{(OFF)}$	$f = 1kHz$ , Figure 5			-55		dB
COM Off Capacitance	$C_{COM(OFF)}$				-92		
COM On Capacitance	$C_{COM(ON)}$	$f = 1kHz$ , Figure 6			8		pF
-3dB Bandwidth	BW	$R_L = 50\Omega$ , Figure 7	Full		8		
Distortion <sup>(9)</sup>	D	$R_L = 10k\Omega$			14		MHz
<b>Supply</b>							
Power-Supply Range	$V_{CC}$		Full	2		6	V
Positive Supply Current	$I_{CC}$	$V_{CC} = 5.5V$ , $V_{IN} = 0V$ or $V_{CC}$ , all channels on or off				1	$\mu A$

#### Notes:

1. The algebraic convention, where the most negative value is a minimum and the most positive is a maximum, is used in this data sheet.
2. Typical values are for DESIGN AID ONLY, not guaranteed or subject to production testing.
3. Guaranteed by design.
4.  $\Delta R_{ON} = R_{ON} \text{ max} - R_{ON} \text{ min}$ .
5. Flatness is defined as the difference between the maximum and minimum value of on-resistance measured.
6. Leakage parameters are 100% tested at maximum rated hot temperature and guaranteed by correlation at +25°C.
7. Off Isolation =  $20\log_{10} [V_{COM}/(V_{NO} \text{ or } V_{NC})]$ . See figure 3.
8. Between any two switches. See figure 4.
9.  $D = R_{FLAT(ON)}/R_L$ .



**PI5A381A  
PI5A383A  
PI5A385A**







### Electrical Specifications - Single +3.3V Supply







( $V_{CC} = +3.3V \pm 10\%$ , GND = 0V,  $V_{INH} = 2.4V$ ,  $V_{INL} = 0.8V$ )

Parameter	Symbol	Conditions	Temp (°C)	Min <sup>(1)</sup>	Typ <sup>(2)</sup>	Max <sup>(1)</sup>	Units	
<b>Analog Switch</b>								
Analog Signal Range <sup>(3)</sup>	$V_{ANALOG}$		Full	0		$V_{CC}$	V	
On-Resistance	$R_{ON}$	$V_{CC} = 3V$ , $I_{COM} = -30mA$ , $V_{NO}$ or $V_{NC} = 1.5V$	25		12	18	$\Omega$	
			Full			22		
On-Resistance Match Between Channels <sup>(4)</sup>	$\Delta R_{ON}$	$V_{CC} = 3.3V$ , $I_{COM} = -30mA$ , $V_{NO}$ or $V_{NC} = 0.8V$ , 2.5V	25		1	2		
			Full			4		
On-Resistance Flatness <sup>(3,5)</sup>	$R_{FLAT(ON)}$		25		4	10		
			Full			12		
<b>Dynamic</b>								
Turn-On Time	$t_{ON}$	$V_{CC} = 3.3V$ , $V_{NO}$ or $V_{NC} = 1.5V$ Figure 1	25		14	25	ns	
			Full			40		
Turn-Off Time	$t_{OFF}$		25		5	12		
			Full			20		
Charge Injection <sup>(3)</sup>	Q	$C_L = 1nF$ , $V_{GEN} = 0V$ , $R_{GEN} = 0V$ , Figure 2	25		5	10	pC	
<b>Supply</b>								
Positive Supply Current	$I_{CC}$	$V_{CC} = 3.6V$ , $V_{IN} = 0V$ or $V_{CC}$ , all channels on or off	Full			1	$\mu A$	

#### Notes:

1. The algebraic convention, where the most negative value is a minimum and the most positive is a maximum, is used in this data sheet.
2. Typical values are for DESIGN AID ONLY, not guaranteed or subject to production testing.
3. Guaranteed by design
4.  $\Delta R_{ON} = R_{ON \text{ max}} - R_{ON \text{ min}}$
5. Flatness is defined as the difference between the maximum and minimum value of on-resistance measured.

**Typical Operating Characteristics ( $T_A=+25^\circ\text{C}$ , unless otherwise noted)**




## Test Circuits/Timing Diagrams




Figure 1. Switching Time




Figure 2. Charge Injection

### Test Circuits/Timing Diagrams (continued)




Figure 3. Off Isolation




Figure 4. Crosstalk




Figure 5. Channel-Off Capacitance




Figure 6. Channel-On Capacitance

### Ordering Information

Part Number	Package
PI5A381AP	16-Pin PDIP
PI5A381AW	Narrow Body SOIC-16
PI5A381AQ	16-Pin QSOP
PI5A383AP	16-Pin PDIP
PI5A383AW	Narrow Body SOIC-16
PI5A383AQ	16-Pin QSOP
PI5A385AP	16-Pin PDIP
PI5A385AW	Narrow Body SOIC-16
PI5A385AQ	16-Pin QSOP




Figure 7. Bandwidth