

UNIDIRECTIONAL THYRISTOR SURGE SUPPRESSOR

APPLICATIONS

- ✓ SLIC Line Card
- ✓ DBX Branch Exchange Switches
- ✓ FCC Part 68 Customer Premise Equipment
- ✓ Line Interface Modem
- ✓ ISDN Architecture Interface

IEC COMPATIBILITY (EN61000-4)


- ✓ 61000-4-2 (ESD): Air - 15kV, Contact - 8kV
- ✓ 61000-4-4 (EFT): 40A - 5/50ns
- ✓ 61000-4-5 (Surge): 8/20 μ s - 95A, L4(Line-Gnd), 48A, L4(Line-Line) & 83A, L2(Power)

FEATURES

- ✓ *Complies with: FCC Part 68, UL 1459, Bellcore 1089, ITU-K.20 & K.21*
- ✓ Peak Off-State Voltage: 80 Volts
- ✓ Surge Current Capability(See Table 1)
- ✓ ESD Protection > 40 kilovolts

MECHANICAL CHARACTERISTICS

- ✓ Molded Plastic DO-214AA Package
- ✓ Weight 2.5 grams (Approximate)
- ✓ Flammability Rating UL 94V-0
- ✓ Device Marking: Logo, Marking Code & Polarity Band or Notch on Top Surface



DEVICE SYMBOL
(UNIDIRECTIONAL)




TABLE 1 - SURGE RATINGS

SERIES	I_{PP} 2 X 10 μ s AMPS	I_{PP} 10 X 1000 μ s AMPS	I_{TSM} 60 Hz AMPS	di/dt AMPS/ μ s (See Note 1)	dv/dt AMPS/ μ s (See Note 1)
SA	125	40	20	500	2000
SC	300	100	60	500	2000

Note 1: Critical Rate of Rise for On-State Current (di/dt) and Off-State Voltage (dv/dt).

PP0901SA & PP0901SC

DEVICE CHARACTERISTICS


MAXIMUM RATINGS @ 25°C Unless Otherwise Specified

PARAMETER	SYMBOL	VALUE	UNITS
Surge Current - 50/60 Hz	I_{TSM}	60	Amps
Junction Temperature	T_j	-40 to 150	°C
Storage Temperature	T_{STG}	-55 to 150	°C
Thermal Resistance(Junction) - SA Series	$R_{\theta jc}$	28	°C/Watt
Thermal Resistance(Junction) - SC Series	$R_{\theta jc}$	26	°C/Watt
Thermal Resistance(Ambient) - SA Series	$R_{\theta ja}$	90	°C/Watt
Thermal Resistance(Ambient) - SC Series	$R_{\theta ja}$	85	°C/Watt


ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified

PART NUMBER	DEVICE MARKING CODE	REPETITIVE PEAK OFF-STATE VOLTAGE V_{DRM} VOLTS	SWITCHING VOLTAGE @ 100V/ μ s V_S VOLTS	MINIMUM HOLDING CURRENT (See Fig. 4) I_H mA	SWITCHING CURRENT I_S mA	MAXIMUM OFF-STATE CURRENT (See Fig. 3) @ V_{DRM} I_{DRM} μ A	MAXIMUM ON-STATE VOLTAGE (See Fig. 3) @ I_T V_T VOLTS	ON-STATE CURRENT I_T AMPS	TYPICAL CAPACITANCE @ 50V, 1 MHz C pF
PP0901SA	JA	80	110	150	800	5	5	1.0	65
PP0901SC	JC	80	110	150	800	5	5	1.0	65

**FIGURE 1
PULSE WAVE FORM**



**FIGURE 2
V-I CHARACTERISTIC CURVE**



PP0901SA & PP0901SC

FIGURE 4
TYPICAL PEAK OFF-STATE CURRENT VS JUNCTION TEMPERATURE




FIGURE 5
TYPICAL ON-STATE CURRENT VS ON-STATE VOLTAGE




FIGURE 6
TYPICAL NORMALIZED V_s VS JUNCTION TEMPERATURE




FIGURE 7
TYPICAL HOLDING CURRENT VS JUNCTION TEMPERATURE






FIGURE 7
ON-STATE CURRENT VS SURGE CURRENT DURATION



PP0901SA & PP0901SC

PACKAGE OUTLINE & DIMENSIONS



TAPE & REEL PACKAGING:

Surface mount product is taped and reeled in accordance with EIA-481, reel quantities and sizes are as follows:
7 Inch Reel - 3,000 pieces per reel; 13 Inch Reel - N/A

ProTek Devices
2929 South Fair Lane, Tempe, AZ 85282
Tel: 602-431-8101 Fax: 602-431-2288
E-Mail: sales@protekdevices.com
Web Site: www.protekdevices.com

COPYRIGHT © ProTek Devices 2001

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.