




## EWS SERIES 5 WATT



### FEATURES

- Industry Standard Package
- Industry Standard Pinout
- 85°C Case Operation
- Short Circuit Protection
- 5V and 12V Inputs
- Input Pi Filter and 6-Sided Shielding
- Regulated Outputs
- 500V Isolation


### DESCRIPTION

EWS DC/DC converters offer excellent regulation and isolation in an industry standard package. Available in 5V or 12V input versions, the EWS is ideal for industrial, datacom, or telecom applications. The EWS features short circuit protection, six-sided shielding, and 500 VDC isolation. Please see the EWD series for dual output applications.

### TECHNICAL SPECIFICATIONS

Input	
Voltage Range	4.5 - 9 VDC
5 VDC Nominal	9 - 18 VDC
12 VDC Nominal	20% $I_{in}$ Max.
Reflected Ripple	100% $I_{in}$ Max.
Reverse Input Current	

Output	
Setpoint Accuracy	±5%
Line Regulation $V_{in}$ Min. - $V_{in}$ Max., $I_{out}$ Rated	±1.5% $V_{out}$
Load Regulation $I_{out}$ Min. - $I_{out}$ Max., $V_{in}$ Nom.	±2.5% $V_{out}$
Minimum Output Current	10%
Dynamic Regulation, Loadstep	25% $I_{out}$
Pk Deviation	1% $V_{out}$
Settling Time	500 $\mu$ s
Temperature Coefficient	0.02%/°C
Ripple And Noise, 20 MHz BW	150 mV
Short Circuit Protection <sup>1</sup>	Continuous
Current Limit	130%



General	
Switching Frequency	200 kHz
Isolation	500 VDC
Input - Output	10 <sup>9</sup> Ohms
Isolation Resistance - Input to Output	-25 to +85°C
Standard Case Operating Range	
Storage range	-40 to +125°C
Humidity Max., Non-Condensing	95%
Vibration, 3 Axes, 5 Min Each	5 g, 10 - 55 Hz
Safety	UL, cUL, TUV
Weight (approx.)	1.4 oz.

Notes	
<sup>1</sup> Converter will auto-restart once fault has been removed.	
Specifications typically at 25°C, normal line, and full load, unless otherwise stated.	
Soldering Conditions: I/O pins, 260°C, ten seconds; fully compatible with commercial wave-soldering equipment.	
Safety: Agency approvals may vary from model to model. Please consult factory for specific model information.	



# EWS SERIES 5 WATT


Powering Communications and Technology

MODELS - (See the last page of Section for options.)

Selection Chart							
Model	Vin (Volts)	Vin Range (Volts)	Iin Max.* (Amps)	Vout (Volts)	Iout Rated (Amps)	Ripple & Noise Pk-Pk (mV)	Efficiency Typ.**
EWS0505	5	4.5 - 9.0	1.80	5	1.00	150	70%
EWS0512	5	4.5 - 9.0	2.10	12	0.50	150	73%
EWS1205	12	9.0 - 18.0	0.85	5	1.00	150	73%
EWS1212	12	9.0 - 18.0	0.95	12	0.50	150	80%
EWS1215	12	9.0 - 18.0	0.91	15	0.40	150	82%

\* Maximum input current at minimum input voltage, maximum rated output power.  
 \*\* At nominal Vin, rated output.

## MECHANICAL DRAWING



BOTTOM VIEW

Thermal Impedance	
Natural Convection	15.4 °C/W
100 LFM	12.2 °C/W
200 LFM	9.3 °C/W
300 LFM	7.4 °C/W
400 LFM	6.4 °C/W

Note:  
 Thermal impedance data is dependent on many environmental factors. The exact thermal performance should be validated for specific application.

Pin	Function
1	+Vin
2	-Vin
3	+Vout
4	-Vout

Tolerances	
Inches:	(Millimeters)
.XX ± 0.040	.X ± 1.0
.XXX ± 0.010	.XX ± 0.25
Pin:	
± 0.002	± 0.05
Case:	
+0.04, -0.00	+1.0, -0.0

(Dimensions as listed unless otherwise specified.)

High Density - Board Mounted Power Division



## OPTIONS

### Powering Communications and Technology

When ordering equipment options, use the following suffix information. Select the option(s) that you prefer and add them to the model number. Example ordering options are located below the options table.

OPTIONS	SUFFIX	APPLICABLE SERIES	REMARKS
Negative Logic	N	HAS, HBD, HBS, HES, HLS, LES, QBS, QES, QLS, TES, TQD	TTL "Low" Turns Module ON TTL "High" Turns Module OFF
Lucent Compatible Trim	T	HAS, HBD, HBS, HES, HLS, QBS, QES, QLS	
Terminal Strip	TS	XWS, XWD, XWT	
Trim	1	IAS, LES	
Enable	2	IAD, IAS, LES, SMS	
Trim and Enable	3	IAS, LES	
Current Share	4	SMS	
Headerless	Y	Encapsulated EWS, IWS, OWS	
<b>PIN LENGTH AND HEATSINK OPTIONS</b>			Standard Pin Length is 0.180" (4.6mm)
0.110" (2.8mm) Pin Length	8	All Units (Except SMS)	
0.150" (3.8mm) Pin Length	9	All Units (Except SMS)	
0.24" (6.1mm) Horizontal Heatsink	1H	All Units (Except DIP, HLS, HLD, QLS, SIP, SM TLD, and TKD Packages)	Includes Thermal Pad
0.24" (6.1mm) Vertical Heatsink	1V	All Units (Except DIP, HLS, HLD, QLS, SIP, SM TLD, and TKD Packages)	Includes Thermal Pad
0.45" (11.4mm) Horizontal Heatsink	2H	All Units (Except DIP, HLS, HLD, QLS, SIP, SM TLD, and TKD Packages)	Includes Thermal Pad
0.45" (11.4mm) Vertical Heatsink	2V	All Units (Except DIP, HLS, HLD, QLS, SIP, SM TLD, and TKD Packages)	Includes Thermal Pad
0.95" (24.1mm) Horizontal Heatsink	3H	All Units (Except DIP, HLS, HLD, QLS, SIP, SM TLD, and TKD Packages)	Includes Thermal Pad
0.95" (24.1mm) Vertical Heatsink	3V	All Units (Except DIP, HLS, HLD, QLS, SIP, SM TLD, and TKD Packages)	Includes Thermal Pad

#### Example Options:

HBS050ZG-ANT3V = HBS050ZG-A with negative logic, Lucent compatible trim, and 0.95" vertical heatsink.

LES015YJ-3N = LES015YJ with optional trim and enable, negative logic.

QBS066ZG-AT8 = QBS066ZG-A with Lucent compatible trim and 0.110" pin length.

**NUCLEAR AND MEDICAL APPLICATIONS** - Power-One products are not authorized for use as critical components in life support systems, equipment used in hazardous environments, or nuclear control systems without the express written consent of the President of Power-One, Inc.

**TECHNICAL REVISIONS** - The appearance of products, including safety agency certifications pictured on labels, may change depending on the date manufactured. Specifications are subject to change without notice.