



1.5 AMP NEGATIVE VOLTAGE REGULATOR




Pin 1 – Ground
 Pin 2 – V_{OUT}
 Case – V_{IN}

K Package – TO-3



Pin 1 – Ground
 Pin 2 – V_{OUT}
 Case – V_{IN}


R Package – TO-66



Pin 1 – Ground
 Pin 2 – V_{IN}
 Pin 3 – V_{OUT}
 Case – V_{IN}

G Package – TO-257
IG Package – TO-257*

* isolated Case on IG package



Pin 1 – Ground
 Pin 2 – V_{IN}
 Pin 3 – V_{OUT}

SMD Package – SMD1
 Ceramic Surface Mount

FEATURES


- **OUTPUT VOLTAGES OF -5, -12, -15V**
- **0.01% / V LINE REGULATION**
- **0.3% / A LOAD REGULATION**
- **THERMAL OVERLOAD PROTECTION**
- **SHORT CIRCUIT PROTECTION**
- **OUTPUT TRANSISTOR SOA PROTECTION**
- **1% VOLTAGE TOLERANCE OPTION (-A VERSIONS)**

DESCRIPTION

The IP120A / LM120 / IP7900A / IP7900 series of 3 terminal regulators is available with several fixed output voltage making them useful in a wide range of applications.

The A suffix devices provide 0.01% / V line regulation, 0.3% / A load regulation and $\pm 1\%$ output voltage tolerance at room temperature.

Protection features include Safe Operating Area current limiting and thermal shutdown.



J Package – 8 Pin Cerdip

ABSOLUTE MAXIMUM RATINGS ($T_{case} = 25^{\circ}C$ unless otherwise stated)

V_I	DC Input Voltage (for $V_O = -5, -12, -15V$)	35V
P_D	Power Dissipation	Internally limited
T_j	Operating Junction Temperature Range	-55 to 150°C
T_{stg}	Storage Temperature	-65 to 150°C

Parameter	Test Conditions	IP7905A IP120A-05			IP7905 , IP120-05 LM120-05			Units	
		Min.	Typ.	Max.	Min.	Typ.	Max.		
V _O Output Voltage	I _O = 500mA V _{IN} = -10V	-4.95	-5	-5.05	-4.9	-5	-5.1	V	
	I _O = 5mA to I _{MAX} P _D ≤ P _{MAX} V _{IN} = -7.5V to -20V T _J = -55 to 150°C	-4.85		-5.15	-4.8		-5.2		
V _O Low Supply	I _O = 5mA to I _{MAX} V _{IN} = -7V to -20V P _D ≤ P _{MAX}	-4.75		-5.15	-4.75		-5.25	V	
ΔV _O Line Regulation	I _O = 0.5 I _{MAX} V _{IN} = -7V to -25V V _{IN} = -7.5V to -20V T _J = -55 to 150°C	3		10	3		25	mV	
		3		10	3		50		
	V _{IN} = -8V to -12V I _O ≤ I _{MAX} T _J = -55 to 150°C	1		4	1		25		
ΔV _O Load Regulation	V _{IN} = -10V I _O = 5mA to 1.5A I _O = 250mA to 750mA	10		25	10		75	mV	
		4		15	4		25		
	V _{IN} = -10V I _O = 5mA to I _{MAX} T _J = -55 to 150°C	7		25	7		50		
I _Q Quiescent Current	I _O ≤ 0.5 I _{MAX} V _{IN} = -10V T _J = -55 to 150°C	1		1.9	1		1.9	mA	
		1		2	1		2		
ΔI _Q Quiescent Current Change	I _O = 5mA to I _{MAX} V _{IN} = -10V T _J = -55 to 150°C	0.2		0.4	0.2		0.4	mA	
		0.2		0.5	0.2		0.5		
	I _O ≤ 0.5 I _{MAX} T _J = -55 to 150°C	V _{IN} = -7V to -25V	0.1		0.4	0.1			0.4
		V _{IN} = -8V to -25V	0.1		0.5	0.1			1.0
V _N Output Noise Voltage	f = 10Hz to 100kHz V _{IN} = -10V	40		400	40		400	μV	
ΔV _{IN} / ΔV _O Ripple Rejection	f = 120Hz V _{IN} = -8V to -18V I _O ≤ I _{MAX} I _O ≤ 0.5 I _{MAX} T _J = -55 to 150°C	66		80	54		80	dB	
		66		80	54		80		
Dropout Voltage	I _O = I _{MAX}	1.1		2.3	1.1		2.3	V	
R _O Output Resistance	f = 1 kHz	5			5			mΩ	
I _{sc} Short Circuit Current	V _{IN} = -35V	0.6		1.2	0.6		1.2	A	
I _{pk} Peak Output Current	V _{IN} = -10V	2.4		3.3	2.4		3.3		
Average Temperature Coefficient of V _O	I _O = 5mA	0.2		2	0.2		2	mV / °C	
Input Voltage required to maintain line regulation	I _O ≤ I _{MAX}	-7.3			-7.3			V	

1) All characteristics are measured with a capacitor across the input of 0.22μF and a capacitor across the output of 0.1μF.

All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques (t_p ≤ 10ms, δ ≤ 5%). Output voltage changes due to changes in internal temperature must be taken into account separately.

2) Test Conditions unless otherwise stated: P_{MAX} = 10W for TO-220SM, P_{MAX} = 1W for Cerdip, P_{MAX} = 20W for all other package devices
I_{MAX} = 1.0A, T_J = 25°C

Parameter	Test Conditions	IP7912A IP120A-12			IP7912, IP120-12 LM120-12			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
V _O Output Voltage	I _O = 500mA V _{IN} = -19V	-11.88	-12	-12.12	-11.76	-12	-12.24	V
	V _{IN} = -14.8V to -27V P _D ≤ P _{MAX} I _O = 5mA to I _{MAX} T _J = -55 to 150°C	-11.64		-12.36	-11.52		-12.48	
V _O Low Supply	I _O = 5mA to I _{MAX} P _D ≤ P _{MAX} V _{IN} = -14.5V to -27V	-11.40		-12.36	-11.40		-12.60	V
ΔV _O Line Regulation	I _O = 0.5 I _{MAX}	V _{IN} = -14.5V to -30V	4	18	4	120	mV	
		V _{IN} = -14.8V to -27V T _J = -55 to 150°C	4	18	4	200		
	I _O ≤ I _{MAX} V _{IN} = -16V to -22V T _J = -55 to 150°C	1	4	1	25			
ΔV _O Load Regulation	V _{IN} = -19V	I _O = 5mA to 1.5A	12	32	12	80	mV	
		I _O = 250mA to 750mA	4	19	4	60		
	V _{IN} = -19V	I _O = 5mA to I _{MAX} T _J = -55 to 150°C	8	60	8	120		
I _Q Quiescent Current	I _O ≤ 0.5 I _{MAX} V _{IN} = -19V		0.2	0.4	0.2	0.4	mA	
	T _J = -55 to 150°C		1	2	1	2		
ΔI _Q Quiescent Current Change	I _O = 5mA to I _{MAX} V _{IN} = -19V	T _J = -55 to 150°C	0.2	0.4	0.2	0.4	mA	
		V _{IN} = -14.5V to -30V	0.1	0.4	0.1	0.4		
	I _O ≤ 0.5 I _{MAX}	V _{IN} = -15V to -30V T _J = -55 to 150°C	0.1	0.5	0.1	0.5		
		T _J = -55 to 150°C	0.1	0.5	0.1	1.0		
V _N Output Noise Voltage	f = 10Hz to 100kHz V _{IN} = -19V	75	960	75	960	μV		
ΔV _{IN} / ΔV _O Ripple Rejection	f = 120Hz V _{IN} = -15V to -25V	I _O ≤ I _{MAX}	58	72	56	72	dB	
		I _O ≤ 0.5 I _{MAX} T _J = -55 to 150°C	58	72	56	72		
Dropout Voltage	I _O = I _{MAX}	1.1	2.3	1.1	2.3	V		
R _O Output Resistance	f = 1 kHz	8		8		mΩ		
I _{sc} Short Circuit Current	V _{IN} = -35V	0.6	1.2	0.6	1.2	A		
I _{pk} Peak Output Current	V _{IN} = -19V	2.4	3.3	2.4	3.3			
Average Temperature Coefficient of V _O	I _O = 5mA	0.5	4.8	0.5	4.8	mV/°C		
Input Voltage required to maintain line regulation	I _O ≤ I _{MAX}	-14.5		-14.5		V		

1) All characteristics are measured with a capacitor across the input of 0.22μF and a capacitor across the output of 0.1μF.

All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques (t_p ≤ 10ms, δ ≤ 5%). Output voltage changes due to changes in internal temperature must be taken into account separately.

2) Test Conditions unless otherwise stated: P_{MAX} = 10W for TO-220SM, P_{MAX} = 1W for Cerdip, P_{MAX} = 20W for all other package devices
I_{MAX} = 1.0A, T_J = 25°C


Parameter	Test Conditions	IP7915A IP120A-15			IP7915, IP120-15 LM120-15			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
V _O Output Voltage	I _O = 500mA V _{IN} = -23V	-14.85	-15	-15.15	-14.7	-15	-15.3	V
	V _{IN} = -17.9V to -30V P _D ≤ P _{MAX} I _O = 5mA to I _{MAX} T _J = -55 to 150°C	-14.55		-15.45	-14.4		-15.6	
V _O Low Supply	I _O = 5mA to I _{MAX} P _D ≤ P _{MAX} V _{IN} = -17.5V to -30V	-14.25		-15.45	-14.25		-15.75	V
ΔV _O Line Regulation	I _O = 0.5 I _{MAX}	V _{IN} = -17.5V to -30V	4	22	4	150	mV	
		V _{IN} = -17.9V to -30V T _J = -55 to 150°C	4	22	4	250		
	I _O ≤ I _{MAX} V _{IN} = -20V to -26V T _J = -55 to 150°C	2	10	2	75			
ΔV _O Load Regulation	V _{IN} = -23V	I _O = 5mA to 1.5A	12	35	12	80	mV	
		I _O = 250mA to 750mA	4	21	4	75		
	V _{IN} = -23V I _O = 5mA to I _{MAX} T _J = -55 to 150°C	9	75	9	150			
I _Q Quiescent Current	I _O ≤ 0.5 I _{MAX} V _{IN} = -23V T _J = -55 to 150°C		1	1.9	1	1.9	mA	
			1	2	1	2		
ΔI _Q Quiescent Current Change	I _O = 5mA to I _{MAX} V _{IN} = -23V T _J = -55 to 150°C		0.2	0.4	0.2	0.4	mA	
			0.2	0.5	0.2	0.5		
	I _O ≤ 0.5 I _{MAX}	V _{IN} = -17.5V to -30V	0.1	0.4	0.1	0.4		
		V _{IN} = -18.5V to -30V T _J = -55 to 150°C	0.1	0.5	0.1	1.0		
V _N Output Noise Voltage	f = 10Hz to 100kHz V _{IN} = -23V	90	1200	90	1200	μV		
ΔV _{IN} / ΔV _O Ripple Rejection	f = 120Hz V _{IN} = -18.5V to -28.5V	I _O ≤ I _{MAX}	56	70	54	70	dB	
		I _O ≤ 0.5 I _{MAX} T _J = -55 to 150°C	56	70	54	70		
Dropout Voltage	I _O = I _{MAX}	1.1	2.3	1.1	2.3	V		
R _O Output Resistance	f = 1 kHz	9		9		mΩ		
I _{sc} Short Circuit Current	V _{IN} = -35V	0.6	1.2	0.6	1.2	A		
I _{pk} Peak Output Current	V _{IN} = -23V	2.4	3.3	2.4	3.3			
Average Temperature Coefficient of V _O	I _O = 5mA	0.6	6	0.6	6	mV/°C		
Input Voltage required to maintain line regulation	I _O ≤ I _{MAX}	-17.5		-17.5		V		

1) All characteristics are measured with a capacitor across the input of 0.22μF and a capacitor across the output of 0.1μF.


All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques (t_p ≤ 10ms, δ ≤ 5%). Output voltage changes due to changes in internal temperature must be taken into account separately.

2) Test Conditions unless otherwise stated: P_{MAX} = 10W for TO-220SM, P_{MAX} = 1W for Cerdip, P_{MAX} = 20W for all other package devices
I_{MAX} = 1.0A, T_J = 25°C

APPLICATIONS INFORMATION




Fixed Output Regulator



Adjustable Output Regulator

$$V_{OUT} \approx V_{REG} \frac{(R1+R2)}{R1}$$



Current Regulator

$$I_{OUT} = \frac{V_{REG}}{R1} + I_Q$$

- * Required if the regulator is located far from the power supply.
- ** Required for stability. 25µF electrolytic may be substituted.

Order Information

Part Number	K-Pack (TO-3)	R-Pack (TO-66)	G/IG-Pack (TO-257)	SG-Pack SMD1	J-Pack 8 Pin Cerdip	Temp. Range	Note: To order, add the package identifier to the part number. eg. IP7900AK IP120SG
IP7900A	✓	✓	✓	✓	✓	-55 to +150°C	
IP7900	✓	✓	✓	✓	✓	"	
IP120A	✓	✓	✓	✓	✓	"	
IP120	✓	✓	✓	✓	✓	"	
LM120	✓	✓	✓	✓	✓	"	