

SANYO	No.1066A	2SC3142
		NPN Epitaxial Planar Silicon Transistor High-Frequency General-Purpose Amp Applications

Features

- . FBET series.
- . Compact package enabling compactness of sets.
- . High f_T and small c_{re} . ($f_T=750\text{MHz typ}$, $c_{re}=0.6 \text{ typ}$)

Absolute Maximum Ratings at $T_a=25^\circ\text{C}$

			unit
Collector to Base Voltage	V_{CB0}	25	V
Collector to Emitter Voltage	V_{CE0}	20	V
Emitter to Base Voltage	V_{EB0}	3	V
Collector Current	I_C	30	mA
Collector Dissipation	P_C	150	mW
Junction Temperature	T_j	125	$^\circ\text{C}$
Storage Temperature	T_{stg}	-40 to +125	$^\circ\text{C}$

Electrical Characteristics at $T_a=25^\circ\text{C}$

			min	typ	max	unit
Collector Cutoff Current	I_{CB0}	$V_{CB}=10\text{V}, I_E=0$			0.1	μA
Emitter Cutoff Current	I_{EB0}	$V_{EB}=3\text{V}, I_C=0$			0.1	μA
DC Current Gain	h_{FE}	$V_{CE}=6\text{V}, I_C=1\text{mA}$	40*		180*	
Gain-Bandwidth Product	f_T	$V_{CE}=6\text{V}, I_C=4\text{mA}$	450	750		MHz
Feedback Capacitance	c_{re}	$V_{CB}=6\text{V}, f=1\text{MHz}$	0.6	0.9		pF
B to C Time Constant	$r_{bb}'C_C$	$V_{CB}=6\text{V}, I_C=1\text{mA}, f=31.9\text{MHz}$			19	ps
Noise Figure	NF	$V_{CE}=6\text{V}, I_C=1\text{mA}, f=100\text{MHz}$	2.2			dB
Power Gain	PG	$V_{CE}=6\text{V}, I_C=1\text{mA}, f=100\text{MHz}$		28		dB


* The 2SC3142 is classified as follows according to h_{FE} at 1mA:

40	2	80	60	3	120	90	4	180
----	---	----	----	---	-----	----	---	-----

(Note) Marking : J

h_{FE} rank: 2,3,4

NF, PG Test Circuit




L1 : 1mm ϕ plated wire 10mm ϕ 5T, pitch 15mm, tap : 2T from base.

L2 : 1mm ϕ plated wire 10mm ϕ 7T, pitch 10mm, tap : 2T from V_C .

L3 : 1mm ϕ enameled wire 10mm ϕ 3T, pitch 10mm.









Unit (Capacitance : F)









Package Dimensions 2018A
(unit:mm)













C: Collector
B: Base
E: Emitter

SANYO: CP









- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.