



# 1SV268

## Silicon Epitaxial Type Transmitting, Receiving Antenna-switch Use PIN Diode


### Features

- Small interterminal capacitance ( $C=0.7\text{pF}$  typ).
- Small forward series resistance ( $r_s=0.5\Omega$  typ).

### Package Dimensions

unit:mm

1163A



### Specifications

#### Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$






Parameter	Symbol	Conditions	Ratings	Unit
Reverse Voltage	$V_R$		50	V
Forward Current	$I_F$		100	mA
Allowable Power Dissipation	P	Mounted on ceramic board (250mm <sup>2</sup> ×0.8mm)	1.0	W
Junction Temperature	$T_j$		125	°C
Storage Temperature	$T_{stg}$		-55 to +125	°C

#### Electrical Characteristics at $T_a = 25^\circ\text{C}$


Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Reverse Voltage	$V_R$	$I_R=10\mu\text{A}$	50			V
Reverse Current	$I_R$	$V_R=45\text{V}$			0.5	$\mu\text{A}$
Forward Voltage	$V_F$	$I_F=100\text{mA}$		0.87	1.0	V
Interterminal Capacitance	C	$V_R=40\text{V}$ , $f=1\text{MHz}$		0.7	1.0	pF
Series Resistance	$r_s$	$I_F=50\text{mA}$ , $f=470\text{MHz}$		0.5	0.7	$\Omega$
Thermal Resistance	$R_{th-a}$	Mounted on ceramic board 250mm <sup>2</sup> ×0.8mm		120		°C/W

- Marking:VD

# 1SV268



## S Parameter



- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
  - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
  - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of May, 1998. Specifications and information herein are subject to change without notice.