

GP2S09/GP2S24/ GP2S26/GP2S27

Subminiature Photointerrupter

■ Features

1. Compact and thin

GP2S09: Compact DIP long lead type

GP2S24: Compact DIP type

GP2S26: Flat lead type



GP2S27: Mini-flat package type

2. Optimum detection distance: 0.6 to 0.8mm

3. Visible light cut-off type

■ Outline Dimensions

(Unit : mm)



■ Absolute Maximum Ratings


(Ta = 25°C)

Parameter		Symbol	Rating	Unit
Input	Forward current	I _F	50	mA
	Reverse voltage	V _R	6	V
	Power dissipation	P	75	mW
Output	Collector-emitter voltage	V _{CEO}	35	V
	Emitter-collector voltage	V _{ECO}	6	V
	Collector current	I _C	20	mA
	Collector power dissipation	P _C	75	mW
	Total power dissipation	P _{tot}	100	mW
	Operating temperature	T _{opr}	- 20 to + 85	°C
	Storage temperature	T _{stg}	- 40 to + 100	°C
	* ¹ Soldering temperature	T _{sol}	260	°C

*1 Within 5 seconds (Soldering areas for each model are shown below)


GP2S09, GP2S24

Soldering area:

The hatched area more than 1mm^{*2} away from the lower edge of package as shown in the figure below.**GP2S26**


Soldering area:

The hatched area more than 2.0mm away from the both edges of package as shown in the figure below.

**GP2S27**

Soldering area

The hatched area more than 0.5mm away from the both edges of package as shown in the figure below.

**■ Electro-optical Characteristics**

(Ta = 25°C)

Parameter		Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Input	Forward voltage	V _F	I _F = 20mA	-	1.2	1.4	V
	Reverse current	I _R	V _R = 6V	-	-	10	μA
Output	Collector dark current	I _{CEO}	V _{CE} = 20V	-	10 ⁻⁹	10 ⁻⁷	A
Transfer characteristics	* ³ Collector current	I _C	I _F = 4mA, V _{CE} = 2V	20	45	120	μA
	Response time	t _r	V _{CE} = 2V, I _C = 100 μA	-	20	100	μs
		t _f	R _L = 1kΩ, d = 1mm	-	20	100	μs
	* ⁴ Leak current	I _{LEAK}	I _F = 4mA, V _{CE} = 2V	-	-	0.1	μA

*3 The condition and arrangement of the reflective object are shown below.


*4 Without reflective object

The ranking of collector current shall be classified into the following 6 ranks.


(GP2S09, GP2S24, GP2S26, GP2S27)

Rank	Collector-current I _C (μA)
* ⁵ A	20 to 42
B	34 to 71
C	58 to 120
A or B	20 to 71
B or C	34 to 120
A, B or C	20 to 120


*5 GP2S24 and GP2S26 and GP2S27 don't have A rank.

Test Condition and Arrangement for Collector Current


**Fig. 1 Forward Current vs.
Ambient Temperature**




**Fig. 2 Power Dissipation vs.
Ambient Temperature**




**Fig. 3 Forward Current vs.
Forward Voltage**



**Fig. 4 Collector Current vs.
Forward Current**



**Fig. 5 Collector Current vs.
Collector-Emitter Voltage**



**Fig. 6 Relative Collector Current vs.
Ambient Temperature**




Fig. 7 Collector Dark Current vs. Ambient Temperature




Fig. 9 Response Time vs. Load Resistance (GP2S24 / GP2S26/GP2S27)




Fig.10 Relative Collector Current vs. Distance between Sensor and Al Evaporation Glass





Fig. 8 Response Time vs. Load Resistance (GP2S09)



Test Circuit for Response Time




Fig.11 Relative Collector Current vs. Card Moving Distance (1)




Fig.12 Relative Collector Current vs. Card Moving Distance (2)




Fig.13-a Frequency Response (GP2S09)





Fig.14 Spectral Sensitivity (Detecting Side)



Test Condition for Distance & Detecting Position Characteristics (EX : GP2S24)





Fig.13-b Frequency Response (GP2S24 / GP2S26 / GP2S27)



- Please refer to the chapter "Precautions for Use".