


# SHINDENGEN

## Switching Power Transistor

# 2SC5382

## 6A NPN

### OUTLINE DIMENSIONS



### RATINGS

#### Absolute Maximum Ratings


| Item                         | Symbol           | Conditions                     | Ratings   | Unit |
|------------------------------|------------------|--------------------------------|-----------|------|
| Storage Temperature          | T <sub>stg</sub> |                                | -55 ~ 150 |      |
| Junction Temperature         | T <sub>j</sub>   |                                | 150       |      |
| Collector to Base Voltage    | V <sub>CBO</sub> |                                | 1200      | V    |
| Collector to Emitter Voltage | V <sub>CEO</sub> |                                | 550       | V    |
| Emitter to Base Voltage      | V <sub>EBO</sub> |                                | 9         | V    |
| Collector Current DC         | I <sub>C</sub>   |                                | 6         | A    |
| Collector Current Peak       | I <sub>CP</sub>  |                                | 12        |      |
| Base Current DC              | I <sub>B</sub>   |                                | 3         | A    |
| Base Current Peak            | I <sub>BP</sub>  |                                | 6         |      |
| Total Transistor Dissipation | P <sub>T</sub>   |                                | 40        | W    |
| Dielectric Strength          | V <sub>dis</sub> | Terminals to case, AC 1 minute | 2         | kV   |
| Mounting Torque              | TOR              | (Recommended torque)           | 0.5(0.3)  | N·m  |

#### Electrical Characteristics (T<sub>c</sub>=25 °C)

| Item                                    | Symbol                | Conditions                                     | Ratings  | Unit |
|---|-----------------------|--|----------|------|
| Collector to Emitter Sustaining Voltage | V <sub>CEO(sus)</sub> | I <sub>C</sub> = 0.1A                          | Min 550  | V    |
| Collector Cutoff Current                | I <sub>CBO</sub>      | V <sub>CB</sub> = 1200V                        | Max 0.1  | mA   |
|   | I <sub>CEO</sub>      | V <sub>CE</sub> = 550V                         | Max 0.1  |      |
| Emitter Cutoff Current                  | I <sub>EBO</sub>      | V <sub>EB</sub> = 9V                           | Max 0.1  | mA   |
| DC Current Gain                         | h <sub>FE</sub>       | V <sub>CE</sub> = 5V, I <sub>C</sub> = 3A      | Min 10   |      |
|   | h <sub>FEL</sub>      | V <sub>CE</sub> = 5V, I <sub>C</sub> = 1mA     | Min 10   |      |
| Collector to Emitter Saturation Voltage | V <sub>CE(sat)</sub>  | I <sub>C</sub> = 3A                            | Max 1.0  | V    |
| Base to Emitter Saturation Voltage      | V <sub>BE(sat)</sub>  | I <sub>B</sub> = 0.6A                          | Max 1.5  | V    |
| Thermal Resistance                      | θ <sub>jc</sub>       | Junction to case                               | Max 3.13 | /W   |
| Turn on Time                            | t <sub>on</sub>       | I <sub>C</sub> = 3A                            | Max 1.3  | μs   |
| Storage Time                            | t <sub>s</sub>        | I <sub>B1</sub> = 0.6A, I <sub>B2</sub> = 1.2A | Max 4.0  |      |
| Fall Time                               | t <sub>f</sub>        | R <sub>L</sub> = 50 Ω, V <sub>BB2</sub> = 4V   | Max 0.3  |      |

# 2SC5382

$h_{FE} - I_C$



100

DC Current Gain  $h_{FE}$

10

1

0.001

0.01

0.1

1

10 12

$V_{CE} = 5V$

$T_C = 150^\circ C$

100°C

50°C

25°C

0°C

-25°C


-55°C

Collector Current  $I_C$  [A]




# 2SC5382

## Switching Time - $I_C$




# 2SC5382 Switching Time - $V_{CC}$




# 2SC5382

## Switching Time - Tc



# 2SC5382 Forward Bias SOA




## 2SC5382 Collector Current Derating





2SC5382

Reverse Bias SOA



## 2SC5382 Transient Thermal Impedance

