


**2SC4876**  
**(TP30S4)**

**30A NPN**

### OUTLINE DIMENSIONS



### RATINGS

#### Absolute Maximum Ratings


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T <sub>stg</sub>		-55 ~ 150	
Junction Temperature	T <sub>j</sub>		150	
Collector to Base Voltage	V <sub>CB0</sub>		60	V
Collector to Emitter Voltage	V <sub>CE0</sub>		40	V
Emitter to Base Voltage	V <sub>EBO</sub>		7	V
Collector Current DC	I <sub>C</sub>		30	A
Collector Current Peak	I <sub>CP</sub>		60	A
Base Current DC	I <sub>B</sub>		4	A
Base Current Peak	I <sub>BP</sub>		6	A
Total Transistor Dissipation	P <sub>T</sub>	T <sub>C</sub> = 25	45	W
Dielectric Strength	V <sub>dis</sub>	Terminal to case, AC 1 minute	2	kV
Mounting Torque	TOR	(Recommended torque : 0.3N·m )	0.5	N·m

#### Electrical Characteristics (T<sub>c</sub>=25 )

Item	Symbol	Conditions	Ratings	Unit
Collector to Emitter Sustaining Voltage	V <sub>CE0(sus)</sub>	I <sub>C</sub> = 0.1A	Min 40	V
Collector Cutoff Current	I <sub>CBO</sub>	At rated Voltage	Max 0.1	mA
	I <sub>CEO</sub>		Max 0.1	
Emitter Cutoff Current	I <sub>EBO</sub>	At rated Voltage	Max 0.1	mA
DC Current Gain	h <sub>FE</sub>	V <sub>CE</sub> = 2V, I <sub>C</sub> = 15A	Min 100	
Collector to Emitter Saturation Voltage	V <sub>CE(sat)</sub>	I <sub>C</sub> = 15A	Max 0.3	V
Base to Emitter Saturation Voltage	V <sub>BE(sat)</sub>	I <sub>B</sub> = 0.75A	Max 1.2	V
Thermal Resistance	θ <sub>JC</sub>	Junction to case	Max 2.78	/W
Transition Frequency	f <sub>T</sub>	V <sub>CE</sub> = 10V, I <sub>C</sub> = 3A	TYP 50	MHz
Turn on Time	t <sub>on</sub>	I <sub>C</sub> = 15A I <sub>B1</sub> = 1.5A, I <sub>B2</sub> = 1.5A R <sub>L</sub> = 2 Ω, V <sub>BB2</sub> = 4V	Max 0.3	μs
Storage Time	t <sub>s</sub>		Max 1.5	
Fall Time	t <sub>f</sub>		Max 0.5	

# 2SC4876


$h_{FE} - I_C$






# 2SC4876

## Switching Time - $I_C$




# 2SC4876

## Switching Time - Tc




## 2SC4876 Transient Thermal Impedance




# 2SC4876

# Forward Bias SOA



## 2SC4876 Collector Current Derating





2SC4876

Reverse Bias SOA

