

2SK2701

External dimensions 1 FM20

Absolute Maximum Ratings (Ta = 25°C)

Symbol	Ratings	Unit
V _{DSS}	450	V
V _{GSS}	±30	V
I _D	±7	A
I _D (pulse) *1	±28	A
P _D	35 (T _c = 25°C)	W
E _{AS} *2	130	mJ
I _{AS}	7	A
T _{ch}	150	°C
T _{stg}	-55 to +150	°C

*1: P_W ≤ 100μs, duty cycle ≤ 1%
 *2: V_{DD} = 30V, L = 5mH, I_L = 7A, unclamped, R_G = 50Ω,
 See Figure 1 on Page 5.

Electrical Characteristics (Ta = 25°C)

Symbol	Ratings			Unit	Conditions
	min	typ	max		
V _{(BR) DSS}	450			V	I _D = 100μA, V _{GS} = 0V
I _{GSS}			±100	nA	V _{GS} = ±30V
I _{DSS}			100	μA	V _{DS} = 450V, V _{GS} = 0V
V _{TH}	2.0	3.0	4.0	V	V _{DS} = 10V, I _D = 1mA
Re (yfs)	3.5	5		S	V _{DS} = 20V, I _D = 3.5A
R _{DS (on)}		0.84	1.10	Ω	V _{GS} = 10V, I _D = 3.5A
C _{iss}		720		pF	V _{DS} = 10V, f = 1.0MHz, V _{GS} = 0V
C _{oss}		150		pF	
C _{rss}		65		pF	
t _{d (on)}		25		ns	I _D = 3.5A, V _{DD} = 200V, R _L = 57Ω, V _{GS} = 10V, See Figure 2 on Page 5.
t _r		40		ns	
t _{d (off)}		70		ns	
t _f		50		ns	
V _{SD}		1.0	1.5	V	

