

Absolute maximum ratings

($T_a=25^\circ\text{C}$)


Symbol	Ratings	Unit
V_{CB0}	550	V
V_{CE0}	550	V
V_{EB0}	6	V
I_c	1	A
I_{CP}	2 (PW \leq 1ms, Du \leq 25%)	A
I_B	0.5	A
P_T	3 ($T_a=25^\circ\text{C}$)	W
	15 ($T_c=25^\circ\text{C}$)	
T_j	150	$^\circ\text{C}$
T_{stg}	-40 to +150	$^\circ\text{C}$

Electrical characteristics

($T_a=25^\circ\text{C}$)


Symbol	Specification			Unit	Conditions
	min	typ	max		
I_{CB0}			100	μA	$V_{CB}=550\text{V}$
I_{EB0}		75	150	mA	$V_{EB}=6\text{V}$
V_{CE0}	550			V	$I_c=100\mu\text{A}$
h_{FE}	200	400	1000		$V_{CE}=4\text{V}$, $I_c=500\text{mA}$
$V_{CE(sat)}$		1.0	1.5	V	$I_c=500\text{mA}$, $I_B=10\text{mA}$
$V_{BE(sat)}$		1.5	2.2	V	
V_{FEC}		1.1	1.5	V	$I_{FEC}=1\text{A}$
t_{on}		0.5		μs	$V_{CC}\doteq 200\text{V}$, $I_c=500\text{mA}$,
t_{stg}		3.5		μs	
t_f		0.7		μs	$I_{B1}=-I_{B2}=10\text{mA}$
f_T		15		MHz	$V_{CE}=12\text{V}$, $I_E=-0.2\text{A}$
C_{ob}		35		pF	$V_{CB}=10\text{V}$, $f=1\text{MHz}$

Equivalent circuit diagram




Characteristic curves


I_c - V_{CE} Characteristics (Typical)




h_{FE} - I_c Characteristics (Typical)




h_{FE} - I_c Temperature Characteristics (Typical)




$V_{CE(sat)}$ - I_c Temperature Characteristics (Typical)




$V_{CE(sat)}$ - I_B Characteristics (Typical)




I_c - V_{BE} Temperature Characteristics (Typical)



θ_{j-a} -PW Characteristics



P_r - T_a Characteristics



Safe Operating Area (SOA)

