

IGBT MODULE

GCA150BA60



UL;E76102 (M)

SanRex IGBT Module **GCA150BA60** is designed for high speed, high current switching applications. This Module is electrically isolated and contains two IGBTs connected in series with a fast switching, soft recovery diode ($t_{rr}=0.1 \mu s$) reverse connected across each IGBT.



- $I_C=150A$ $V_{CES}=600V$
- $V_{CES(sat)}=2.4V$ Typ
- $t_f=0.10 \mu s$ Typ
- Soft recovery diode

(Applications)

Inverter for motor control (VVF)

UPS, AC servo

DC power supply, Welder



Unit : mm

Maximum Ratings

(Unless otherwise $T_j=25^\circ C$)

Symbol	Item		Conditions	Ratings		Unit
				GCA150BA60		
V_{CES}	Collector-Emitter Voltage		with gate terminal shorted to emitter	600		V
V_{GES}	Gate-Emitter Voltage		with collector shorted to emitter	± 20		V
I_C	Collector Current	DC		150		A
I_{CP}		Pulse (1 ms)		300		
$-I_C$	Reverse Collector Current			150		A
P_T	Total Power Dissipation		$T_c=25^\circ C$	600		W
T_j	Junction Temperature			150		$^\circ C$
T_{stg}	Storage Temperature			$-40 \sim +125$		$^\circ C$
V_{ISO}	Isolation Voltage (R.M.S.)		A.C. 1 minute	2500		V
	Mounting Torque	Mounting (M6)	Recommended Value 2.5~3.9 (25~40)	4.7 (48)		N·m (kgf·cm)
		Terminal (M5)	Recommended Value 1.5~2.5 (15~25)	2.7 (28)		
	Mass		Typical Value	225		g

Electrical Characteristics

(Unless otherwise $T_j=25^\circ C$)

Symbol	Item		Conditions	Ratings			Unit
				Min.	Typ.	Max.	
I_{GES}	Gate Leakage Current		$V_{GE}=\pm 20V, V_{CE}=0V$			± 500	nA
I_{CES}	Collector Cut-Off Current		$V_{CE}=600V, V_{GE}=0V$			1.0	mA
$V_{(BR)CES}$	Collector-Emitter Breakdown Voltage		$V_{GE}=0V, I_C=1 \text{ mA}$	600			V
$V_{GE(th)}$	Gate Threshold Voltage		$V_{CE}=10V, I_C=15 \text{ mA}$	3.0		7.0	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage		$I_C=150A, V_{GE}=15V$		2.4	2.8	V
C_{ies}	Input Capacitance		$V_{CE}=10V, V_{GE}=0V, f=1 \text{ MHz}$		9	15	nF
t_r	Switching Time	Rise Time	$I_C=150A, V_{GE}=+15V/-5V$ $V_{CC}=300V, R_G=4 \Omega$		0.10	0.20	μs
$t_d(on)$		Turn-on Delay Time			0.20	0.40	
t_f		Fall Time			0.10	0.20	
$t_d(off)$		Turn-off Delay Time			0.40	0.80	
V_{ECS}	Emitter-Collector Voltage		$-I_C=150A, V_{GE}=0V$		2.30	2.80	V
t_{rr}	Reverse Recovery Time		$-I_C=150A, V_{GE}=-10V, di/dt=300A/\mu s$		0.1	0.15	μs
$R_{th(j-c)}$	Thermal Resistance		IGBT-Case			0.21	$^\circ C/W$
			Diode-Case			0.50	

